



**Supporting Document
Mandatory Technical Document**

Evaluation Activities for Network Device
cPP

March-2018

Version 2.0 + Errata 20180314

CCDB-2017-<month TBD>-<number TBD>

Deleted: <object>

Deleted: February-2015

Deleted: 1

Deleted: 2015-01-001

Foreword

This is a supporting document, intended to complement the Common Criteria version 3 and the associated Common Evaluation Methodology for Information Technology Security Evaluation.

Supporting documents may be “Guidance Documents”, that highlight specific approaches and application of the standard to areas where no mutual recognition of its application is required, and as such, are not of normative nature, or “Mandatory Technical Documents”, whose application is mandatory for evaluations whose scope is covered by that of the supporting document. The usage of the latter class is not only mandatory, but certificates issued as a result of their application are recognized under the CCRA.

This supporting document has been developed by the Network International Technical Community (NDFW-iTC) and is designed to be used to support the evaluations of products against the cPPs identified in section 1.1.

Technical Editor: Network International Technical Community (NDFW-iTC)

Document history:

V2.0 + Errata 20180314,	14 March 2018 (published version incorporating editorial changes from evaluator review)
V2.0,	5 May 2017 (published version)
V1.1,	21 July 2016 (Updated draft published for public review)
V1.0,	27 February 2015 (published version)
V0.4,	26 January 2015 (incorporates changes due to comments received from CCDB review)
V0.3,	17 October 2014 (released version following public review, submitted for CCDB review)
V0.2,	13 October 2014 (internal draft in response to public review comments, for iTC review)
V0.1,	5 September 2014 (Initial release for public review)

General Purpose: See section 1.1.

Field of special use: This Supporting Document applies to the evaluation of TOEs claiming conformance with the collaborative Protection Profile for Network Devices [NDcPP] and collaborative Protection Profile for Stateful Traffic Filter Firewalls [FWcPP].

Acknowledgements:

This Supporting Document was developed by the Network international Technical Community with representatives from industry, Government agencies, Common Criteria Test Laboratories, and members of academia.

Deleted:

Deleted:

Deleted:

Deleted:

Deleted:

Deleted: Section Break (Next Page)

Deleted: <object><object><object>

Table of contents

Table of Contents

1 INTRODUCTION..... 8

1.1 Technology Area and Scope of Supporting Document 8

1.2 Structure of the Document 8

1.3 Application of this Supporting Document..... 9

1.4 Terminology 10

1.4.1 Glossary 10

1.4.2 Acronyms 10

2 EVALUATION ACTIVITIES FOR SFRS..... 11

2.1 Security Audit (FAU) 12

2.1.1 FAU_GEN.1 Audit data generation 12

2.1.2 FAU_GEN.2 User identity association 13

2.1.3 FAU_STG_EXT.1 Protected audit event storage..... 13

2.2 Cryptographic Support (FCS)..... 16

2.2.1 FCS_CKM.1 Cryptographic Key Generation 16

2.2.2 FCS_CKM.2 Cryptographic Key Establishment..... 18

2.2.3 FCS_CKM.4 Cryptographic Key Destruction..... 21

2.2.4 FCS_COP.1/DataEncryption Cryptographic Operation (AES Data Encryption/Decryption)..... 23

2.2.5 FCS_COP.1/SigGen Cryptographic Operation (Signature Generation and Verification)..... 27

2.2.6 FCS_COP.1/Hash Cryptographic Operation (Hash Algorithm) 28

2.2.7 FCS_COP.1/KeyedHash Cryptographic Operation (Keyed Hash Algorithm) 30

2.2.8 FCS_RBG_EXT.1 Extended: Cryptographic Operation (Random Bit Generation) 30

2.3 Identification and Authentication (FIA)..... 31

2.3.1 FIA_AFL.1 Authentication Failure Management 31

2.3.2 FIA_PMG_EXT.1 Password Management 33

2.3.3 FIA_UIA_EXT.1 User Identification and Authentication 33

2.3.4 FIA_UAU_EXT.2 Password-based Authentication Mechanism 35

2.3.5 FIA_UAU.7 Protected Authentication Feedback 35

2.4 Security management (FMT) 35

2.4.1 General requirements for distributed TOEs..... 35

2.4.2 FMT_MOF.1/ManualUpdate 35

2.4.3 FMT_MTD.1/CoreData Management of TSF Data..... 36

2.4.4 FMT_SMF.1 Specification of Management Functions..... 36

2.4.5 FMT_SMR.2 Restrictions on security roles 37

2.5 Protection of the TSF (FPT) 38

2.5.1 FPT_SKP_EXT.1 Protection of TSF Data (for reading of all pre-shared.

- Deleted: ¶
- Deleted: Glossary→9
- Deleted: EVALUATION ACTIVITIES FOR SFRS→10
- Deleted: Security Audit (FAU)
- Deleted: FAU_GEN.1 Audit data generation→10
- Deleted: FAU_GEN.2 User identity association→11
- Deleted: FAU_STG_EXT.1 Protected audit trail storage→11
- Deleted: STG_EXT
- Deleted: Protected audit event storage→11
- Deleted: STG_EXT
- Deleted: Counting lost audit data
- Deleted:
- Deleted: 3 Display warning for local
- Deleted: space
- Deleted: 14
- Deleted: 14
- Deleted: 16
- Deleted: 19
- Deleted: (1)
- Deleted: Encryption/Decryption→20
- Deleted: ¶
- FCS_COP.1(2) Cryptographic Operation (Signature Generation and Verification→23¶
- FCS_COP.1(3) Cryptographic Operation (Hash Algorithm)→24¶
- FCS_COP.1(4) Cryptographic Operation (Keyed Hash Algorithm)→25¶
- FCS_RBG_EXT.1 Extended: Cryptographic Operation (Random Bit Generation)→26¶
- FCS_HTTPS_EXT.1 HTTPS Protocol→27¶
- FCS_IPSEC_EXT.1 IPsec Protocol→27¶
- FCS_SSHC_EXT.1 SSH Client→36¶
- FCS_SSHS_EXT.1 SSH Server→39¶
- FCS_TLSC_EXT.1 Extended: TLS Client Protocol→42¶
- FCS_TLSC_EXT.2 Extended: TLS Client Protocol with authentication→46¶
- FCS_TLSS_EXT.1 Extended: TLS Server Protocol→50¶
- FCS_TLSS_EXT.2 Extended: TLS Server Protocol with mutual authentication→52¶
- Identification and Authentication (FIA)→55¶**
- FIA_PMG_EXT.1 Password Management→55¶
- FIA_UIA_EXT.1 User Identification and Authentication→56¶
- FIA_UAU_EXT.2 Password-based Authentication Mechanism→56¶
- FIA_UAU.7 Protected Authentication Feedback→57¶
- FIA_X509_EXT.1 X.509 Certificate Validation→57¶
- FIA_X509_EXT.2 X.509 Certificate Authentication→58¶
- FIA_X509_EXT.3 Extended: X509 Certificate Requests→59¶
- Security management (FMT)→60¶**
- FMT_MOF.1(1)/TrustedUpdate→60¶
- FMT_MOF.1(2)/TrustedUpdate→60¶
- FMT_MOF.1(1)/Audit→60¶
- FMT_MOF.1(2)/Audit→61¶
- FMT_MOF.1(1)/AdminAct→61¶
- FMT_MOF.1(2)/AdminAct→61¶
- FMT_MOF.1/LocSpace Management of security ... [1]

Table of contents

symmetric and private keys).....	38
2.5.2 FPT APW EXT.1 Protection of Administrator Passwords.....	38
2.5.3 FPT TST EXT.1 TSF testing.....	38
2.5.4 FPT TUD EXT.1 Trusted Update.....	39
2.5.5 FPT STM EXT.1 Reliable Time Stamps.....	44
2.6 TOE Access (FTA).....	45
2.6.1 FTA SSL EXT.1 TSF-initiated Session Locking.....	45
2.6.2 FTA SSL.3 TSF-initiated Termination.....	45
2.6.3 FTA SSL.4 User-initiated Termination.....	45
2.6.4 FTA TAB.1 Default TOE Access Banners.....	46
2.7 Trusted path/channels (FTP).....	46
2.7.1 FTP ITC.1 Inter-TSF trusted channel.....	46
2.7.2 FTP TRP.1/Admin Trusted Path.....	47
3 EVALUATION ACTIVITIES FOR OPTIONAL REQUIREMENTS.....	49
3.1 Security Audit (FAU).....	49
3.1.1 FAU STG.1 Protected audit trail storage.....	49
3.1.2 FAU STG EXT.2/LocSpace Counting lost audit data.....	50
3.1.3 FAU STG.3/LocSpace Action in case of possible audit data loss.....	50
3.2 Identification and Authentication (FIA).....	51
3.2.1 FIA X509 EXT.1/ITT X.509 Certificate Validation.....	51
3.3 Security management (FMT).....	53
3.3.1 FMT MOF.1/Services.....	53
3.3.2 FMT MTD.1/CryptoKeys Management of TSF Data.....	54
3.4 Protection of the TSF (FPT).....	54
3.4.1 FPT ITT.1 Basic internal TSF data transfer protection.....	54
3.5 Trusted path/channels (FTP).....	55
3.5.1 FTP TRP.1/Join Trusted Path.....	55
3.6 Communication (FCO).....	57
3.6.1 FCO CPC EXT.1 Component Registration Channel Definition.....	57
4 EVALUATION ACTIVITIES FOR SELECTION-BASED REQUIREMENTS ...	63
4.1 Cryptographic Support (FCS).....	63
4.1.1 FCS DTLSC EXT.1 Extended: DTLS Client Protocol.....	63
4.1.2 FCS DTLSC EXT.2 Extended: DTLS Client Protocols with authentication.....	67
4.1.3 FCS DTLSS EXT.1 Extended: DTLS Server Protocol.....	71
4.1.4 FCS DTLSS EXT.2 Extended: DTLS Server Protocol with mutual authentication.....	74
4.1.5 FCS HTTPS EXT.1 HTTPS Protocol.....	78
4.1.6 FCS IPSEC EXT.1 IPsec Protocol.....	78
4.1.7 FCS SSHC EXT.1 SSH Client.....	88
4.1.8 FCS SSHS EXT.1 SSH Server.....	92

Deleted: <object>

Deleted: FTP_TRP.1 Trusted Path-71

Deleted: EVALUATION ACTIVITIES FOR SARS-73

Deleted: <#>ASE: Security Target Evaluation-73[¶]
<#>Conformance claims (ASE_CCL.1)-73[¶]
<#>ADV: Development-74[¶]
<#>Basic Functional Specification (ADV_FSP.1)-74[¶]
<#>AGD: Guidance Documents-75[¶]
<#>Operational User Guidance (AGD_OPE.1)-75[¶]
<#>Preparative Procedures (AGD_PRE.1)-76[¶]
<#>ATE: Tests-77[¶]
<#>Independent Testing - Conformance (ATE_IND.1)-77[¶]
<#>AVA: Vulnerability Assessment-78[¶]
<#>Vulnerability Survey (AVA_VAN.1)-78[¶]
<#>REQUIRED SUPPLEMENTARY INFORMATION-80[¶]
<#>REFERENCES-81[¶]
<#>VULNERABILITY ANALYSIS-82[¶]
<#>Introduction-82[¶]

Table of contents

4.1.9 FCS_TLSC_EXT.1 Extended: TLS Client Protocol.....96
4.1.10 FCS_TLSC_EXT.2 Extended: TLS Client Protocol with authentication99
4.1.11 FCS_TLSS_EXT.1 Extended: TLS Server Protocol.....103
4.1.12 FCS_TLSS_EXT.2 Extended: TLS Server Protocol with mutual authentication,
105
4.2 Identification and Authentication (FIA)109
4.2.1 FIA_X509_EXT.1/Rev_X.509 Certificate Validation.....109
4.2.2 FIA_X509_EXT.2 X.509 Certificate Authentication111
4.2.3 FIA_X509_EXT.3 Extended: X509 Certificate Requests.....112
4.3 Protection of the TSF (FPT)112
4.3.1 FPT_TST_EXT.2 Self tests based on certificates112
4.3.2 FPT_TUD_EXT.2 Trusted Update based on certificates113
4.4 Security management (FMT)114
4.4.1 FMT_MOF.1/AutoUpdate.....114
4.4.2 FMT_MOF.1/Functions Management of security functions behaviour.....114
5 EVALUATION ACTIVITIES FOR SARS117
5.1 ASE: Security Target Evaluation.....117
5.1.1 General ASE.....117
5.1.2 TOE summary specification (ASE_TSS.1) for Distributed TOEs.....117
5.2 ADV: Development.....118
5.2.1 Basic Functional Specification (ADV_FSP.1).....118
5.3 AGD: Guidance Documents120
5.3.1 Operational User Guidance (AGD_OPE.1)121
5.3.2 Preparative Procedures (AGD_PRE.1)122
5.4 ALC: Life-cycle Support.....123
5.4.1 Labelling of the TOE (ALC_CMC.1)123
5.4.2 TOE CM coverage (ALC_CMS.1).....123
5.5 ATE: Tests.....123
5.5.1 Independent Testing – Conformance (ATE_IND.1).....123
5.6 AVA: Vulnerability Assessment.....124
5.6.1 Vulnerability Survey (AVA_VAN.1).....124
6 REQUIRED SUPPLEMENTARY INFORMATION.....128
7 REFERENCES.....129
A. VULNERABILITY ANALYSIS132
A.1 Sources of vulnerability information132
A.1.1 Type 1 Hypotheses – Public-Vulnerability-Based.....132

Deleted: Additional Documentation –82

Deleted: Sources of vulnerability information –83

Deleted: Process for Evaluator Vulnerability Analysis –85

Deleted: Reporting –86

Deleted: Public Vulnerability Database Entries for Flaw Hypotheses –87

Deleted: Additional Flaw Hypotheses –87

Deleted: iTC Activities – cPP and Supporting Document Maintenance –87

Deleted: NETWORK DEVICE EQUIVALENCY CONSIDERATIONS –90

Deleted: Introduction –90

Deleted: Evaluator guidance for determining equivalence –90

Deleted: Strategy –92

Deleted: Test presentation/Truth in advertising –93

Deleted: ¶

Table of contents

Deleted: <object>

A.1.2 Type 2 Hypotheses – iTC-Sourced..... 133
A.1.3 Type 3 Hypotheses – Evaluation-Team-Generated..... 133
A.1.4 Type 4 Hypotheses – Tool-Generated..... 133
A.2 Process for Evaluator Vulnerability Analysis..... 135
A.3 Reporting..... 136
A.4 Public Vulnerability Sources..... 138
A.5 Additional Flaw Hypotheses..... 139
B. NETWORK DEVICE EQUIVALENCY CONSIDERATIONS..... 140
B.1 Introduction..... 140
B.2 Evaluator guidance for determining equivalence..... 140
B.2.1 Strategy..... 140
B.2.2 Guidance for Network Devices..... 141
B.3 Test presentation/Truth in advertising..... 143
B.4 Evaluating additional components for a distributed TOE..... 143
B.4.1 Evaluator Actions for Assessing the ST..... 144
B.4.2 Evaluator Actions for Assessing the Guidance Documentation..... 144
B.4.3 Evaluator Actions for Testing the TOE..... 145

List of tables

List of tables

Table 1: Mapping of ADV_FSP.1 CEM Work Units to Evaluation Activities..... 119
Table 2: Mapping of AVA_VAN.1 CEM Work Units to Evaluation Activities 126
Table 3: Evaluation Equivalency Analysis..... 143

Deleted: List of tables
Table 1 - Evaluation Equivalency Analysis-92
Introduction

1 Introduction

1.1 Technology Area and Scope of Supporting Document

1 This Supporting Document defines the Evaluation Activities associated with the collaborative Protection Profile for Network Devices [NDcPP].

2 The Network Device technical area has a number of specialised aspects, such as those relating to the secure implementation and use of protocols, and to the particular ways in which remote management facilities need to be assessed across a range of different physical and logical interfaces for different types of infrastructure devices. This degree of specialisation, and the associations between individual SFRs in the cPP, make it important for both efficiency and effectiveness that evaluation activities are given more specific interpretations than those found in the generic CEM activities.

3 This Supporting Document is mandatory for evaluations of products that claim conformance to any of the following cPP(s):

- a) collaborative Protection Profile for Network Devices [NDcPP]
- b) collaborative Protection Profile for Stateful Traffic Filter Firewalls [FWcPP].

4 Although Evaluation Activities are defined mainly for the evaluators to follow, the definitions in this Supporting Document aim to provide a common understanding for developers, evaluators and users as to what aspects of the TOE are tested in an evaluation against the associated cPPs, and to what depth the testing is carried out. This common understanding in turn contributes to the goal of ensuring that evaluations against the cPP achieve comparable, transparent and repeatable results. In general the definition of Evaluation Activities will also help Developers to prepare for evaluation by identifying specific requirements for their TOE. The specific requirements in Evaluation Activities may in some cases clarify the meaning of SFRs, and may identify particular requirements for the content of Security Targets (especially the TOE Summary Specification), user guidance documentation, and possibly supplementary information (e.g. for entropy analysis or cryptographic key management architecture – see [section 6](#)).

Deleted: section 4

1.2 Structure of the Document

5 Evaluation Activities can be defined for both Security Functional Requirements and Security Assurance Requirements. These are defined in separate sections of this Supporting Document.

6 If any Evaluation Activity cannot be successfully completed in an evaluation then the overall verdict for the evaluation is a 'fail'. In rare cases there may be acceptable reasons why an Evaluation Activity may be modified or deemed not applicable for a particular TOE, but this must be agreed with the Certification Body for the evaluation.

Deleted:

Introduction

7 In general, if all Evaluation Activities (for both SFRs and SARs) are successfully completed in an evaluation then it would be expected that the overall verdict for the evaluation is a 'pass'. To reach a 'fail' verdict when the Evaluation Activities have been successfully completed would require a specific justification from the evaluator as to why the Evaluation Activities were not sufficient for that TOE.

8 Similarly, at the more granular level of Assurance Components, if the Evaluation Activities for an Assurance Component and all of its related SFR Evaluation Activities are successfully completed in an evaluation then it would be expected that the verdict for the Assurance Component is a 'pass'. To reach a 'fail' verdict for the Assurance Component when these Evaluation Activities have been successfully completed would require a specific justification from the evaluator as to why the Evaluation Activities were not sufficient for that TOE.

1.3 Application of this Supporting Document

9 This Supporting Document (SD) defines three types of Evaluation Activities (EAs) – TOE Summary Specification (TSS), Guidance Documentation, and Tests and is designed to be used in conjunction with cPPs. cPPs that rely on this SD will explicitly identify it as a source for their EAs¹. Each security requirement (SFR or SAR) specified in the cPP could have multiple EAs associated with it. The security requirement naming convention is consistent between cPP and SD ensuring a clear one to one correspondence between security requirements and evaluation activities.

10 The cPP and SD are designed to be used in conjunction with each other, where the cPP lists SFRs and SARs and the SD catalogues EAs associated with each SFR and SAR. Some of the SFRs included in the cPP are optional or selection-based. Therefore an ST claiming conformance to the cPP does not necessarily have to include all possible SFRs defined in the cPP.

11 In an ST conformant to the cPP, several operations need to be performed (mainly selections and assignments). Some EAs define separate actions for different selected or assigned values in SFRs. The evaluator shall neither carry out EAs related to SFRs that are not claimed in the ST nor EAs related to specific selected or assigned values that are not claimed in the ST.

12 EAs do not necessarily have to be executed independently from each other. A description in a guidance documentation or one test case, for example, can cover multiple EAs at a time, no matter whether the EAs are related to the same or different SFRs.

¹In general a cPP may reference one or more SDs as sources for the Evaluation Activities for different sets of SFRs.

Deleted: Introduction

Deleted: <object><object><object>

Introduction

1.4 Terminology

1.4.1 Glossary

13 For definitions of standard CC terminology see [CC] part 1.

Term	Meaning
<u>Administrator</u>	See <u>Security Administrator</u>
<u>Assurance</u>	Grounds for confidence that a TOE meets the SFRs [CC1].
<u>Key Chaining</u>	The method of using multiple layers of encryption keys to protect data. A top layer key encrypts a lower layer key which encrypts the data; this method can have any number of layers.
<u>Required Supplementary Information</u>	Information that is not necessarily included in the Security Target or operational guidance, and that may not necessarily be public. Examples of such information could be entropy analysis, or description of a cryptographic key management architecture used in (or in support of) the TOE. The requirement for any such supplementary information will be identified in the relevant cPP (see description in Section 6).
<u>Security Administrator</u>	The terms "Administrator", "Security Administrator", and "User" are used interchangeably in this document at present and are used to represent a person that has authorized access to the TOE to perform configuration and management tasks.
<u>Target of Evaluation</u>	A set of software, firmware and/or hardware possibly accompanied by guidance. [CC1]
<u>TOE Security Functionality (TSF)</u>	A set consisting of all hardware, software, and firmware of the TOE that must be relied upon for the correct enforcement of the SFRs. [CC1]
<u>TSF Data</u>	Data for the operation of the TSF upon which the enforcement of the requirements relies.
<u>User</u>	See <u>Security Administrator</u>

1.4.2 Acronyms

Acronym	Meaning
<u>cPP</u>	<u>collaborative Protection Profile</u>
<u>CA</u>	<u>Certificate Authority</u>
<u>CN</u>	<u>Certificate Name</u>
<u>CVE</u>	<u>Common Vulnerabilities and Exposures (database)</u>
<u>DN</u>	<u>Domain Name</u>
<u>DNS</u>	<u>Domain Name Service</u>
<u>EA</u>	<u>Evaluation Activity</u>
<u>ECDHE</u>	<u>Elliptic Curve Diffie-Hellman Key Exchange</u>
<u>ITC</u>	<u>International Technical Community</u>
<u>NIST</u>	<u>National Institute of Standards and Technology</u>
<u>SAN</u>	<u>Storage Area Network</u>
<u>SAR</u>	<u>Security Assurance Requirement</u>
<u>SD</u>	<u>Supporting Document</u>
<u>SSL</u>	<u>Secure Sockets Layer</u>
<u>TLS</u>	<u>Transport Layer Security</u>

Deleted: <object><object><object>

Evaluation Activities for SFRs

2 Evaluation Activities for SFRs

14 The EAs presented in this section capture the actions the evaluator performs to address technology specific aspects covering specific SARs (e.g., ASE_TSS.1, ADV_FSP.1, AGD_OPE.1, and ATE_IND.1) – this is in addition to the CEM work units that are performed in Section 5 (Evaluation Activities for SARs).

15 Regarding design descriptions (designated by the subsections labelled TSS, as well as any required supplementary material that may be treated as proprietary), the evaluator must ensure there is specific information that satisfies the EA. For findings regarding the TSS section, the evaluator's verdicts will be associated with the CEM work unit ASE_TSS.1-1. Evaluator verdicts associated with the supplementary evidence will also be associated with ASE_TSS.1-1, since the requirement to provide such evidence is specified in ASE in the cPP.

16 For ensuring the guidance documentation provides sufficient information for the administrators/users as it pertains to SFRs, the evaluator's verdicts will be associated with CEM work units ADV_FSP.1-7, AGD_OPE.1-4, and AGD_OPE.1-5.

17 Finally, the subsection labelled Tests is where the iTC has determined that testing of the product in the context of the associated SFR is necessary. While the evaluator is expected to develop tests, there may be instances where it is more practical for the developer to construct tests, or where the developer may have existing tests. Therefore, it is acceptable for the evaluator to witness developer-generated tests in lieu of executing the tests. In this case, the evaluator must ensure the developer's tests are executing both in the manner declared by the developer and as mandated by the EA. The CEM work units that are associated with the EAs specified in this section are: ATE_IND.1-3, ATE_IND.1-4, ATE_IND.1-5, ATE_IND.1-6, and ATE_IND.1-7.

Additional Note for Distributed TOEs

18 For a distributed TOE, all examination of Operational Guidance information should be extended to include confirmation that it defines sufficient information to configure individual components such that the overall TOE is correctly established.

19 Evaluation activities for SFRs must be carried out for all distributed TOE components that implement the SFR (as defined in the mapping of SFRs to components – cf. section 5.1.2). This applies to optional and selection-based SFRs in section 3 and 4 as well as to the core SFRs in this section.

Moved (insertion) [1]

Deleted: cPP – collaborative Protection Profile

CVE – Common Vulnerabilities and Exposures (database)

iTC – International Technical Community

SD – Supporting Document

Supplementary information – information that is not necessarily included in the Security Target or guidance documentation, and that may not necessarily be public. Examples of such information could be entropy analysis, or description of a cryptographic key management architecture used in (or in support of) the TOE. The requirement for any such supplementary information will be identified in the relevant cPP (see description in section 4).

Evaluation Activities for SFRs

Deleted: <object><object><object>

Evaluation Activities for SFRs

2.1 Security Audit (FAU)

2.1.1 FAU_GEN.1 Audit data generation

2.1.1.1 TSS

20 For the administrative task of generating/import of, changing, or deleting of cryptographic keys as defined in FAU_GEN.1.1c, the TSS should identify what information is logged to identify the relevant key.

Moved (insertion) [2]

21 For distributed TOEs the evaluator shall examine the TSS to ensure it describes which auditable events are generated and recorded by which TOE components. The evaluator shall confirm that all components defined as generating audit information for a particular SFR should also contribute to that SFR as defined in the mapping of SFRs to TOE components, and that the audit records generated by each component cover all the SFRs that it implements.

2.1.1.2 Guidance Documentation

22 The evaluator shall check the guidance documentation and ensure that it lists all of the auditable events and provides a format for audit records. Each audit record format type must be covered, along with a brief description of each field. The evaluator shall check to make sure that every audit event type mandated by the cPP is described and that the description of the fields contains the information required in FAU_GEN.1.2, and the additional information specified in the table of audit events.

23 The evaluator shall also make a determination of the administrative actions related to TSF data related to configuration changes. The evaluator shall examine the guidance documentation and make a determination of which administrative commands, including subcommands, scripts, and configuration files, are related to the configuration (including enabling or disabling) of the mechanisms implemented in the TOE that are necessary to enforce the requirements specified in the cPP. The evaluator shall document the methodology or approach taken while determining which actions in the administrative guide are related to TSF data related to configuration changes. The evaluator may perform this activity as part of the activities associated with ensuring that the corresponding guidance documentation satisfies the requirements related to it.

Deleted: that are relevant in the context of the cPP.

Deleted: security relevant with respect to the cPP.

2.1.1.3 Tests

24 The evaluator shall test the TOE's ability to correctly generate audit records by having the TOE generate audit records for the events listed in the table of audit events and administrative actions listed above. This should include all instances of an event: for instance, if there are several different I&A mechanisms for a system, the FIA_UIA_EXT.1 events must be generated for each mechanism. The evaluator shall test that audit records are generated for the establishment and termination of a channel for each of the cryptographic protocols contained in the ST. If HTTPS is implemented, the test demonstrating the establishment and termination of a TLS session can be

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

combined with the test for an HTTPS session, When verifying the test results, the evaluator shall ensure the audit records generated during testing match the format specified in the guidance documentation, and that the fields in each audit record have the proper entries.

Deleted: <object>

Deleted: Logging of all activities related to trusted update should be tested in detail and with utmost diligence....

25 For distributed TOEs the evaluator shall perform tests on all TOE components according to the mapping of auditable events to TOE components in the Security Target. For all events involving more than one TOE component when an audit event is triggered, the evaluator has to check that the event has been audited on both sides (e.g. failure of building up a secure communication channel between the two components). This is not limited to error cases but includes also events about successful actions like successful build up/tear down of a secure communication channel between TOE components.

26 Note that the testing here can be accomplished in conjunction with the testing of the security mechanisms directly.

Deleted:Section Break (Next Page).....

2.1.2 FAU_GEN.2 User identity association

2.1.2.1 Tests

Moved (insertion) [3]

27 This activity should be accomplished in conjunction with the testing of FAU_GEN.1.1.

Moved down [4]: <#>FAU_STG.1 Protected audit trail storage¶
<#>TSS¶
<#>The evaluator shall examine the TSS to ensure it describes the amount of audit data that are stored locally and how these records are protected against unauthorized modification or deletion. The evaluator shall ensure that the TSS describes the conditions that must be met for authorized deletion of audit records.¶

28 For distributed TOEs the evaluator shall verify that where auditable events are instigated by another component, the component that records the event associates the event with the identity of the instigator. The evaluator shall perform at least one test on one component where another component instigates an auditable event. The evaluator shall verify that the event is recorded by the component as expected and the event is associated with the instigating component. It is assumed that an event instigated by another component can at least be generated for building up a secure channel between two TOE components. If for some reason (could be e.g. TSS or Guidance Documentation) the evaluator would come to the conclusion that the overall TOE does not generate any events instigated by other components, then this requirement shall be omitted.

Moved down [5]: <#>Guidance Documentation¶
<#>The evaluator shall examine the guidance documentation to determine that it describes any configuration required for protection of the locally stored audit data against unauthorized modification or deletion.¶
<#>Tests¶
<#>The evaluator shall perform the following tests:¶

2.1.3 FAU_STG_EXT.1 Protected audit event storage

2.1.3.1 TSS

Deleted: <#>Test 1: The evaluator shall access the audit trail as an *unauthorized* administrator and attempt to modify and delete the audit records. The evaluator shall verify that these attempts fail.¶

29 The evaluator shall examine the TSS to ensure it describes the means by which the audit data are transferred to the external audit server, and how the trusted channel is provided.

Moved down [6]: <#>¶
<#>Test 2: The evaluator shall access the audit trail as an authorized administrator and attempt to delete the audit records. The evaluator shall verify that these attempts succeed. The evaluator shall verify that only the records authorized for deletion are deleted.¶

30 The evaluator shall examine the TSS to ensure it describes the amount of audit data that are stored locally; what happens when the local audit data store is full; and how these records are protected against unauthorized access.

Deleted: <#>If the TOE complies with FAU_STG_EXT.2 the evaluator shall verify that the numbers provided by the TOE according to the selection for FAU_STG_EXT.2 are correct when performing the tests for FAU_STG_EXT.1.3.¶

31 The evaluator shall examine the TSS to ensure that it details the behaviour of the TOE when the storage space for audit data is full. When the option

Deleted: <#>

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

'overwrite previous audit record' is selected this description should include an outline of the rule for overwriting audit data. If 'other actions' are chosen such as sending the new audit data to an external IT entity, then the related behaviour of the TOE shall also be detailed in the TSS.

32 The evaluator shall examine the TSS to ensure that it details whether the transmission of audit information to an external IT entity can be done in real-time or periodically. In case the TOE does not perform transmission in real-time the evaluator needs to verify that the TSS provides details about what event stimulates the transmission to be made as well as the possible as well as acceptable frequency for the transfer of audit data.

Moved (insertion) [7]

33 For distributed TOEs the evaluator shall examine the TSS to ensure it describes to which TOE components this SFR applies and how audit data transfer to the external audit server is implemented among the different TOE components (e.g. every TOE components does its own transfer or the data is sent to another TOE component for central transfer of all audit events to the external audit server).

34 For distributed TOEs the evaluator shall examine the TSS to ensure it describes which TOE components are storing audit information locally and which components are buffering audit information and forwarding the information to another TOE component for local storage. For every component the TSS shall describe the behaviour when local storage space or buffer space is exhausted.

2.1.3.2 Guidance Documentation

35 The evaluator shall also examine the guidance documentation to ensure it describes how to establish the trusted channel to the audit server, as well as describe any requirements on the audit server (particular audit server protocol, version of the protocol required, etc.), as well as configuration of the TOE needed to communicate with the audit server.

36 The evaluator shall also examine the guidance documentation to determine that it describes the relationship between the local audit data and the audit data that are sent to the audit log server. For example, when an audit event is generated, is it simultaneously sent to the external server and the local store, or is the local store used as a buffer and "cleared" periodically by sending the data to the audit server.

37 The evaluator shall also ensure that the guidance documentation describes all possible configuration options for FAU_STG_EXT.1.3 and the resulting behaviour of the TOE for each possible configuration. The description of possible configuration options and resulting behaviour shall correspond to those described in the TSS.

2.1.3.3 Tests

38 Testing of the trusted channel mechanism for audit will be performed as specified in the associated assurance activities for the particular trusted

Deleted:

Moved down [8]: channel mechanism. The evaluator shall perform the following additional

Deleted: test for this requirement:

Deleted: <object><object><object>

Evaluation Activities for SFRs

channel mechanism. The evaluator shall perform the following additional tests for this requirement:

- a) Test 1: The evaluator shall establish a session between the TOE and the audit server according to the configuration guidance provided. The evaluator shall then examine the traffic that passes between the audit server and the TOE during several activities of the evaluator's choice designed to generate audit data to be transferred to the audit server. The evaluator shall observe that these data are not able to be viewed in the clear during this transfer, and that they are successfully received by the audit server. The evaluator shall record the particular software (name, version) used on the audit server during testing. The evaluator shall verify that the TOE is capable of transferring audit data to an external audit server automatically without administrator intervention.
- b) Test 2: The evaluator shall perform operations that generate audit data and verify that this data is stored locally. The evaluator shall perform operations that generate audit data until the local storage space is exceeded and verifies that the TOE complies with the behaviour defined in FAU_STG_EXT.1.3. Depending on the configuration this means that the evaluator has to check the content of the audit data when the audit data is just filled to the maximum and then verifies that
 - 1) The audit data remains unchanged with every new auditable event that should be tracked but that the audit data is recorded again after the local storage for audit data is cleared (for the option 'drop new audit data' in FAU_STG_EXT.1.3).
 - 2) The existing audit data is overwritten with every new auditable event that should be tracked according to the specified rule (for the option 'overwrite previous audit records' in FAU_STG_EXT.1.3)
 - 3) The TOE behaves as specified (for the option 'other action' in FAU_STG_EXT.1.3).
- c) Test 3: If the TOE complies with FAU_STG_EXT.2/LocSpace the evaluator shall verify that the numbers provided by the TOE according to the selection for FAU_STG_EXT.2/LocSpace are correct when performing the tests for FAU_STG_EXT.1.3.
- d) Test 4: For distributed TOEs, Test 1 defined above should be applicable to all TOE components that forward audit data to an external audit server. For the local storage according to FAU_STG_EXT.1.2 and FAU_STG_EXT.1.3 the Test 2 specified above shall be applied to all TOE components that store audit data locally and comply with FAU_STG_EXT.2/LocSpace Test 3 specified above shall be applied. The evaluator shall verify that the transfer of audit data to an external audit server is implemented.

Deleted: <object>

Moved (insertion) [8]

Deleted: ¶

Moved down [10]: Guidance Documentation¶

¶ The evaluator shall also ensure that the guidance documentation describes all possible configuration options and the meaning of the result returned by the TOE for each possible configuration. The description of possible configuration options and explanation of the result shall correspond to those described in the TSS.¶

¶ The evaluator shall verify that the guidance documentation contains a warning for the administrator about the loss of audit data when

Deleted: 2.1.5→

Deleted:

Moved down [9]: ~~Counting lost audit data~~¶

¶ This activity should be accomplished in conjunction with the testing of FAU_STG_EXT.1.2 and FAU_STG_EXT.1.3.¶

¶ TSS¶

¶ The evaluator shall examine the TSS to ensure that it details the possible options the TOE supports for information about the number of audit records that have been dropped, overwritten, etc. if the local storage for audit data is full.¶

Deleted: he clears

Deleted: local storage for audit records.¶

¶ Tests¶

¶ The

Deleted: .

Deleted: ~~FAU_STG_EXT.3~~ ~~Display warning for local storage space~~¶

Moved down [11]: ~~¶~~¶

~~¶~~ This activity should be accomplished in conjunction with the testing of FAU_STG_EXT.1.2 and FAU_STG_EXT.1.3.¶

Deleted: ~~¶~~Section Break (Next Page)¶

Moved down [12]: ~~¶~~¶

~~¶~~ TSS¶

~~¶~~¶

~~¶~~ The evaluator shall examine the TSS to ensure that it details how the user is warned before the local storage for audit data is full.¶

Moved down [13]: ~~¶~~¶

~~¶~~ Guidance Documentation¶

~~¶~~¶

~~¶~~ The evaluator shall also ensure that the guidance documentation describes how the user is warned before the local storage for audit data is full and how this warning is displayed or stored (since there is no guarantee that an administrator session is running at the time the warning is issued, it is probably stored in the log files). The description in the guidance

Deleted: <object><object><object>

Deleted: <object>

2.2 Cryptographic Support (FCS)

2.2.1 FCS_CKM.1 Cryptographic Key Generation

2.2.1.1 TSS

39 The evaluator shall ensure that the TSS identifies the key sizes supported by the TOE. If the ST specifies more than one scheme, the evaluator shall examine the TSS to verify that it identifies the usage for each scheme.

2.2.1.2 Guidance Documentation

40 The evaluator shall verify that the AGD guidance instructs the administrator how to configure the TOE to use the selected key generation scheme(s) and key size(s) for all cryptographic protocols defined in the Security Target.

Deleted: uses

Deleted: this PP

2.2.1.3 Tests

41 Note: The following tests require the developer to provide access to a test platform that provides the evaluator with tools that are typically not found on factory products.

Key Generation for FIPS PUB 186-4 RSA Schemes

42 The evaluator shall verify the implementation of RSA Key Generation by the TOE using the Key Generation test. This test verifies the ability of the TSF to correctly produce values for the key components including the public verification exponent e , the private prime factors p and q , the public modulus n and the calculation of the private signature exponent d .

43 Key Pair generation specifies 5 ways (or methods) to generate the primes p and q . These include:

Deleted: =====Section Break (Next Page)=====

a) Random Primes:

- Provable primes
- Probable primes

b) Primes with Conditions:

- Primes p_1, p_2, q_1, q_2, p and q shall all be provable primes
- Primes $p_1, p_2, q_1,$ and q_2 shall be provable primes and p and q shall be probable primes
- Primes p_1, p_2, q_1, q_2, p and q shall all be probable primes

44 To test the key generation method for the Random Provable primes method and for all the Primes with Conditions methods, the evaluator must seed the TSF key generation routine with sufficient data to deterministically generate the RSA key pair. This includes the random seed(s), the public exponent of the RSA key, and the desired key length. For each key length supported, the

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

evaluator shall have the TSF generate 25 key pairs. The evaluator shall verify the correctness of the TSF's implementation by comparing values generated by the TSF with those generated from a known good implementation.

Key Generation for Elliptic Curve Cryptography (ECC)

FIPS 186-4 ECC Key Generation Test

45 For each supported NIST curve, i.e., P-256, P-384 and P-521, the evaluator shall require the implementation under test (IUT) to generate 10 private/public key pairs. The private key shall be generated using an approved random bit generator (RBG). To determine correctness, the evaluator shall submit the generated key pairs to the public key verification (PKV) function of a known good implementation.

FIPS 186-4 Public Key Verification (PKV) Test

46 For each supported NIST curve, i.e., P-256, P-384 and P-521, the evaluator shall generate 10 private/public key pairs using the key generation function of a known good implementation and modify five of the public key values so that they are incorrect, leaving five values unchanged (i.e., correct). The evaluator shall obtain in response a set of 10 PASS/FAIL values.

Key Generation for Finite-Field Cryptography (FFC)

47 The evaluator shall verify the implementation of the Parameters Generation and the Key Generation for FFC by the TOE using the Parameter Generation and Key Generation test. This test verifies the ability of the TSF to correctly produce values for the field prime p, the cryptographic prime q (dividing p-1), the cryptographic group generator g, and the calculation of the private key x and public key y.

Deleted:

48 The Parameter generation specifies 2 ways (or methods) to generate the cryptographic prime q and the field prime p:

Deleted: =====Section Break (Next Page)=====

- Primes q and p shall both be provable primes
- Primes q and field prime p shall both be probable primes

49 and two ways to generate the cryptographic group generator g:

- Generator g constructed through a verifiable process
- Generator g constructed through an unverifiable process.

50 The Key generation specifies 2 ways to generate the private key x:

- len(q) bit output of RBG where $1 \leq x \leq q-1$
- len(q) + 64 bit output of RBG, followed by a mod q-1 operation and a +1 operation, where $1 \leq x \leq q-1$.

51 The security strength of the RBG must be at least that of the security offered by the FFC parameter set.

52 To test the cryptographic and field prime generation method for the provable primes method and/or the group generator g for a verifiable process, the

Deleted:

Deleted: <object><object><object>

Deleted: <object>

evaluator must seed the TSF parameter generation routine with sufficient data to deterministically generate the parameter set.

53 For each key length supported, the evaluator shall have the TSF generate 25 parameter sets and key pairs. The evaluator shall verify the correctness of the TSF's implementation by comparing values generated by the TSF with those generated from a known good implementation. Verification must also confirm

- $g \neq 0, 1$
- q divides $p-1$
- $g^q \text{ mod } p = 1$
- $g^x \text{ mod } p = y$

54 for each FFC parameter set and key pair.

2.2.2 FCS_CKM.2 Cryptographic Key Establishment

2.2.2.1 TSS

55 The evaluator shall ensure that the supported key establishment schemes correspond to the key generation schemes identified in FCS_CKM.1.1. If the ST specifies more than one scheme, the evaluator shall examine the TSS to verify that it identifies the usage for each scheme (including whether the TOE acts as a sender, a recipient, or both). If Diffie-Hellman group 14 is selected from FCS_CKM.2.1, the TSS shall describe how the implementation meets RFC 3526 Section 3.

2.2.2.2 Guidance Documentation

56 The evaluator shall verify that the AGD guidance instructs the administrator how to configure the TOE to use the selected key establishment scheme(s).

2.2.2.3 Tests

Deleted: ~~~~~Section Break (Next Page)~~~~~

Key Establishment Schemes

57 The evaluator shall verify the implementation of the key establishment schemes of the supported by the TOE using the applicable tests below.

SP800-56A Key Establishment Schemes

58 The evaluator shall verify a TOE's implementation of SP800-56A key agreement schemes using the following Function and Validity tests. These validation tests for each key agreement scheme verify that a TOE has implemented the components of the key agreement scheme according to the specifications in the Recommendation. These components include the calculation of the DLC primitives (the shared secret value Z) and the calculation of the derived keying material (DKM) via the Key Derivation Function (KDF). If key confirmation is supported, the evaluator shall also verify that the components of key confirmation have been implemented.

Deleted:

Deleted: <object><object><object>

Deleted: <object>

correctly, using the test procedures described below. This includes the parsing of the DKM, the generation of MACdata and the calculation of MACtag.

Function Test

- 59 The Function test verifies the ability of the TOE to implement the key agreement schemes correctly. To conduct this test the evaluator shall generate or obtain test vectors from a known good implementation of the TOE supported schemes. For each supported key agreement scheme-key agreement role combination, KDF type, and, if supported, key confirmation role- key confirmation type combination, the tester shall generate 10 sets of test vectors. The data set consists of one set of domain parameter values (FFC) or the NIST approved curve (ECC) per 10 sets of public keys. These keys are static, ephemeral or both depending on the scheme being tested.
- 60 The evaluator shall obtain the DKM, the corresponding TOE's public keys (static and/or ephemeral), the MAC tag(s), and any inputs used in the KDF, such as the Other Information field OI and TOE id fields.
- 61 If the TOE does not use a KDF defined in SP 800-56A, the evaluator shall obtain only the public keys and the hashed value of the shared secret.
- 62 The evaluator shall verify the correctness of the TSF's implementation of a given scheme by using a known good implementation to calculate the shared secret value, derive the keying material DKM, and compare hashes or MAC tags generated from these values.
- 63 If key confirmation is supported, the TSF shall perform the above for each implemented approved MAC algorithm.

Deleted:Section Break (Next Page).....

Validity Test

- 64 The Validity test verifies the ability of the TOE to recognize another party's valid and invalid key agreement results with or without key confirmation. To conduct this test, the evaluator shall obtain a list of the supporting cryptographic functions included in the SP800-56A key agreement implementation to determine which errors the TOE should be able to recognize. The evaluator generates a set of 24 (FFC) or 30 (ECC) test vectors consisting of data sets including domain parameter values or NIST approved curves, the evaluator's public keys, the TOE's public/private key pairs, MACtag, and any inputs used in the KDF, such as the other info and TOE id fields.
- 65 The evaluator shall inject an error in some of the test vectors to test that the TOE recognizes invalid key agreement results caused by the following fields being incorrect: the shared secret value Z, the DKM, the other information field OI, the data to be MACed, or the generated MACtag. If the TOE contains the full or partial (only ECC) public key validation, the evaluator will also individually inject errors in both parties' static public keys, both parties' ephemeral public keys and the TOE's static private key to assure the TOE detects errors in the public key validation function and/or the partial key.

Deleted:

Deleted: <object><object><object>

Deleted: <object>

validation function (in ECC only). At least two of the test vectors shall remain unmodified and therefore should result in valid key agreement results (they should pass).

66 The TOE shall use these modified test vectors to emulate the key agreement scheme using the corresponding parameters. The evaluator shall compare the TOE's results with the results using a known good implementation verifying that the TOE detects these errors.

SP800-56B Key Establishment Schemes

67 If the TOE acts as a sender, the following assurance activity shall be performed to ensure the proper operation of every TOE supported combination of RSA-based key establishment scheme:

Deleted: <#>The evaluator shall verify that the TSS describes whether the TOE acts as a sender, a recipient, or both for RSA-based key establishment schemes. <#>

a) To conduct this test the evaluator shall generate or obtain test vectors from a known good implementation of the TOE supported schemes. For each combination of supported key establishment scheme and its options (with or without key confirmation if supported, for each supported key confirmation MAC function if key confirmation is supported, and for each supported mask generation function if KTS-OAEP is supported), the tester shall generate 10 sets of test vectors. Each test vector shall include the RSA public key, the plaintext keying material, any additional input parameters if applicable, the MacKey and MacTag if key confirmation is incorporated, and the outputted ciphertext. For each test vector, the evaluator shall perform a key establishment encryption operation on the TOE with the same inputs (in cases where key confirmation is incorporated, the test shall use the MacKey from the test vector instead of the randomly generated MacKey used in normal operation) and ensure that the outputted ciphertext is equivalent to the ciphertext in the test vector.

Deleted: ¶

68 If the TOE acts as a receiver, the following assurance activities shall be performed to ensure the proper operation of every TOE supported combination of RSA-based key establishment scheme:

a) To conduct this test the evaluator shall generate or obtain test vectors from a known good implementation of the TOE supported schemes. For each combination of supported key establishment scheme and its options (with our without key confirmation if supported, for each supported key confirmation MAC function if key confirmation is supported, and for each supported mask generation function if KTS-OAEP is supported), the tester shall generate 10 sets of test vectors. Each test vector shall include the RSA private key, the plaintext keying material (KeyData), any additional input parameters if applicable, the MacTag in cases where key confirmation is incorporated, and the outputted ciphertext. For each test vector, the evaluator shall perform the key establishment decryption operation on the TOE and ensure that the outputted plaintext keying material (KeyData) is equivalent to the plaintext keying material in the test vector. In cases where key confirmation is incorporated, the evaluator shall perform the key,

Deleted:

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

confirmation steps and ensure that the outputted MacTag is equivalent to the MacTag in the test vector.

- b) The evaluator shall ensure that the TSS describes how the TOE handles decryption errors. In accordance with NIST Special Publication 800-56B, the TOE must not reveal the particular error that occurred, either through the contents of any outputted or logged error message or through timing variations. If KTS-OAEP is supported, the evaluator shall create separate contrived ciphertext values that trigger each of the three decryption error checks described in NIST Special Publication 800-56B section 7.2.2.3, ensure that each decryption attempt results in an error, and ensure that any outputted or logged error message is identical for each. If KTS-KEM-KWS is supported, the evaluator shall create separate contrived ciphertext values that trigger each of the three decryption error checks described in NIST Special Publication 800-56B section 7.2.3.3, ensure that each decryption attempt results in an error, and ensure that any outputted or logged error message is identical for each.

Deleted:

Deleted:

Diffie-Hellman Group 14

69 The evaluator shall verify the correctness of the TSF's implementation of Diffie-Hellman group 14 by using a known good implementation for each protocol selected in FTP_TRP.1/Admin, FTP_TRP.1/Join, FTP_ITC.1 and FPT_ITT.1 that uses Diffie-Hellman group 14.

2.2.3 FCS_CKM.4 Cryptographic Key Destruction

2.2.3.1 TSS

70 The evaluator examines the TSS to ensure it lists all relevant keys (describing the origin and storage location of each), all relevant key destruction situations (e.g. factory reset or device wipe function, disconnection of trusted channels, key change as part of a secure channel protocol), and the destruction method used in each case. For the purpose of this Evaluation Activity the relevant keys are those keys that are relied upon to support any of the SFRs in the Security Target. The evaluator confirms that the description of keys and storage locations is consistent with the functions carried out by the TOE (e.g. that all keys for the TOE-specific secure channels and protocols, or that support FPT_APW.EXT.1 and FPT_SKP_EXT.1, are accounted for²). In particular, if a TOE claims not to store plaintext keys in non-volatile memory then the evaluator checks that this is consistent with the operation of the TOE.

71 The evaluator shall check to ensure the TSS identifies how the TOE destroys keys stored as plaintext in non-volatile memory, and that the description

² Where keys are stored encrypted or wrapped under another key then this may need to be explained in order to allow the evaluator to confirm the consistency of the description of keys with the TOE functions.

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

includes identification and description of the interfaces that the TOE uses to destroy keys (e.g., file system APIs, key store APIs).

72 Note that where selections involve ‘destruction of reference’ (for volatile memory) or ‘invocation of an interface’ (for non-volatile memory) then the relevant interface definition is examined by the evaluator to ensure that the interface supports the selection(s) and description in the TSS. In the case of non-volatile memory the evaluator includes in their examination the relevant interface description for each media type on which plaintext keys are stored. The presence of OS-level and storage device-level swap and cache files is not examined in the current version of the Evaluation Activity.

73 Where the TSS identifies keys that are stored in a non-plaintext form, the evaluator shall check that the TSS identifies the encryption method and the key-encrypting-key used, and that the key-encrypting-key is either itself stored in an encrypted form or that it is destroyed by a method included under FCS_CKM.4.

Moved (insertion) [14]

74 The evaluator shall check that the TSS identifies any configurations or circumstances that may not conform to the key destruction requirement (see further discussion in the Guidance Documentation section below). Note that reference may be made to the Guidance Documentation for description of the detail of such cases where destruction may be prevented or delayed.

Deleted: The evaluator shall check to ensure the TSS lists each type of plaintext key material and its origin and storage location. [2]

75 Where the ST specifies the use of “a value that does not contain any CSP” to overwrite keys, the evaluator examines the TSS to ensure that it describes how that pattern is obtained and used, and that this justifies the claim that the pattern does not contain any CSPs.

2.2.3.2 Guidance Documentation

76 A TOE may be subject to situations that could prevent or delay key destruction in some cases. The evaluator shall check that the guidance documentation identifies configurations or circumstances that may not strictly conform to the key destruction requirement, and that this description is consistent with the relevant parts of the TSS (and any other supporting information used). The evaluator shall check that the guidance documentation provides guidance on situations where key destruction may be delayed at the physical layer.

77 For example, when the TOE does not have full access to the physical memory, it is possible that the storage may be implementing wear-levelling and garbage collection. This may result in additional copies of the key that are logically inaccessible but persist physically. Where available, the TOE might then describe use of the TRIM command³ and garbage collection to destroy these persistent copies upon their deletion (this would be explained in TSS and Operational Guidance).

³ Where TRIM is used then the TSS and/or guidance documentation is also expected to describe how the keys are stored such that they are not inaccessible to TRIM. (e.g. they would need not to be contained in a file less than 982 bytes which would be completely contained in the master file table).

Deleted: <object><object><object>

Evaluation Activities for SFRs

2.2.4 FCS_COP.1/(DataEncryption Cryptographic Operation (AES Data Encryption/Decryption))

2.2.4.1 Tests

AES-CBC Known Answer Tests

78 There are four Known Answer Tests (KATs), described below. In all KATs, the plaintext, ciphertext, and IV values shall be 128-bit blocks. The results from each test may either be obtained by the evaluator directly or by supplying the inputs to the implementer and receiving the results in response. To determine correctness, the evaluator shall compare the resulting values to those obtained by submitting the same inputs to a known good implementation.

79 **KAT-1.** To test the encrypt functionality of AES-CBC, the evaluator shall supply a set of 10 plaintext values and obtain the ciphertext value that results from AES-CBC encryption of the given plaintext using a key value of all zeros and an IV of all zeros. Five plaintext values shall be encrypted with a 128-bit all-zeros key, and the other five shall be encrypted with a 256-bit all-zeros key.

80 To test the decrypt functionality of AES-CBC, the evaluator shall perform the same test as for encrypt, using 10 ciphertext values as input and AES-CBC decryption.

81 **KAT-2.** To test the encrypt functionality of AES-CBC, the evaluator shall supply a set of 10 key values and obtain the ciphertext value that results from AES-CBC encryption of an all-zeros plaintext using the given key value and an IV of all zeros. Five of the keys shall be 128-bit keys, and the other five shall be 256-bit keys.

82 To test the decrypt functionality of AES-CBC, the evaluator shall perform the same test as for encrypt, using an all-zero ciphertext value as input and AES-CBC decryption.

83 **KAT-3.** To test the encrypt functionality of AES-CBC, the evaluator shall supply the two sets of key values described below and obtain the ciphertext value that results from AES encryption of an all-zeros plaintext using the given key value and an IV of all zeros. The first set of keys shall have 128 128-bit keys, and the second set shall have 256 256-bit keys. Key *i* in each set shall have the leftmost *i* bits be ones and the rightmost *N-i* bits be zeros, for *i* in [1,N].

84 To test the decrypt functionality of AES-CBC, the evaluator shall supply the two sets of key and ciphertext value pairs described below and obtain the plaintext value that results from AES-CBC decryption of the given ciphertext using the given key and an IV of all zeros. The first set of key/ciphertext pairs

Deleted: <object>

Moved up [1]: ¶
The

Deleted: evaluator shall verify that the TSS describes when each type of key material is cleared (for example, on system power off, on wipe function, on disconnection of trusted channels, when no longer needed by the trusted channel per the protocol, etc.).¶

¶ The evaluator shall also verify that, for each type of key, the type of clearing procedure that is performed (cryptographic erase, overwrite with zeros, overwrite with random pattern, or block erase) is listed. If different types of memory are used to store the materials to be protected, the evaluator shall check to ensure that the TSS describes the clearing procedure in terms of the memory in which the data are stored (for example, "secret keys stored on flash are cleared by overwriting once with zeros, while secret keys stored on the internal persistent storage device are cleared by overwriting three times with a random pattern that is changed before each write").¶

Deleted: (1)

Deleted: Encryption/

Deleted:

Deleted:

Deleted: =====Section Break (Next Page)=====

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

shall have 128 128-bit key/ciphertext pairs, and the second set of key/ciphertext pairs shall have 256 256-bit key/ciphertext pairs. Key i in each set shall have the leftmost i bits be ones and the rightmost $N-i$ bits be zeros, for i in $[1,N]$. The ciphertext value in each pair shall be the value that results in an all-zeros plaintext when decrypted with its corresponding key.

Deleted:

85 **KAT-4.** To test the encrypt functionality of AES-CBC, the evaluator shall supply the set of 128 plaintext values described below and obtain the two ciphertext values that result from AES-CBC encryption of the given plaintext using a 128-bit key value of all zeros with an IV of all zeros and using a 256-bit key value of all zeros with an IV of all zeros, respectively. Plaintext value i in each set shall have the leftmost i bits be ones and the rightmost $128-i$ bits be zeros, for i in $[1,128]$.

86 To test the decrypt functionality of AES-CBC, the evaluator shall perform the same test as for encrypt, using ciphertext values of the same form as the plaintext in the encrypt test as input and AES-CBC decryption.

AES-CBC Multi-Block Message Test

87 The evaluator shall test the encrypt functionality by encrypting an i -block message where $1 < i \leq 10$. The evaluator shall choose a key, an IV and plaintext message of length i blocks and encrypt the message, using the mode to be tested, with the chosen key and IV. The ciphertext shall be compared to the result of encrypting the same plaintext message with the same key and IV using a known good implementation.

88 The evaluator shall also test the decrypt functionality for each mode by decrypting an i -block message where $1 < i \leq 10$. The evaluator shall choose a key, an IV and a ciphertext message of length i blocks and decrypt the message, using the mode to be tested, with the chosen key and IV. The plaintext shall be compared to the result of decrypting the same ciphertext message with the same key and IV using a known good implementation.

Deleted: ¶
¶

AES-CBC Monte Carlo Tests

89 The evaluator shall test the encrypt functionality using a set of 200 plaintext, IV, and key 3-tuples. 100 of these shall use 128 bit keys, and 100 shall use 256 bit keys. The plaintext and IV values shall be 128-bit blocks. For each 3-tuple, 1000 iterations shall be run as follows:

Deleted:

```
# Input: PT, IV, Key
for i = 1 to 1000:
  if i == 1:
    CT[1] = AES-CBC-Encrypt(Key, IV, PT)
    PT = IV
  else:
```

Deleted: <object><object><object>

$$CT[i] = \text{AES-CBC-Encrypt}(\text{Key}, PT)$$

$$PT = CT[i-1]$$

90 The ciphertext computed in the 1000th iteration (i.e., CT[1000]) is the result for that trial. This result shall be compared to the result of running 1000 iterations with the same values using a known good implementation.

91 The evaluator shall test the decrypt functionality using the same test as for encrypt, exchanging CT and PT and replacing AES-CBC-Encrypt with AES-CBC-Decrypt.

AES-GCM Test

92 The evaluator shall test the authenticated encrypt functionality of AES-GCM for each combination of the following input parameter lengths:

128 bit and 256 bit keys

- a) **Two plaintext lengths.** One of the plaintext lengths shall be a non-zero integer multiple of 128 bits, if supported. The other plaintext length shall not be an integer multiple of 128 bits, if supported.
- a) **Three AAD lengths.** One AAD length shall be 0, if supported. One AAD length shall be a non-zero integer multiple of 128 bits, if supported. One AAD length shall not be an integer multiple of 128 bits, if supported.
- b) **Two IV lengths.** If 96 bit IV is supported, 96 bits shall be one of the two IV lengths tested.

93 The evaluator shall test the encrypt functionality using a set of 10 key, plaintext, AAD, and IV tuples for each combination of parameter lengths above and obtain the ciphertext value and tag that results from AES-GCM authenticated encrypt. Each supported tag length shall be tested at least once per set of 10. The IV value may be supplied by the evaluator or the implementation being tested, as long as it is known.

94 The evaluator shall test the decrypt functionality using a set of 10 key, ciphertext, tag, AAD, and IV 5-tuples for each combination of parameter lengths above and obtain a Pass/Fail result on authentication and the decrypted plaintext if Pass. The set shall include five tuples that Pass and five that Fail.

95 The results from each test may either be obtained by the evaluator directly or by supplying the inputs to the implementer and receiving the results in response. To determine correctness, the evaluator shall compare the resulting values to those obtained by submitting the same inputs to a known good implementation.

AES-CTR Known Answer Tests

- 96 There are four Known Answer Tests (KATs) described below. For all KATs, the plaintext, IV, and ciphertext values shall be 128-bit blocks. The results from each test may either be obtained by the validator directly or by supplying the inputs to the implementer and receiving the results in response. To determine correctness, the evaluator shall compare the resulting values to those obtained by submitting the same inputs to a known good implementation.
- 97 KAT-1 To test the encrypt functionality, the evaluator shall supply a set of 10 plaintext values and obtain the ciphertext value that results from encryption of the given plaintext using a key value of all zeros and an IV of all zeros. Five plaintext values shall be encrypted with a 128-bit all zeros key, and the other five shall be encrypted with a 256-bit all zeros key. To test the decrypt functionality, the evaluator shall perform the same test as for encrypt, using 10 ciphertext values as input.
- 98 KAT-2 To test the encrypt functionality, the evaluator shall supply a set of 10 key values and obtain the ciphertext value that results from encryption of an all zeros plaintext using the given key value and an IV of all zeros. Five of the key values shall be 128-bit keys, and the other five shall be 256-bit keys. To test the decrypt functionality, the evaluator shall perform the same test as for encrypt, using an all zero ciphertext value as input.
- 99 KAT-3 To test the encrypt functionality, the evaluator shall supply the two sets of key values described below and obtain the ciphertext values that result from AES encryption of an all zeros plaintext using the given key values and an IV of all zeros. The first set of keys shall have 128 128-bit keys, and the second shall have 256 256-bit keys. Key i in each set shall have the leftmost i bits be ones and the rightmost $N-i$ bits be zeros, for i in $[1, N]$. To test the decrypt functionality, the evaluator shall supply the two sets of key and ciphertext value pairs described below and obtain the plaintext value that results from decryption of the given ciphertext using the given key values and an IV of all zeros. The first set of key/ciphertext pairs shall have 128 128-bit key/ciphertext pairs, and the second set of key/ciphertext pairs shall have 256 256-bit pairs. Key i in each set shall have the leftmost i bits be ones and the rightmost $N-i$ bits be zeros for i in $[1, N]$. The ciphertext value in each pair shall be the value that results in an all zeros plaintext when decrypted with its corresponding key.
- 100 KAT-4 To test the encrypt functionality, the evaluator shall supply the set of 128 plaintext values described below and obtain the two ciphertext values that result from encryption of the given plaintext using a 128-bit key value of all zeros and using a 256 bit key value of all zeros, respectively, and an IV of all zeros. Plaintext value i in each set shall have the leftmost bits be ones and the rightmost 128- i bits be zeros, for i in $[1, 128]$. To test the decrypt functionality, the evaluator shall perform the same test as for encrypt, using ciphertext values of the same form as the plaintext in the encrypt test as input.

Evaluation Activities for SFRs

Deleted: <object>

AES-CTR Multi-Block Message Test

101 The evaluator shall test the encrypt functionality by encrypting an i-block message where 1 less-than i less-than-or-equal to 10. For each i the evaluator shall choose a key, IV, and plaintext message of length i blocks and encrypt the message, using the mode to be tested, with the chosen key. The ciphertext shall be compared to the result of encrypting the same plaintext message with the same key and IV using a known good implementation. The evaluator shall also test the decrypt functionality by decrypting an i-block message where 1 less-than i less-than-or-equal to 10. For each i the evaluator shall choose a key and a ciphertext message of length i blocks and decrypt the message, using the mode to be tested, with the chosen key. The plaintext shall be compared to the result of decrypting the same ciphertext message with the same key using a known good implementation.

AES-CTR Monte-Carlo Test

102 The evaluator shall test the encrypt functionality using 200 plaintext/key pairs. 100 of these shall use 128 bit keys, and 100 of these shall use 256 bit keys. The plaintext values shall be 128-bit blocks. For each pair, 1000 iterations shall be run as follows:

```
# Input: PT, Key
for i = 1 to 1000:
  CT[i] = AES-CTR-Encrypt(Key, PT) PT = CT[i]
```

103 The ciphertext computed in the 1000th iteration is the result for that trial. This result shall be compared to the result of running 1000 iterations with the same values using a known good implementation.

104 There is no need to test the decryption engine.

2.2.5 FCS_COP.1/SigGen Cryptographic Operation (Signature Generation and Verification)

Deleted: (2)

2.2.5.1 Tests

ECDSA Algorithm Tests

ECDSA FIPS 186-4 Signature Generation Test

105 For each supported NIST curve (i.e., P-256, P-384 and P-521) and SHA function pair, the evaluator shall generate 10 1024-bit long messages and obtain for each message a public key and the resulting signature values R and S. To determine correctness, the evaluator shall use the signature verification function of a known good implementation.

ECDSA FIPS 186-4 Signature Verification Test

106 For each supported NIST curve (i.e., P-256, P-384 and P-521) and SHA function pair, the evaluator shall generate a set of 10 1024-bit message, public

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

key and signature tuples and modify one of the values (message, public key or signature) in five of the 10 tuples. The evaluator shall obtain in response a set of 10 PASS/FAIL values.

RSA Signature Algorithm Tests

Signature Generation Test

107 The evaluator generates or obtains 10 messages for each modulus size/SHA combination supported by the TOE. The TOE generates and returns the corresponding signatures.

108 The evaluator shall verify the correctness of the TOE's signature using a trusted reference implementation of the signature verification algorithm and the associated public keys to verify the signatures.

Signature Verification Test

109 For each modulus size/hash algorithm selected, the evaluator generates a modulus and three associated key pairs, (d, e). Each private key d is used to sign six pseudorandom messages each of 1024 bits using a trusted reference implementation of the signature generation algorithm. Some of the public keys, e, messages, or signatures are altered so that signature verification should fail. For both the set of original messages and the set of altered messages: the modulus, hash algorithm, public key e values, messages, and signatures are forwarded to the TOE, which then attempts to verify the signatures and returns the verification results.

110 The evaluator verifies that the TOE confirms correct signatures on the original messages and detects the errors introduced in the altered messages.

2.2.6 FCS_COP.1/Hash Cryptographic Operation (Hash Algorithm)

2.2.6.1 TSS

111 The evaluator shall check that the association of the hash function with other TSF cryptographic functions (for example, the digital signature verification function) is documented in the TSS.

2.2.6.2 Guidance Documentation

112 The evaluator checks the AGD documents to determine that any configuration that is required to configure the required hash sizes is present.

2.2.6.3 Tests

113 The TSF hashing functions can be implemented in one of two modes. The first mode is the byte-oriented mode. In this mode the TSF only hashes messages

Deleted: <object>

Deleted: shall verify the implementation of RSA Signature Generation by the TOE using the Signature Generation Test. To conduct this test the evaluator must generate

Deleted: obtain

Deleted: from a trusted reference implementation

Deleted: TSF

Deleted: evaluator shall have the

Deleted: use their private key

Deleted: modulus value to sign these messages

Deleted: =====Section Break (Next Page)=====

Deleted: TSF's

Deleted: known good

Deleted: The

Deleted: shall perform the Signature Verification test to verify the ability of the TOE to recognize another party's valid...

Deleted: invalid signatures. The evaluator shall inject errors into the test vectors produced during the Signature Verification Test by introducing errors in some...

Deleted: IR format, and/

Deleted: . The TOE

Deleted: success or failure.

The evaluator shall use these test vectors to emulate the signature verification test using

Deleted: corresponding parameters and verify that the TOE detects these errors

Deleted: (3)

Deleted:

Deleted: <object><object><object>

Deleted: <object>

that are an integral number of bytes in length; i.e., the length (in bits) of the message to be hashed is divisible by 8. The second mode is the bit-oriented mode. In this mode the TSF hashes messages of arbitrary length. As there are different tests for each mode, an indication is given in the following sections for the bit-oriented vs. the byte-oriented testmacs.

114 The evaluator shall perform all of the following tests for each hash algorithm implemented by the TSF and used to satisfy the requirements of this PP.

Short Messages Test • Bit-oriented Mode

115 The evaluators devise an input set consisting of m+1 messages, where m is the block length of the hash algorithm. The length of the messages range sequentially from 0 to m bits. The message text shall be pseudorandomly generated. The evaluators compute the message digest for each of the messages and ensure that the correct result is produced when the messages are provided to the TSF.

Deleted: ¶
¶

Short Messages Test • Byte-oriented Mode

116 The evaluators devise an input set consisting of m/8+1 messages, where m is the block length of the hash algorithm. The length of the messages range sequentially from 0 to m/8 bytes, with each message being an integral number of bytes. The message text shall be pseudorandomly generated. The evaluators compute the message digest for each of the messages and ensure that the correct result is produced when the messages are provided to the TSF.

Selected Long Messages Test • Bit-oriented Mode

117 The evaluators devise an input set consisting of m messages, where m is the block length of the hash algorithm (e.g. 512 bits for SHA-256). The length of the ith message is m + 99*i, where 1 ≤ i ≤ m. The message text shall be pseudorandomly generated. The evaluators compute the message digest for each of the messages and ensure that the correct result is produced when the messages are provided to the TSF.

Selected Long Messages Test • Byte-oriented Mode

118 The evaluators devise an input set consisting of m/8 messages, where m is the block length of the hash algorithm (e.g. 512 bits for SHA-256). The length of the ith message is m + 8*99*i, where 1 ≤ i ≤ m/8. The message text shall be pseudorandomly generated. The evaluators compute the message digest for each of the messages and ensure that the correct result is produced when the messages are provided to the TSF.

Pseudorandomly Generated Messages Test

119 This test is for byte-oriented implementations only. The evaluators randomly generate a seed that is n bits long, where n is the length of the message digest produced by the hash function to be tested. The evaluators then formulate a set

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

of 100 messages and associated digests by following the algorithm provided in Figure 1 of [SHAVS]. The evaluators then ensure that the correct result is produced when the messages are provided to the TSF.

2.2.7 FCS_COP.1/KeyedHash Cryptographic Operation (Keyed Hash Algorithm)

Deleted: (4)

2.2.7.1 TSS

120 The evaluator shall examine the TSS to ensure that it specifies the following values used by the HMAC function: key length, hash function used, block size, and output MAC length used.

2.2.7.2 Tests

Deleted:Section Break (Next Page).....

121 For each of the supported parameter sets, the evaluator shall compose 15 sets of test data. Each set shall consist of a key and message data. The evaluator shall have the TSF generate HMAC tags for these sets of test data. The resulting MAC tags shall be compared to the result of generating HMAC tags with the same key and message data using a known good implementation.

Deleted:

Deleted: IV

2.2.8 FCS_RBG_EXT.1 Extended: Cryptographic Operation (Random Bit Generation)

122 Documentation shall be produced—and the evaluator shall perform the activities—in accordance with Appendix D of [NDcPP].

2.2.8.1 TSS

Deleted: 2.2.8.1 →

123 The evaluator shall examine the TSS to determine that it specifies the DRBG type, identifies the entropy source(s) seeding the DRBG, and state the assumed or calculated min-entropy supplied either separately by each source or the min-entropy contained in the combined seed value.

2.2.8.2 Guidance Documentation

124 The evaluator shall confirm that the guidance documentation contains appropriate instructions for configuring the RNG functionality.

2.2.8.3 Tests

125 The evaluator shall perform 15 trials for the RNG implementation. If the RNG is configurable, the evaluator shall perform 15 trials for each configuration.

Deleted: The evaluator shall also confirm that the guidance documentation contains appropriate instructions for configuring the RNG functionality.

126 If the RNG has prediction resistance enabled, each trial consists of (1) instantiate DRBG, (2) generate the first block of random bits (3) generate a second block of random bits (4) unstantiate. The evaluator verifies that the second block of random bits is the expected value. The evaluator shall generate eight input values for each trial. The first is a count (0 – 14). The next three are entropy input, nonce, and personalization string for the instantiate.

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

operation. The next two are additional input and entropy input for the first call to generate. The final two are additional input and entropy input for the second call to generate. These values are randomly generated. "generate one block of random bits" means to generate random bits with number of returned bits equal to the Output Block Length (as defined in NIST SP800-90A).

127 If the RNG does not have prediction resistance, each trial consists of (1) instantiate DRBG, (2) generate the first block of random bits (3) reseed, (4) generate a second block of random bits (5) uninstantiate. The evaluator verifies that the second block of random bits is the expected value. The evaluator shall generate eight input values for each trial. The first is a count (0 - 14). The next three are entropy input, nonce, and personalization string for the instantiate operation. The fifth value is additional input to the first call to generate. The sixth and seventh are additional input and entropy input to the call to reseed. The final value is additional input to the second generate call.

Deleted:

128 The following paragraphs contain more information on some of the input values to be generated/selected by the evaluator.

Deleted: ~~~~~Section Break (Next Page)~~~~~

Entropy input: the length of the entropy input value must equal the seed length.

Nonce: If a nonce is supported (CTR_DRBG with no Derivation Function does not use a nonce), the nonce bit length is one-half the seed length.

Personalization string: The length of the personalization string must be <= seed length. If the implementation only supports one personalization string length, then the same length can be used for both values. If more than one string length is support, the evaluator shall use personalization strings of two different lengths. If the implementation does not use a personalization string, no value needs to be supplied.

Additional input: the additional input bit lengths have the same defaults and restrictions as the personalization string lengths.

Moved (insertion) [15]

2.3 Identification and Authentication (FIA)

2.3.1 FIA AFL.1 Authentication Failure Management

2.3.1.1 TSS

129 The evaluator shall examine the TSS to determine that it contains a description, for each supported method for remote administrative actions, of how successive unsuccessful authentication attempts are detected and tracked. The TSS shall also describe the method by which the remote administrator is prevented from successfully logging on to the TOE, and the actions necessary to restore this ability.

Moved (insertion) [16]

130 The evaluator shall examine the TSS to confirm that the TOE ensures that authentication failures by remote administrators cannot lead to a situation

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

where no administrator access is available, either permanently or temporarily (e.g. by providing local logon which is not subject to blocking).

2.3.1.2 Guidance Documentation

131 The evaluator shall examine the guidance documentation to ensure that instructions for configuring the number of successive unsuccessful authentication attempts and time period (if implemented) are provided, and that the process of allowing the remote administrator to once again successfully log on is described for each “action” specified (if that option is chosen). If different actions or mechanisms are implemented depending on the secure protocol employed (e.g., TLS vs. SSH), all must be described.

132 The evaluator shall examine the guidance documentation to confirm that it describes, and identifies the importance of, any actions that are required in order to ensure that administrator access will always be maintained, even if remote administration is made permanently or temporarily unavailable due to blocking of accounts as a result of FIA_AFL.1.

Moved (insertion) [17]

2.3.1.3 Tests

133 The evaluator shall perform the following tests for each method by which remote administrators access the TOE (e.g. any passwords entered as part of establishing the connection protocol or the remote administrator application):

a) Test 1: The evaluator shall use the operational guidance to configure the number of successive unsuccessful authentication attempts allowed by the TOE (and, if the time period selection in FIA_AFL.1.2 is included in the ST, then the evaluator shall also use the operational guidance to configure the time period after which access is re-enabled). The evaluator shall test that once the authentication attempts limit is reached, authentication attempts with valid credentials are no longer successful.

b) Test 2: After reaching the limit for unsuccessful authentication attempts as in Test 1 above, the evaluator shall proceed as follows.

If the administrator action selection in FIA_AFL.1.2 is included in the ST then the evaluator shall confirm by testing that following the operational guidance and performing each action specified in the ST to re-enable the remote administrator’s access results in successful access (when using valid credentials for that administrator).

If the time period selection in FIA_AFL.1.2 is included in the ST then the evaluator shall wait for just less than the time period configured in Test 1 and show that an authorisation attempt using valid credentials does not result in successful access. The evaluator shall then wait until just after the time period configured in Test 1 and show that an authorisation attempt using valid credentials results in successful access.

Deleted: <object><object><object>

▼ Evaluation Activities for SFRs

2.3.2 FIA_PMG_EXT.1 Password Management

2.3.2.1 Guidance Documentation

134 The evaluator shall examine the guidance documentation to determine that it:

- a) identifies the characters that may be used in passwords and provides guidance to security administrators on the composition of strong passwords, and
- b) provides instructions on setting the minimum password length and describes the valid minimum password lengths supported.

2.3.2.2 Tests

135 The evaluator shall perform the following tests.

- a) Test 1: The evaluator shall compose passwords that either meet the requirements, or fail to meet the requirements, in some way. For each password, the evaluator shall verify that the TOE supports the password. While the evaluator is not required (nor is it feasible) to test all possible compositions of passwords, the evaluator shall ensure that all characters, and a minimum length listed in the requirement are supported, and justify the subset of those characters chosen for testing.

▼ **2.3.3 FIA_UIA_EXT.1 User Identification and Authentication**

2.3.3.1 TSS

136 The evaluator shall examine the TSS to determine that it describes the logon process for each logon method (local, remote (HTTPS, SSH, etc.)) supported for the product. This description shall contain information pertaining to the credentials allowed/used, any protocol transactions that take place, and what constitutes a “successful logon”.

137 The evaluator shall examine the TSS to determine that it describes which actions are allowed before user identification and authentication. The description shall cover authentication and identification for local and remote TOE administration.

138 For distributed TOEs the evaluator shall examine that the TSS details how Security Administrators are authenticated and identified by all TOE components. If not all TOE components support authentication of Security Administrators according to FIA_UIA_EXT.1 and FIA_UAU_EXT.2, the TSS shall describe how the overall TOE functionality is split between TOE components including how it is ensured that no unauthorized access to any TOE component can occur.

Deleted: <object>

Moved down [18]: <#>FCS_HTTPS_EXT.1 HTTPS [9]

Moved down [19]: <#> [1]

Moved down [20]: <#>an application notification... [6]

Moved down [23]: <#> [1]

Moved down [24]: <#> [1]

Moved down [39]: <#>flow in plaintext. The selectors

Deleted: <#> form the SPD in terms of the BYPASS [7]

Moved down [22]: <#> drop the packet), and

Deleted: <#>The evaluator shall perform the following [1]

Deleted: <#>Certificate validity shall be tested in ... [5]

Deleted: <#>11 [1]

Deleted: <#>The evaluator shall examine the TSS to [8]

Deleted: <#>The evaluator shall ensure the TSS ... [9]

Deleted: <#> [1]

Moved down [25]: <#>FCS_IPSEC_EXT.1.8 [1]

Moved down [26]: <#>The evaluator shall check to

Deleted: <#>(2) Cryptographic Operations (for ... [10]

Moved down [27]: <#>If pre-shared keys are chosen in

Deleted: <#>The evaluator shall verify that the TSS [11]

Moved down [28]: <#> [1]

Deleted: <#>, and if either AES-GCM-128 or AES [12]

Moved down [29]: <#> [1]

Deleted: <#>5 [1] ... [13]

Moved down [30]: <#> [1] ... [14]

Moved down [32]: <#> [1]

Moved down [51]: <#> evaluator shall configure a

Deleted: <#>6 [1] ... [15]

Moved down [33]: <#>evaluator just ensures that this

Deleted: <#>Currently there are no values mandated [16]

Deleted: <#>The evaluator ensures that the guidance [17]

Moved up [14]: <#> [1]

Deleted: <#>guidance documentation describes how [18]

Moved down [34]: <#> The description in the guidance

Deleted: <#>In order to construct the environment... and [19]

Moved down [35]: <#> [1]

Moved down [36]: <#> [1]

Deleted: <#>14 [1] ... [20]

Deleted: <#> 1

Moved down [37]: <#> [1]

Moved down [38]: <#>Test 1: The evaluator shall

Moved down [46]: <#> evaluator uses the guidance

Deleted: <#>the guidance documentation to configure [1]

Deleted: <#>

Moved down [40]: <#>send packets to the gateway [23]

Moved down [48]: <#> The evaluator shall initiate an

Deleted: <#> [1] ... [22]

Deleted: <#>The evaluator observes via the audit trail [24]

Moved down [42]: <#>: appropriate packets were

Moved down [43]: <#>created entries (there may be a

Moved down [44]: <#>The evaluator configures the

Deleted: <#>The evaluator shall then modify a field [25]

Deleted: <#>Test 1 (conditional): If tunnel mode is [26]

Moved down [45]: <#>The evaluator shall then initiate

Deleted: <#> cryptographic algorithms, authentication [27]

Deleted: <#>Test 1 (Conditional): The

Deleted: <#>Test 2: The

Moved down [47]: <#> evaluator shall configure the

Deleted: <#>(conditional): The

Deleted: <#> (conditional): The evaluator shall ... [28]

Deleted: <#>

Moved down [49]: <#>rekeying the SA when

Deleted: <#> [1] ... [29]

Moved down [50]: <#> If the two ends have the same

Deleted: that it

Deleted: ensure that all characters, rule [20]

Evaluation Activities for SFRs

Deleted: <object>

139 For distributed TOEs, the evaluator shall examine the TSS to determine that it describes for each TOE component which actions are allowed before user identification and authentication. The description shall cover authentication and identification for local and remote TOE administration. For each TOE component that does not support authentication of Security Administrators according to FIA_UIA_EXT.1 and FIA_UAU_EXT.2 the TSS shall describe any unauthenticated services/services that are supported by the component.

2.3.3.2 Guidance Documentation

140 The evaluator shall examine the guidance documentation to determine that any necessary preparatory steps (e.g., establishing credential material such as pre-shared keys, tunnels, certificates, etc.) to logging in are described. For each supported the login method, the evaluator shall ensure the guidance documentation provides clear instructions for successfully logging on. If configuration is necessary to ensure the services provided before login are limited, the evaluator shall determine that the guidance documentation provides sufficient instruction on limiting the allowed services.

2.3.3.3 Tests

141 The evaluator shall perform the following tests for each method by which administrators access the TOE (local and remote), as well as for each type of credential supported by the login method:

a) Test 1: The evaluator shall use the guidance documentation to configure the appropriate credential supported for the login method. For that credential/login method, the evaluator shall show that providing correct I&A information results in the ability to access the system, while providing incorrect information results in denial of access.

Deleted: ¶

Deleted:

b) Test 2: The evaluator shall configure the services allowed (if any) according to the guidance documentation, and then determine the services available to an external remote entity. The evaluator shall determine that the list of services available is limited to those specified in the requirement.

c) Test 3: For local access, the evaluator shall determine what services are available to a local administrator prior to logging in, and make sure this list is consistent with the requirement.

Deleted:

Deleted:

Deleted:

d) Test 4: For distributed TOEs where not all TOE components support the authentication of Security Administrators according to FIA_UIA_EXT.1 and FIA_UAU_EXT.2, the evaluator shall test that the components authenticate Security Administrators as described in the TSS.

Deleted:

Deleted:

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

2.3.4 FIA_UAU_EXT.2 Password-based Authentication Mechanism

142 Evaluation Activities for this requirement are covered under those for FIA_UIA_EXT.1. If other authentication mechanisms are specified, the evaluator shall include those methods in the activities for FIA_UIA_EXT.1.

2.3.5 FIA_UAU.7 Protected Authentication Feedback

2.3.5.1 Tests

143 The evaluator shall perform the following test for each method of local login allowed:

- a) Test 1: The evaluator shall locally authenticate to the TOE. While making this attempt, the evaluator shall verify that at most obscured feedback is provided while entering the authentication information.

2.4 Security management (FMT)

2.4.1 General requirements for distributed TOEs

2.4.1.1 TSS

144 For distributed TOEs it is required to verify the TSS to ensure that it describes how every function related to security management is realized for every TOE component and shared between different TOE components. The evaluator shall confirm that all relevant aspects of each TOE component are covered by the FMT SFRs.

2.4.1.2 Guidance Documentation

145 For distributed TOEs it is required to verify the Guidance Documentation to describe management of each TOE component. The evaluator shall confirm that all relevant aspects of each TOE component are covered by the FMT SFRs.

2.4.1.3 Tests

146 Tests defined to verify the correct implementation of security management functions shall be performed for every TOE component. For security management functions that are implemented centrally, sampling should be applied when defining the evaluator's tests (ensuring that all components are covered by the sample).

2.4.2 FMT MOF.1/ManualUpdate

2.4.2.1 TSS

147 For distributed TOEs see chapter 2.4.1.1. There are no specific requirements for non-distributed TOEs.

Deleted: <object>

Deleted:Section Break (Next Page).....

Deleted: <#>FIA_X509_EXT.1 X.509 Certificate Validation

Moved (insertion) [164]

Deleted: ensure the TSS describes where

Moved (insertion) [149]

Deleted: check of validity of

Deleted: certificates takes place.

Deleted: ensures

Moved (insertion) [77]

Deleted: TSS also provides a description of

Deleted: certificate path validation algorithm.

Moved down [165]: ¶

Tests ¶

Moved down [166]: ¶

Test 2: The evaluator shall demonstrate that validating an expired certificate results in the function failing. ¶

Test 3: The evaluator shall test that the TOE can properly handle revoked certificates—conditional on whether CRL or OCSP is selected; if both are selected, then a test shall be performed for each method. The evaluator shall test revocation of the TOE certificate and revocation of the TOE intermediate CA certificate i.e. the intermediate CA certificate should be revoked by the root CA. The evaluator shall ensure that a valid certificate is used, and that the validation function succeeds. The evaluator then attempts the test with a certificate that has been revoked (for each method chosen in the selection) to ensure when the certificate is no longer valid that the validation function fails.

Deleted: ¶

Moved down [167]: ¶

Test 4: If OCSP is selected, the evaluator shall configure the OCSP server or use a man-in-the-middle tool to present a certificate that does not have the OCSP signing purpose and verify that validation of the OCSP response fails. If CRL is selected, the evaluator shall configure the CA to sign a CRL

Deleted: ¶

... [32]

Moved down [168]: ¶

Test 5: The evaluator shall modify any byte in the first eight

Deleted: ¶

... [33]

Moved down [169]: ¶

Test 1: The evaluator shall construct a certificate path, such

Deleted: The evaluator shall perform the following tests for FIA_X509_EXT.1.1: ¶

Deleted: four certificates: the node certificate to be tested, two intermediate CAs, and the self-signed Root CA. ¶

Moved down [171]: <#>FIA_X509_EXT.2 X.509 Certificate Authentication ¶

Deleted: <#>The evaluator shall check the TSS to ensure that it describes how the TOE chooses which ¶

Deleted: <object><object><object>

Evaluation Activities for SFRs

2.4.2.2 Guidance Documentation

148 The evaluator shall examine the guidance documentation to determine that any necessary steps to perform manual update are described. The guidance documentation shall also provide warnings regarding functions that may cease to operate during the update (if applicable).

149 For distributed TOEs the guidance documentation shall describe all steps how to update all TOE components. This shall contain description of the order in which components need to be updated if the order is relevant to the update process. The guidance documentation shall also provide warnings regarding functions of TOE components and the overall TOE that may cease to operate during the update (if applicable).

2.4.2.3 Tests

150 The evaluator shall try to perform the update using a legitimate update image without prior authentication as security administrator (either by authentication as a user with no administrator privileges or without user authentication at all, depending on the configuration of the TOE). The attempt to update the TOE shall fail.

151 The evaluator shall try to perform the update with prior authentication as security administrator using a legitimate update image. This attempt should be successful. This test case should be covered by the tests for FPT_TUD_EXT.1 already.

2.4.3 FMT_MTD.1/CoreData Management of TSF Data

2.4.3.1 TSS

152 The evaluator shall examine the TSS to determine that, for each administrative function identified in the guidance documentation; those that are accessible through an interface prior to administrator log-in are identified. For each of these functions, the evaluator shall also confirm that the TSS details how the ability to manipulate the TSF data through these interfaces is disallowed for non-administrative users.

2.4.3.2 Guidance Documentation

153 The evaluator shall review the guidance documentation to determine that each of the TSF-data-manipulating functions implemented in response to the requirements of the cPP is identified, and that configuration information is provided to ensure that only administrators have access to the functions.

2.4.4 FMT_SMF.1 Specification of Management Functions

154 The security management functions for FMT_SMF.1 are distributed throughout the cPP and are included as part of the requirements in FTA_SSL_EXT.1, FTA_SSL.3, FTA_TAB.1, FMT_MOF.1/ManualUpdate, FMT_MOF.1/AutoUpdate (if included in the ST), FIA_AFL.1, FIA_X509_EXT.2.2 (if included in the ST), FPT_TUD_EXT.1.2 &

- Deleted: <object>
- Moved down [172]: The evaluator shall verify that
- Deleted: TSS to confirm that it describes the ... [35]
- Deleted: all supported administrator-configurable... [36]
- Deleted: ¶
- Moved down [173]: FIA_X509_EXT.3 Extended: X509
- Deleted: Section Break (Next Page)
- Moved down [174]: ¶
- Deleted: The evaluator shall then delete one of the ... [37]
- Moved up [164]: Security management (FMT) ¶
- Deleted: FMT_MOF.1(1)/TrustedUpdate ¶
- Deleted: – depending on the configuration of the ... [38]
- Moved (insertion) [175]
- Deleted: test...ttempt should pass ... [39]
- Deleted: <#>FMT_MOF.1(2)/TrustedUpdate ¶
- Moved down [176]: <#> ¶
- Deleted: <#>The evaluator shall try to enable and.. [40]
- Moved up [175]: <#> depending on the configuration
- Deleted: <#>This test should fail. ¶ ... [41]
- Moved down [177]: <#>Tests ¶
- Deleted: <#>The evaluator shall try to modify all... [42]
- Moved down [178]: <#> ¶
- Deleted: <#>modify all parameters for configuration... [43]
- Moved down [179]: <#>The effects of the
- Deleted: <#>The evaluator does not necessarily have to... [44]
- Moved down [180]: <#> ¶
- Deleted: <#>(2)/Audit ¶
- Moved down [181]: <#> ¶
- Deleted: <#>The evaluator shall try to modify all... [45]
- Moved down [182]: <#> The effects of the
- Deleted: <#> ¶ ... [46]
- Moved down [183]: <#> ¶
- Deleted: <#>The evaluator shall try to perform at least... [47]
- Moved down [184]: <#> ¶
- Deleted: <#>These attempts should succeed. ¶ ... [48]
- Moved up [17]: <#> ¶
- Deleted: <#>The evaluator shall try to perform at least... [49]
- Moved down [185]: <#> ¶
- Deleted: <#>try to perform at least one of the related... [50]
- Deleted: ...o ...the requirements of the cPP is ... [51]
- Moved down [186]: ¶
- Deleted: AdminAct Management of TSF Data ¶
- Moved down [187]: ¶
- Deleted: The evaluator shall try to perform at least one of... [52]
- Deleted: TAB...SL_EXT.1, FTA_SSL.3, ... [53]
- Deleted: <object><object><object>

Evaluation Activities for SFRs

FPT_TUD_EXT.2.2 (if included in the ST and if they include an administrator-configurable action), FMT_MOF.1/Services, and FMT_MOF.1/Functions (for all of these SFRs that are included in the ST), FMT_MTD, FPT_TST_EXT, and any cryptographic management functions specified in the reference standards. Compliance to these requirements satisfies compliance with FMT_SMF.1.

2.4.4.1 TSS (containing also requirements on Guidance Documentation and Tests)

155 The evaluator shall examine the TSS, Guidance Documentation and the TOE as observed during all other testing and shall confirm that the management functions specified in FMT_SMF.1 are provided by the TOE. The evaluator shall confirm that the TSS details which security management functions are available through which interface(s) (local administration interface, remote administration interface).

156 For distributed TOEs with the option 'ability to configure the interaction between TOE components' the evaluator shall examine that the ways to configure the interaction between TOE components is detailed in the TSS and Guidance Documentation. The evaluator shall check that the TOE behaviour observed during testing of the configured SFRs is as described in the TSS and Guidance Documentation.

2.4.4.2 Guidance Documentation

157 See section 2.4.4.1.

2.4.4.3 Tests

158 The evaluator tests management functions as part of testing the SFRs identified in section 2.4.4. No separate testing for FMT_SMF.1 is required unless one of the management functions in FMT_SMF.1.1 has not already been exercised under any other SFR.

2.4.5 FMT_SMR.2 Restrictions on security roles

2.4.5.1 Guidance Documentation

159 The evaluator shall review the guidance documentation to ensure that it contains instructions for administering the TOE both locally and remotely, including any configuration that needs to be performed on the client for remote administration.

2.4.5.2 Tests

160 In the course of performing the testing activities for the evaluation, the evaluator shall use all supported interfaces, although it is not necessary to repeat each test involving an administrative action with each interface. The evaluator shall ensure, however, that each supported method of administering the TOE that conforms to the requirements of this cPP be tested; for instance, if the TOE can be administered through a local hardware interface; SSH; and,

Deleted: <object>

Deleted: →

Deleted: →FMT_MOF.1(1)/Audit,

Deleted: (2)/Audit, →FMT_MOF.1.1(1)/AdminAct , FMT_MOF.1.1(2)/AdminAct

Deleted: LocSpace

Moved (insertion) [141]

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

TLS/HTTPS; then all three methods of administration must be exercised during the evaluation team's test activities.

2.5 Protection of the TSF (FPT)

2.5.1 FPT_SKP_EXT.1 Protection of TSF Data (for reading of all pre-shared, symmetric and private keys)

2.5.1.1 TSS

161 The evaluator shall examine the TSS to determine that it details how any pre-shared keys, symmetric keys, and private keys are stored and that they are unable to be viewed through an interface designed specifically for that purpose, as outlined in the application note. If these values are not stored in plaintext, the TSS shall describe how they are protected/obscured.

2.5.2 FPT_APW_EXT.1 Protection of Administrator Passwords

2.5.2.1 TSS

162 The evaluator shall examine the TSS to determine that it details all authentication data that are subject to this requirement, and the method used to obscure the plaintext password data when stored. The TSS shall also detail passwords are stored in such a way that they are unable to be viewed through an interface designed specifically for that purpose, as outlined in the application note.

2.5.3 FPT_TST_EXT.1 TSF testing

2.5.3.1 TSS

163 The evaluator shall examine the TSS to ensure that it details the self-tests that are run by the TSF; this description should include an outline of what the tests are actually doing (e.g., rather than saying "memory is tested", a description similar to "memory is tested by writing a value to each memory location and reading it back to ensure it is identical to what was written" shall be used). The evaluator shall ensure that the TSS makes an argument that the tests are sufficient to demonstrate that the TSF is operating correctly.

164 For distributed TOEs the evaluator shall examine the TSS to ensure that it details which TOE component performs which self-tests and when these self-tests are run.

2.5.3.2 Guidance Documentation

165 The evaluator shall also ensure that the guidance documentation describes the possible errors that may result from such tests, and actions the administrator should take in response; these possible errors shall correspond to those described in the TSS.

Deleted: <object>

Deleted: ¶

Deleted: 2.5.1.1 →

Deleted: 322 →

Deleted:

Deleted: ::::::::::::::::::::Section Break (Next Page)::::::::::::::::::

Deleted: ¶

Deleted:

Deleted: ¶

Deleted: <object><object><object>

Evaluation Activities for SFRs

166 For distributed TOEs the evaluator shall ensure that the guidance documentation describes how to determine from an error message returned which TOE component has failed the self-test.

2.5.3.3 Tests

167 It is expected that at least the following tests are performed:

- a) Verification of the integrity of the firmware and executable software of the TOE
- b) Verification of the correct operation of the cryptographic functions necessary to fulfil any of the SFRs.

168 Although formal compliance is not mandated, the self-tests performed should aim for a level of confidence comparable to:

- a) [FIPS 140-2], chap. 4.9.1, Software/firmware integrity test for the verification of the integrity of the firmware and executable software. Note that the testing is not restricted to the cryptographic functions of the TOE.
- b) [FIPS 140-2], chap. 4.9.1, Cryptographic algorithm test for the verification of the correct operation of cryptographic functions. Alternatively, national requirements of any CCRA member state for the security evaluation of cryptographic functions should be considered as appropriate.

169 The evaluator shall either verify that the self-tests described above are carried out during initial start-up or that the developer has justified any deviation from this.

170 For distributed TOEs the evaluator shall perform testing of self-tests on all TOE components according to the description in the TSS about which self-test are performed by which component.

2.5.4 FPT_TUD_EXT.1 Trusted Update

2.5.4.1 TSS

171 The evaluator shall verify that the TSS describe how to query the currently active version. If a trusted update can be installed on the TOE with a delayed activation, the TSS needs to describe how and when the inactive version becomes active. The evaluator shall verify this description.

172 The evaluator shall verify that the TSS describes all TSF software update mechanisms for updating the system firmware and software (for simplicity the term 'software' will be used in the following although the requirements apply to firmware and software). The evaluator shall verify that the description includes a digital signature verification of the software before installation and that installation fails if the verification fails. Alternatively an approach using a published hash can be used. In this case the TSS shall detail this mechanism.

Deleted: <object>

Moved (insertion) [165]

Moved down [188]: Tests

Deleted: Future versions of this cPP will mandate a clearly defined minimum set of self tests. But also for this version of the cPP it

Deleted: fulfil

Deleted:

Deleted: ,

Deleted: ,

Deleted: ¶

Deleted:

Deleted: either

Deleted: and

Deleted: (if applicable).

Moved down [189]: FPT_TST_EXT.2 - Self tests based on certificates

Tests

The

Deleted: ¶

Deleted: verify that the self test mechanism includes a certificate validation

Deleted: FIA_X509_EXT.1 and a check for

Deleted: Code Signing purpose

Deleted: extendedKeyUsage.

The evaluator shall use an invalid certificate and perform the

Deleted: test. This test

Moved down [190]: should fail. The evaluator shall use a certificate that does not have the Code Signing purpose and verify that the self test fails. The evaluator shall repeat the test using a valid certificate and a certificate that contains the Code Signing purpose and verify that the self test succeeds. Testing for this element is

Deleted: in conjunction with the assurance activities for FPT_TST_EXT.1...

Deleted: ¶

Deleted: software.

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

instead of the digital signature verification mechanism. The evaluator shall verify that the TSS describes the method by which the digital signature or published hash is verified to include how the candidate updates are obtained, the processing associated with verifying the digital signature or published hash of the update, and the actions that take place for both successful and unsuccessful signature verification or published hash verification.

173 If the options ‘support automatic checking for updates’ or ‘support automatic updates’ are chosen from the selection in FPT_TUD_EXT.1.2, the evaluator shall verify that the TSS explains what actions are involved in automatic checking or automatic updating by the TOE, respectively.

174 For distributed TOEs, the evaluator shall examine the TSS to ensure that it describes how all TOE components are updated, that it describes all mechanisms that support continuous proper functioning of the TOE during update (when applying updates separately to individual TOE components) and how verification of the signature or checksum is performed for each TOE component. Alternatively, this description can be provided in the guidance documentation. In that case the evaluator should examine the guidance documentation instead.

175 If the ST author indicates that a certificate-based mechanism is used for software update digital signature verification, the evaluator shall verify that the TSS contains a description of how the certificates are contained on the device. The evaluator also ensures that the TSS (or guidance documentation) describes how the certificates are installed/updated/selected, if necessary.

Deleted: ~~~~~Section Break (Next Page)~~~~~

176 If a published hash is used to protect the trusted update mechanism, then the evaluator shall verify that the trusted update mechanism does involve an active authorization step of the Security Administrator, and that download of the published hash value, hash comparison and update is not a fully automated process involving no active authorization by the Security Administrator. In particular, authentication as Security Administration according to FMT_MOF.1/ManualUpdate needs to be part of the update process when using published hashes.

2.5.4.2 Guidance Documentation

Moved (insertion) [185]

177 The evaluator shall verify that the guidance documentation describes how to query the currently active version. If a trusted update can be installed on the TOE with a delayed activation, the guidance documentation needs to describe how to query the loaded but inactive version.

178 The evaluator shall verify that the guidance documentation describes how the verification of the authenticity of the update is performed (digital signature verification or verification of published hash). The description shall include the procedures for successful and unsuccessful verification. The description shall correspond to the description in the TSS.

179 If a published hash is used to protect the trusted update mechanism, the evaluator shall verify that the guidance documentation describes how the

Deleted: <object><object><object>

▼ Evaluation Activities for SFRs

Deleted: <object>

Security Administrator can obtain authentic published hash values for the updates.

180 For distributed TOEs the evaluator shall verify that the guidance documentation describes how the versions of individual TOE components are determined for FPT_TUD_EXT.1, how all TOE components are updated, and the error conditions that may arise from checking or applying the update (e.g. failure of signature verification, or exceeding available storage space) along with appropriate recovery actions. . The guidance documentation only has to describe the procedures relevant for the user; it does not need to give information about the internal communication that takes place when applying updates.

181 If this information was not provided in the TSS: For distributed TOEs, the evaluator shall examine the Guidance Documentation to ensure that it describes how all TOE components are updated, that it describes all mechanisms that support continuous proper functioning of the TOE during update (when applying updates separately to individual TOE components) and how verification of the signature or checksum is performed for each TOE component.

182 If this information was not provided in the TSS: If the ST author indicates that a certificate-based mechanism is used for software update digital signature verification, the evaluator shall verify that the Guidance Documentation contains a description of how the certificates are contained on the device. The evaluator also ensures that the Guidance Documentation describes how the certificates are installed/updated/selected, if necessary.

2.5.4.3 Tests

183 The evaluator shall perform the following tests:

- a) Test 1: The evaluator performs the version verification activity to determine the current version of the product. If a trusted update can be installed on the TOE with a delayed activation, the evaluator shall also query the most recently installed version (for this test the TOE shall be in a state where these two versions match). The evaluator obtains a legitimate update using procedures described in the guidance documentation and verifies that it is successfully installed on the TOE. For some TOEs loading the update onto the TOE and activation of the update are separate steps ('activation' could be performed e.g. by a distinct activation step or by rebooting the device). In that case the evaluator verifies after loading the update onto the TOE but before activation of the update that the current version of the product did not change but the most recently installed version has changed to the new product version. After the update, the evaluator performs the version verification activity again to verify the version correctly corresponds to that of the update and that current version of the product and most recently installed version match again.

Deleted: as well as

Deleted: should be the same version before updating...

Deleted: ¶

Deleted: <object><object><object>

Evaluation Activities for SFRs

b) Test 2 (if digital signatures are used): The evaluator first confirms that no updates are pending and then performs the version verification activity to determine the current version of the product, verifying that it is different from the version claimed in the update(s) to be used in this test. The evaluator obtains or produces illegitimate updates as defined below, and attempts to install them on the TOE. The evaluator verifies that the TOE rejects all of the illegitimate updates. The evaluator performs this test using all of the following forms of illegitimate updates:

- 1) A modified version (e.g. using a hex editor) of a legitimately signed update,
- 2) An image that has not been signed,
- 3) An image signed with an invalid signature (e.g. by using a different key as expected for creating the signature or by manual modification of a legitimate signature),

4) If the TOE allows a delayed activation of updates the TOE must be able to display both the currently executing version and most recently installed version. The handling of version information of the most recently installed version might differ between different TOEs depending on the point in time when an attempted update is rejected. The evaluator shall verify that the TOE handles the most recently installed version information for that case as described in the guidance documentation. After the TOE has rejected the update the evaluator shall verify, that both, current version and most recently installed version, reflect the same version information as prior to the update attempt.

c) Test 3 (if published hash is verified on the TOE): If the published hash is provided to the TOE by the Security Administrator and the verification of the hash value over the update file(s) against the published hash is performed by the TOE, then the evaluator shall perform the following tests. The evaluator first confirms that no update is pending and then performs the version verification activity to determine the current version of the product, verifying that it is different from the version claimed in the update(s) to be used in this test.

- 1) The evaluator obtains or produces an illegitimate update such that the hash of the update does not match the published hash. The evaluator provides the published hash value to the TOE and calculates the hash of the update either on the TOE itself (if that functionality is provided by the TOE), or else outside the TOE. The evaluator confirms that the hash values are different, and attempts to install the update on the TOE, verifying that this fails because of the difference in hash values (and that the failure is logged). Depending on the

Deleted: <object>

Deleted: :

Deleted: as well as

Deleted: most recently installed

Deleted: (should

Deleted: the same version before updating).

Deleted: (if digital signatures are used) or a version that does not match the published hash (if published hashes are used)

Deleted: (if digital signatures are used) or an image without published hash (if published hashes are used)

Deleted: (only if digital signatures are used).

Deleted: <object><object><object>

▼ Evaluation Activities for SFRs

implementation of the TOE, the TOE might not allow the user to even attempt updating the TOE after the verification of the hash value fails. In that case the verification that the hash comparison fails is regarded as sufficient verification of the correct behaviour of the TOE

▼ 2) The evaluator uses a legitimate update and tries to perform verification of the hash value without storing the published hash value on the TOE. The evaluator confirms that this attempt fails. Depending on the implementation of the TOE it might not be possible to attempt the verification of the hash value without providing a hash value to the TOE, e.g. if the hash value needs to be handed over to the TOE as a parameter in a command line message and the syntax check of the command prevents the execution of the command without providing a hash value. In that case the mechanism that prevents the execution of this check shall be tested accordingly, e.g. that the syntax check rejects the command without providing a hash value, and the rejection of the attempt is regarded as sufficient verification of the correct behaviour of the TOE in failing to verify the hash. The evaluator then attempts to install the update on the TOE (in spite of the unsuccessful hash verification) and confirms that this fails. Depending on the implementation of the TOE, the TOE might not allow to even attempt updating the TOE after the verification of the hash value fails. In that case the verification that the hash comparison fails is regarded as sufficient verification of the correct behaviour of the TOE

3) If the TOE allows delayed activation of updates, the TOE must be able to display both the currently executing version and most recently installed version. The handling of version information of the most recently installed version might differ between different TOEs. Depending on the point in time when the attempted update is rejected, the most recently installed version might or might not be updated. The evaluator shall verify that the TOE handles the most recently installed version information for that case as described in the guidance documentation. After the TOE has rejected the update the evaluator shall verify, that both, current version and most recently installed version, reflect the same version information as prior to the update attempt.

184 If the verification of the hash value over the update file(s) against the published hash is not performed by the TOE, Test 3 shall be skipped.

185 The evaluator shall perform Test 1, Test 2 and Test 3 (if applicable) for all methods supported (manual updates, automatic checking for updates, automatic updates).

Deleted: <object>

Moved (insertion) [37]

Deleted: ~~~~~Section Break (Next Page)~~~~~

Deleted: the Tests

Deleted: 2

Deleted: <object><object><object>

Evaluation Activities for SFRs

186 For distributed TOEs the evaluator shall perform Test 1, Test 2 and Test 3 (if applicable) for all TOE components.

2.5.5 FPT_STM_EXT.1 Reliable Time Stamps

2.5.5.1 TSS

187 The evaluator shall examine the TSS to ensure that it lists each security function that makes use of time, and that it provides a description of how the time is maintained and considered reliable in the context of each of the time related functions.

2.5.5.2 Guidance Documentation

188 The evaluator examines the guidance documentation to ensure it instructs the administrator how to set the time. If the TOE supports the use of an NTP server, the guidance documentation instructs how a communication path is established between the TOE and the NTP server, and any configuration of the NTP client on the TOE to support this communication.

2.5.5.3 Tests

189 The evaluator shall perform the following tests:

- a) Test 1: If the TOE supports direct setting of the time by the Security Administrator then the evaluator uses the guidance documentation to set the time. The evaluator shall then use an available interface to observe that the time was set correctly.
- b) Test 2: If the TOE supports the use of an NTP server; the evaluator shall use the guidance documentation to configure the NTP client on the TOE, and set up a communication path with the NTP server. The evaluator will observe that the NTP server has set the time to what is expected. If the TOE supports multiple protocols for establishing a connection with the NTP server, the evaluator shall perform this test using each supported protocol claimed in the guidance documentation.

190 If the audit component of the TOE consists of several parts with independent time information, then the evaluator shall verify that the time information between the different parts are either synchronized or that it is possible for all audit information to relate the time information of the different part to one base information unambiguously.

Deleted: <object>

Moved down [191]:
FPT_TUD_EXT.2 Trusted Update based on certificates
TSS

Deleted: The

Deleted: verify that the TSS describes how the TOE reacts if X.509 certificates are used for trusted updates and the administrator attempts to

Deleted: the trusted update using an expired certificate.

Moved down [192]:
Guidance Documentation

The evaluator shall verify that the guidance documentation describes how the

Deleted: reacts if X.509 certificates are used for trusted updates and the administrator attempts to perform the trusted update using an expired certificate. The description shall correspond to the description in the TSS

Deleted: <#>Tests

<#>

<#>The evaluator shall verify that the update mechanism includes a certificate validation according to FIA_X509_EXT.1 and a check for the Code Signing purpose in the extendedKeyUsage.

<#>

<#>The evaluator shall digitally sign the update with an invalid certificate and verify that update installation fails. The evaluator shall digitally sign the application with a certificate that does not have the Code Signing purpose and verify that application installation fails. The evaluator shall repeat the test using a valid certificate and a certificate that contains the Code Signing purpose and verify that the application installation succeeds. The evaluator shall use a previously valid but expired certificate and verifies that the TOE reacts as described in the TSS and the guidance documentation. Testing for this element is performed in conjunction with the assurance activities for FPT_TUD_EXT.1.

<#>

Deleted: . The TSS

Deleted: The

Deleted:
2.5.8 FPT_FLS.1/LocSpace Failure with preservation of secure state
2.5.8.1

Deleted: <object><object><object>

Evaluation Activities for SFRs

2.6 TOE Access (FTA)

2.6.1 FTA_SSL_EXT.1 TSF-initiated Session Locking

2.6.1.1 Guidance Documentation

191 The evaluator shall confirm that the guidance documentation states whether local administrative session locking or termination is supported and instructions for configuring the inactivity time period.

2.6.1.2 Tests

192 The evaluator shall perform the following test:

- a) Test 1: The evaluator follows the guidance documentation to configure several different values for the inactivity time period referenced in the component. For each period configured, the evaluator establishes a local interactive session with the TOE. The evaluator then observes that the session is either locked or terminated after the configured time period. If locking was selected from the component, the evaluator then ensures that re-authentication is needed when trying to unlock the session.

2.6.2 FTA_SSL.3 TSF-initiated Termination

2.6.2.1 Guidance Documentation

193 The evaluator shall confirm that the guidance documentation states whether local administrative session locking or termination is supported and instructions for configuring the inactivity time period.

2.6.2.2 Tests

194 For each method of remote administration, the evaluator shall perform the following test:

- a) Test 1: The evaluator follows the guidance documentation to configure several different values for the inactivity time period referenced in the component. For each period configured, the evaluator establishes a remote interactive session with the TOE. The evaluator then observes that the session is terminated after the configured time period.

2.6.3 FTA_SSL.4 User-initiated Termination

2.6.3.1 Guidance Documentation

195 The evaluator shall confirm that the guidance documentation states how to terminate a local or remote interactive session.

Deleted: <#>

Moved down [193]: <#>Tests¶
<#>¶

Deleted: <#>The evaluator shall perform a test that the local storage space for audit data is not full (e.g. by executing an action that is logged and verifying that the audit data is updated accordingly). The evaluator shall test that the security functions are running properly (some sampling may be required here). Then the auditor shall execute activities that are logged until the local storage space for audit data is full. The evaluator shall verify that the security functions are no longer working or are no longer accessible. The security functions necessary to preserve the secure state according to¶
<#>¶
<#>FPT_FLS.1/Local Audit Storage Space Full shall be regarded as an exception to this rule, since they have to work properly to fulfil the requirement itself. If the evaluator has used sampling for the verification that the security functions did run properly when the local space for audit data was not full, then the evaluator shall verify for the same security functions that they have stopped working after the local storage space for audit data is full.¶
<#>¶

Moved down [194]: <#>Tests¶
<#>¶

Moved down [195]: <#>perform the following test:¶
<#>¶
<#>Test 1: The evaluator follows

Deleted: <#>to configure several different values

Deleted: <#> referenced in the component. For each period configured, the evaluator establishes a local interactive session with the TOE.

Moved down [196]: <#> The evaluator then observes that the session is either locked or terminated after the configured time period. If locking was selected from the component, the evaluator then ensures that

Deleted: <#> re- authentication is needed when trying to unlock the session

Moved down [197]: <#>FTA_SSL.3 TSF-initiated Termination¶
<#>¶

Moved (insertion) [196]

Moved (insertion) [197]

Moved (insertion) [150]

Moved (insertion) [193]

Moved (insertion) [195]

Deleted:

Deleted:

Deleted:

Moved down [198]: <#>Tests¶
<#>¶

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

2.6.3.2 Tests

Moved (insertion) [177]

196 For each method of remote administration, the evaluator shall perform the following tests:

- a) Test 1: The evaluator initiates an interactive local session with the TOE. The evaluator then follows the guidance documentation to exit or log off the session and observes that the session has been terminated.
- b) Test 2: The evaluator initiates an interactive remote session with the TOE. The evaluator then follows the guidance documentation to exit or log off the session and observes that the session has been terminated.

Deleted:

Deleted:

Deleted:

Deleted:

Deleted:

Deleted:

Deleted: ¶

2.6.4 FTA_TAB.1 Default TOE Access Banners

2.6.4.1 TSS

197 The evaluator shall check the TSS to ensure that it details each method of access (local and remote) available to the administrator (e.g., serial port, SSH, HTTPS).

2.6.4.2 Guidance Documentation

198 The evaluator shall check the guidance documentation to ensure that it describes how to configure the banner message.

2.6.4.3 Tests

199 The evaluator shall also perform the following test:

- a) Test 1: The evaluator follows the guidance documentation to configure a notice and consent warning message. The evaluator shall then, for each method of access specified in the TSS, establish a session with the TOE. The evaluator shall verify that the notice and consent warning message is displayed in each instance.

2.7 Trusted path/channels (FTP)

2.7.1 FTP_ITC.1 Inter-TSF trusted channel

2.7.1.1 TSS

200 The evaluator shall examine the TSS to determine that, for all communications with authorized IT entities identified in the requirement, each communications mechanism is identified in terms of the allowed protocols for that IT entity, and the method of assured identification of the non-TSF endpoint. The evaluator shall also confirm that all protocols listed in the TSS are specified and included in the requirements in the ST.

Deleted: .

Deleted: ¶

Deleted: <object><object><object>

▼ Evaluation Activities for SFRs

Deleted: <object>

2.7.1.2 Guidance Documentation

201 The evaluator shall confirm that the guidance documentation contains instructions for establishing the allowed protocols with each authorized IT entity, and that it contains recovery instructions should a connection be unintentionally broken.

2.7.1.3 Tests

202 The evaluator shall perform the following tests:

- a) Test 1: The evaluators shall ensure that communications using each protocol with each authorized IT entity is tested during the course of the evaluation, setting up the connections as described in the guidance documentation and ensuring that communication is successful.
- b) Test 2: For each protocol that the TOE can initiate as defined in the requirement, the evaluator shall follow the guidance documentation to ensure that in fact the communication channel can be initiated from the TOE.
- c) Test 3: The evaluator shall ensure, for each communication channel with an authorized IT entity, the channel data is not sent in plaintext.
- d) Test 4: The evaluators shall, for each protocol associated with each authorized IT entity tested during test 1, the connection is physically interrupted. The evaluator shall ensure that when physical connectivity is restored, communications are appropriately protected.

Deleted: ¶

203 Further assurance activities are associated with the specific protocols.

204 For distributed TOEs the evaluator shall perform tests on all TOE components according to the mapping of external secure channels to TOE components in the Security Target.

2.7.2 **FTP_TRP.1/Admin Trusted Path**

2.7.2.1 TSS

205 The evaluator shall examine the TSS to determine that the methods of remote TOE administration are indicated, along with how those communications are protected. The evaluator shall also confirm that all protocols listed in the TSS in support of TOE administration are consistent with those specified in the requirement, and are included in the requirements in the ST.

2.7.2.2 Guidance Documentation

206 The evaluator shall confirm that the guidance documentation contains instructions for establishing the remote administrative sessions for each supported method.

Deleted: ¶

Deleted: <object><object><object>

Evaluation Activities for SFRs

Deleted: <object>

2.7.2.3 Tests

207 The evaluator shall perform the following tests:

a) Test 1: The evaluators shall ensure that communications using each specified (in the guidance documentation) remote administration method is tested during the course of the evaluation, setting up the connections as described in the guidance documentation and ensuring that communication is successful.

b) Test 2: The evaluator shall ensure, for each communication channel, the channel data is not sent in plaintext.

Deleted: For

c) Test 3: The evaluators shall ensure that, for each protocol tested during test 1, the connection is physically interrupted. The evaluator shall ensure that when physical connectivity is restored, communications are appropriately protected.

Deleted: that the

208 Further assurance activities are associated with the specific protocols.

209 For distributed TOEs the evaluator shall perform tests on all TOE components according to the mapping of trusted paths to TOE components in the Security Target.

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

3 Evaluation Activities for Optional Requirements

3.1 Security Audit (FAU)

3.1.1 FAU STG.1 Protected audit trail storage

3.1.1.1 TSS

210 The evaluator shall examine the TSS to ensure it describes the amount of audit data that are stored locally and how these records are protected against unauthorized modification or deletion. The evaluator shall ensure that the TSS describes the conditions that must be met for authorized deletion of audit records.

211 For distributed TOEs the evaluator shall examine the TSS to ensure it describes to which TOE components this SFR applies and how local storage is implemented among the different TOE components (e.g. every TOE component does its own local storage or the data is sent to another TOE component for central local storage of all audit events).

3.1.1.2 Guidance Documentation

212 The evaluator shall examine the guidance documentation to determine that it describes any configuration required for protection of the locally stored audit data against unauthorized modification or deletion.

3.1.1.3 Tests

213 The evaluator shall perform the following tests:

a) ~~Test 1: The evaluator shall access the audit trail without authentication as Security Administrator (either by authentication as a non-administrative user, if supported, or without authentication at all) and attempt to modify and delete the audit records. The evaluator shall verify that these attempts fail. According to the implementation no other users than the Security Administrator might be defined and without any user authentication the user might not be able to get to the point where the attempt to access the audit trail can be executed. In that case it shall be demonstrated that access control mechanisms prevent execution up to the step that can be reached without authentication as Security Administrator.~~

b) ~~Test 2: The evaluator shall access the audit trail as an authorized administrator and attempt to delete the audit records. The evaluator shall verify that these attempts succeed. The evaluator shall verify that only the records authorized for deletion are deleted.~~

214 For distributed TOEs the evaluator shall perform test 1 and test 2 for each component that is defined by the TSS to be covered by this SFR.

Moved (insertion) [4]

Moved (insertion) [5]

Deleted: can initiate

Moved (insertion) [6]

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

3.1.2 FAU_STG_EXT.2/LocSpace Counting lost audit data

Moved (insertion) [9]

215 This activity should be accomplished in conjunction with the testing of FAU_STG_EXT.1.2 and FAU_STG_EXT.1.3.

3.1.2.1 TSS

216 The evaluator shall examine the TSS to ensure that it details the possible options the TOE supports for information about the number of audit records that have been dropped, overwritten, etc. if the local storage for audit data is full.

217 For distributed TOEs the evaluator shall examine the TSS to ensure it describes to which TOE components this SFR applies. Since this SFR is optional, it might only apply to some TOE components but not all. This might lead to the situation where all TOE components store their audit information themselves but FAU_STG_EXT.2/LocSpace is supported only by one of the components.

3.1.2.2 Guidance Documentation

Moved (insertion) [10]

218 The evaluator shall also ensure that the guidance documentation describes all possible configuration options and the meaning of the result returned by the TOE for each possible configuration. The description of possible configuration options and explanation of the result shall correspond to those described in the TSS.

219 The evaluator shall verify that the guidance documentation contains a warning for the administrator about the loss of audit data when clearing the local storage for audit records.

3.1.2.3 Tests

Moved (insertion) [187]

220 The evaluator shall verify that the numbers provided by the TOE according to the selection for FAU_STG_EXT.2/LocSpace are correct when performing the tests for FAU_STG_EXT.1.3.

221 For distributed TOEs the evaluator shall verify the correct implementation of counting of lost audit data for all TOE components that are supporting this feature according to the description in the TSS.

3.1.3 FAU_STG.3/LocSpace Action in case of possible audit data loss

Moved (insertion) [11]

222 This activity should be accomplished in conjunction with the testing of FAU_STG_EXT.1.2 and FAU_STG_EXT.1.3.

3.1.3.1 TSS

Moved (insertion) [12]

223 The evaluator shall examine the TSS to ensure that it details how the user is warned before the local storage for audit data is full.

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

224 For distributed TOEs the evaluator shall examine the TSS to ensure it describes to which TOE components this SFR applies and how each TOE component realises this SFR. Since this SFR is optional, it might only apply to some TOE components but not all. This might lead to the situation where all TOE components store their audit information themselves but FAU_STG.3/LocSpace is supported only by one of the components. In particular, the evaluator has to verify, that the TSS describes for every component supporting this functionality, whether the warning is generated by the component itself or through another component and name the corresponding component in the latter case. The evaluator has to verify that the TSS makes clear any situations in which audit records might be 'invisibly lost'.

3.1.3.2 Guidance Documentation

225 The evaluator shall also ensure that the guidance documentation describes how the user is warned before the local storage for audit data is full and how this warning is displayed or stored (since there is no guarantee that an administrator session is running at the time the warning is issued, it is probably stored in the log files). The description in the guidance documentation shall correspond to the description in the TSS.

3.1.3.3 Tests

226 The evaluator shall verify that a warning is issued by the TOE before the local storage space for audit data is full.

227 For distributed TOEs the evaluator shall verify the correct implementation of display warning for local storage space for all TOE components that are supporting this feature according to the description in the TSS. The evaluator shall verify that each component that supports this feature according to the description in the TSS is capable of generating a warning itself or through another component.

3.2 Identification and Authentication (FIA)

3.2.1 FIA X509 EXT.1/ITT X.509 Certificate Validation

3.2.1.1 TSS

228 The evaluator shall ensure the TSS describes where the check of validity of the certificates takes place, and that the TSS identifies any of the rules for extendedKeyUsage fields (in FIA X509 EXT.1.1) that are not supported by the TOE (i.e. where the ST is therefore claiming that they are trivially satisfied). If selected, the TSS shall describe how certificate revocation checking is performed. It is not sufficient to verify the status of a X.509 certificate only when it's loaded onto the device.

Moved (insertion) [13]

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

3.2.1.2 Tests

229 The evaluator shall demonstrate that checking the validity of a certificate is performed when a certificate is used in an authentication step. It is not sufficient to verify the status of a X.509 certificate only when it is loaded onto the device. The evaluator shall perform the following tests for FIA_X509_EXT.1.1/ITT:

a) Test 1a: The evaluator shall load a valid chain of certificates (terminating in a trusted CA certificate) as needed to validate the certificate to be used in the function, and shall use this chain to demonstrate that the function succeeds.

Test 1b: The evaluator shall then delete one of the certificates in the chain (i.e. the root CA certificate or other intermediate certificate, but not the end-entity certificate), and show that the function fails.

b) Test 2: The evaluator shall demonstrate that validating an expired certificate results in the function failing.

c) Test 3: The evaluator shall test that the TOE can properly handle revoked certificates—conditional on whether CRL or OCSP is selected; if both are selected, then a test shall be performed for each method. The evaluator shall test revocation of the TOE certificate and revocation of the TOE intermediate CA certificate i.e. the intermediate CA certificate should be revoked by the root CA. The evaluator shall ensure that a valid certificate is used, and that the validation function succeeds. The evaluator then attempts the test with a certificate that has been revoked (for each method chosen in the selection) to ensure when the certificate is no longer valid that the validation function fails. No testing is required if no revocation method is selected.

d) Test 4: If OCSP is selected, the evaluator shall configure the OCSP server or use a man-in-the-middle tool to present a certificate that does not have the OCSP signing purpose and verify that validation of the OCSP response fails. If CRL is selected, the evaluator shall configure the CA to sign a CRL with a certificate that does not have the cRLsign key usage bit set, and verify that validation of the CRL fails.

e) Test 5: The evaluator shall modify any byte in the first eight bytes of the certificate and demonstrate that the certificate fails to validate. (The certificate will fail to parse correctly.)

f) Test 6: The evaluator shall modify any byte in the last byte of the certificate and demonstrate that the certificate fails to validate. (The signature on the certificate will not validate.)

g) Test 7: The evaluator shall modify any byte in the public key of the certificate and demonstrate that the certificate fails to validate. (The hash of the certificate will not validate.)

Moved (insertion) [188]

Moved (insertion) [69]

Moved (insertion) [166]

Moved (insertion) [167]

Moved (insertion) [168]

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

230 The evaluator shall perform the following tests for FIA_X509_EXT.1.2/ITT. The tests described must be performed in conjunction with the other certificate services assurance activities, including the functions in FIA_X509_EXT.2.1/ITT. The tests for the extendedKeyUsage rules are performed in conjunction with the uses that require those rules. Where the TSS identifies any of the rules for extendedKeyUsage fields (in FIA_X509_EXT.1.1) that are not supported by the TOE (i.e. where the ST is therefore claiming that they are trivially satisfied) then the associated extendedKeyUsage rule testing may be omitted.

Moved (insertion) [169]

231 The evaluator shall create a chain of at least two certificates: the node certificate to be tested, and the self-signed Root CA.

Moved (insertion) [170]

- a) Test 1: The evaluator shall construct a certificate path, such that the certificate of the CA issuing the TOE's certificate does not contain the basicConstraints extension. The validation of the certificate path fails.
- b) Test 2: The evaluator shall construct a certificate path, such that the certificate of the CA issuing the TOE's certificate has the cA flag in the basicConstraints extension set to FALSE. The validation of the certificate path fails.
- c) Test 3: The evaluator shall construct a certificate path, such that the certificate of the CA issuing the TOE's certificate has the cA flag in the basicConstraints extension set to TRUE. The validation of the certificate path succeeds.

3.3 Security management (FMT)

3.3.1 FMT MOF.1/Services

3.3.1.1 TSS

232 For distributed TOEs see chapter 2.4.1.1. There are no specific requirements for non-distributed TOEs.

Moved (insertion) [176]

3.3.1.2 Tests

233 The evaluator shall try to enable and disable at least one of the services as defined in the Application Notes for FAU_GEN.1.1 (whichever is supported by the TOE) without prior authentication as security administrator (either by authenticating as a user with no administrator privileges, if possible, or without prior authentication at all). The attempt to enable/disable this service/these services should fail. According to the implementation no other users than the Security Administrator might be defined and without any user authentication the user might not be able to get to the point where the attempt to enable/disable this service/these services can be executed. In that case it shall be demonstrated that access control mechanisms prevent execution up to the step that can be reached without authentication as Security Administrator.

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

234 The evaluator shall try to enable and disable at least one of the services as defined in the Application Notes for FAU_GEN.1.1 (whichever is supported by the TOE) with prior authentication as security administrator. The attempt to enable/disable this service/these services should be successful.

Moved (insertion) [186]

3.3.2 FMT_MTD.1/CryptoKeys Management of TSF Data

3.3.2.1 TSS

235 For distributed TOEs see chapter 2.4.1.1. There are no specific requirements for non-distributed TOEs.

Moved (insertion) [183]

3.3.2.2 Tests

236 The evaluator shall try to perform at least one of the related actions (modify, delete, generate/import) without prior authentication as security administrator (either by authentication as a non-administrative user, if supported, or without authentication at all). Attempts to perform related actions without prior authentication should fail. According to the implementation no other users than the Security Administrator might be defined and without any user authentication the user might not be able to get to the point where the attempt to manage cryptographic keys can be executed. In that case it shall be demonstrated that access control mechanisms prevent execution up to the step that can be reached without authentication as Security Administrator.

Moved (insertion) [184]

237 The evaluator shall try to perform at least one of the related actions with prior authentication as security administrator. This attempt should be successful.

3.4 Protection of the TSF (FPT)

3.4.1 FPT_ITT.1 Basic internal TSF data transfer protection

238 If the TOE is not a distributed TOE then no evaluator action is necessary. For a distributed TOE the evaluator carries out the activities below.

3.4.1.1 TSS

239 The evaluator shall examine the TSS to determine that, for all communications between components of a distributed TOE, each communications mechanism is identified in terms of the allowed protocols for that IT entity. The evaluator shall also confirm that all protocols listed in the TSS for these inter-component communications are specified and included in the requirements in the ST.

3.4.1.2 Guidance Documentation

240 The evaluator shall confirm that the guidance documentation contains instructions for establishing the relevant allowed communication channels and protocols between each pair of authorized TOE components, and that it contains recovery instructions should a connection be unintentionally broken.

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

3.4.1.3 Tests

241 The evaluator shall perform the following tests:

- a) Test 1: The evaluator shall ensure that communications using each protocol between each pair of authorized TOE components is tested during the course of the evaluation, setting up the connections as described in the guidance documentation and ensuring that communication is successful.
- b) Test 2: The evaluator shall ensure, for each communication channel with an authorized IT entity, the channel data is not sent in plaintext.
- c) Test 3: The evaluator shall, for each protocol associated with each authorized IT entity tested during test a), the connection is physically interrupted. The evaluator shall ensure that when physical connectivity is restored, communications are appropriately protected.

242 Further assurance activities are associated with the specific protocols.

3.5 Trusted path/channels (FTP)

3.5.1 FTP TRP.1/Join Trusted Path

3.5.1.1 TSS

243 The evaluator shall examine the TSS to determine that the methods of joining components to the TOE are identified, along with how those communications are protected, including identification of whether the environment is required to provide confidentiality of the communications or whether the registration data exchanged does not require confidentiality. If the TSS asserts that registration data does not require confidentiality protection then the evaluator shall examine the justification provided to confirm that.

244 The evaluator shall also check that all protocols listed in the TSS in support of this process are included in the SFRs in the ST, and that if the ST uses FPT_TRP.1/Join for the registration channel then this channel cannot be reused as the normal inter-component communication channel (the latter channel must meet FTP_ITC.1 or FPT_ITT.1).

3.5.1.2 Guidance Documentation

245 The evaluator shall examine the guidance documentation to confirm that it contains instructions for establishing and using the enablement and registration channel. The evaluator shall confirm that the guidance documentation makes clear which component initiates the communication. The evaluator shall confirm that the guidance documentation contains recovery instructions should a connection be unintentionally broken during the registration process.

246 In the case of a distributed TOE that relies on the operational environment to provide security for some aspects of the registration channel security then

Moved (insertion) [198]

Moved (insertion) [86]

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

there are particular requirements on the Preparative Procedures as listed below. (Reliance on the operational environment in this way is indicated in an ST by a reference to operational guidance in the assignment in FTP_TRP.1.3/Join.) In this case the evaluator shall examine the Preparative Procedures to confirm that they:

- a) clearly state the strength of the authentication and encryption provided by the registration channel itself and the specific requirements on the environment used for joining components to the TOE (e.g. where the environment is relied upon to prevent interception of sensitive messages, IP spoofing attempts, man-in-the-middle attacks, or race conditions)
- b) identify what confidential values are transmitted over the enablement channel (e.g. any keys, their lengths, and their purposes), use of any non-confidential keys (e.g. where a developer uses the same key for more than one device or across all devices of a type or family), and use of any unauthenticated identification data (e.g. IP addresses, self-signed certificates)
- c) highlight any situation in which a secret value/key may be transmitted over a channel that uses a key of lower comparable strength than the transmitted value/key. Comparable strength is defined as the amount of work required to compromise the algorithm or key and is typically expressed as 'bits' of security. The ST author and evaluator should consult NIST 800-57 Table 2 for further guidance on comparable algorithm strength.

3.5.1.3 Tests

247 The evaluator shall perform the following tests:

- a) Test 1: The evaluator shall ensure that the communications path for joining components to the TSF is tested for each distinct (non-equivalent) component type⁴, setting up the connections as described in the guidance documentation and ensuring that communication is successful. In particular the evaluator shall confirm that requirements on environment protection for the registration process are consistent with observations made on the test configuration (for example, a requirement to isolate the components from the Internet during registration might be inconsistent with the need for a component to contact a license server). If no requirements on the registration environment are identified as necessary to protect confidentiality, then the evaluator shall confirm that the key used for registration can be configured (following the instructions in the guidance documentation) to be at least the same length as the key used for the internal TSF

⁴The intention here is to cover all different software sections involved. For example, a single software image may be installed on different TOE components, but with different sections of the image executed according to the hardware platform or communications stack. In such as case tests should be carried out for each different software section.

Moved (insertion) [181]

Moved (insertion) [96]

Deleted: in the

Deleted: , the

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

channel that is being enabled. The evaluator shall confirm that the key used for the channel is unique to the pair of components (this is done by identifying the relevant key during the registration test: it is not necessary to examine the key value).

- b) Test 2: The evaluator shall follow the guidance documentation to ensure that in fact the communication channel can be enabled by an administrator for all the TOE components identified in the guidance documentation as capable of initiation.
- c) Test 3: The evaluator shall ensure that if the guidance documentation states that the channel data is encrypted then the data observed on the channel is not plaintext.
- d) Test 4: The evaluator shall ensure that, for each different pair of non-equivalent component types that can use the registration channel, the connection is physically interrupted during a joining attempt. The evaluator shall ensure that when physical connectivity is restored, communications are appropriately protected.

248 Further assurance activities are associated with the specific protocols.

3.6 Communication (FCO)

3.6.1 FCO CPC EXT.1 Component Registration Channel Definition

249 If the TOE is not a distributed TOE then no evaluator action is necessary. For a distributed TOE the evaluator carries out the activities below. In carrying out these activities the evaluator shall determine answers to the following questions based on a combination of documentation analysis and testing (possibly also using input from carrying out the Evaluation Activities for the relevant registration channel, such as FTP_TRP.1/Join), and shall report the answers.

- a) What stops⁵ a component from successfully communicating with TOE components (in a way that enables it to participate as part of the TOE) before it has properly authenticated and joined the TOE?

⁵The intent of the phrasing “what stops...” as opposed to “what secures...” is for the evaluator to pursue the answer to its lowest level of dependency, i.e. a level at which the security can clearly be seen to depend on things that are under appropriate control. For example, a channel may be protected by a public key that is provided to the relying party in a self-signed certificate. This enables cryptographic mechanisms to be applied to provide authentication (and therefore invites an answer that “the check on the public key certificate secures...”), but does not ultimately stop an attacker from apparently authenticating because the attacker can produce their own self-signed certificate. The question “what stops an unauthorised component from successfully communicating...” focuses attention on what an attacker needs to do, and therefore pushes the answer down to the level of whether a self-signed certificate could be produced by an attacker. Similarly a well-known key, or a key that is common to a type of device rather than an individual device, may be used in a confidentiality mechanism but does not provide confidentiality because an attacker can find the well-known key or obtain his own instance of a device containing the non-unique key.

Deleted: initiated from the TOE

Deleted: , for each communication channel with an authorized IT entity,

Deleted: data

Deleted: sent in

Deleted: evaluators

Deleted: protocol associated with each authorized IT entity tested during test 1

Deleted: ¶
¶

Deleted: .

Deleted: =====Section Break (Next Page)=====

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

- b) What is the enablement step? (Describe what interface it uses, with a reference to the relevant section and step in the operational guidance).
 - 1) What stops anybody other than a Security Administrator from carrying out this step?
 - 2) How does the Security Administrator know that they are enabling the intended component to join? (Identification of the joiner might be part of the enablement action itself or might be part of secure channel establishment, but it must prevent unintended joining of components)
- c) What stops a component successfully joining if the Administrator has not carried out the enablement step; or, equivalently, how does the TOE ensure that an action by an authentic Administrator is required before a component can successfully join?
- d) What stops a component from carrying out the registration process over a different, insecure channel?
- e) If the FTP_TRP.1/Join channel type is selected in FCO_CPC_EXT.1.2 then how do the registration process and its secure channel ensure that the data is protected from disclosure and provides detection of modification?
- f) Where the registration channel does not rely on protection of the registration environment, does the registration channel provide a sufficient level of protection (especially with regard to confidentiality) for the data that passes over it?
- g) Where the registration channel is subsequently used for normal internal communication between TOE components (i.e. after the joiner has completed registration), do any of the authentication or encryption features of the registration channel result in use of a channel that has weaker protection than the normal FPT_ITT.1 requirements for such a channel?
- h) What is the disablement step? (Describe what interface it uses, with a reference to the relevant section and step in the operational guidance).
- i) What stops a component successfully communicating with other TOE components if the Administrator has carried out the disablement step?

3.6.1.1 TSS

250 (Note: paragraph 249 lists questions for which the evaluator needs to determine and report answers through the combination of the TSS, Guidance Documentation, and Tests Evaluation Activities.)

251 The evaluator shall examine the TSS to confirm that it:

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

- a) Describes the method by which a Security Administrator enables and disables communications between pairs of TOE components.
- b) Describes the relevant details according to the type of channel in the main selection made in FCO_CPC_EXT.1.2:
 - First type: the TSS identifies the relevant SFR iteration that specifies the channel used
 - Second type: the TSS (with support from the operational guidance if selected in FTP_TRP.1.3/Join) describes details of the channel and the mechanisms that it uses (and describes how the process ensures that the key is unique to the pair of components) – see also the Evaluation Activities for FTP_TRP.1/Join.

252 The evaluator shall confirm that if any aspects of the registration channel are identified as not meeting FTP_ITC.1 or FPT_ITT.1, then the ST has also selected the FTP_TRP.1/Join option in the main selection in FCO_CPC_EXT.1.2.

3.6.1.2 Guidance Documentation

253 (Note: paragraph 249 lists questions for which the evaluator needs to determine and report answers through the combination of the TSS, Guidance Documentation, and Tests Evaluation Activities.)

254 The evaluator shall examine the guidance documentation to confirm that it contains instructions for enabling and disabling communications with any individual component of a distributed TOE. The evaluator shall confirm that the method of disabling is such that all other components can be prevented from communicating with the component that is being removed from the TOE (preventing the remaining components from either attempting to initiate communications to the disabled component, or from responding to communications from the disabled component).

255 The evaluator shall examine the guidance documentation to confirm that it includes recovery instructions should a connection be unintentionally broken during the registration process.

256 If the TOE uses a registration channel for registering components to the TOE (i.e. where the ST author uses the FTP_ITC.1/FPT_ITT.1 or FTP_TRP.1/Join channel types in the main selection for FCO_CPC_EXT.1.2) then the evaluator shall examine the Preparative Procedures to confirm that they:

- a) describe the security characteristics of the registration channel (e.g. the protocol, keys and authentication data on which it is based) and shall highlight any aspects which do not meet the requirements for a steady-state inter-component channel (as in FTP_ITC.1 or FPT_ITT.1)
- b) identify any dependencies between the configuration of the registration channel and the security of the subsequent inter-component

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

communications (e.g. where AES-256 inter-component communications depend on transmitting 256 bit keys between components and therefore rely on the registration channel being configured to use an equivalent key length)

- c) identify any aspects of the channel can be modified by the operational environment in order to improve the channel security, and shall describe how this modification can be achieved (e.g. generating a new key pair, or replacing a default public key certificate).

257 As background for the examination of the registration channel description, it is noted that the requirements above are intended to ensure that administrators can make an accurate judgement of any risks that arise from the default registration process. Examples would be the use of self-signed certificates (i.e. certificates that are not chained to an external or local Certification Authority), manufacturer-issued certificates (where control over aspects such as revocation, or which devices are issued with recognised certificates, is outside the control of the operational environment), use of generic/non-unique keys (e.g. where the same key is present on more than one instance of a device), or well-known keys (i.e. where the confidentiality of the keys is not intended to be strongly protected – note that this need not mean there is a positive action or intention to publicise the keys).

258 In the case of a distributed TOE for which the ST author uses the FTP TRP.1/Join channel type in the main selection for FCO CPC EXT.1.2 and the TOE relies on the operational environment to provide security for some aspects of the registration channel security then there are additional requirements on the Preparative Procedures as described in section 3.5.1.2.

3.6.1.3 Tests

259 (Note: paragraph 249 lists questions for which the evaluator needs to determine and report answers through the combination of the TSS, Guidance Documentation, and Tests Evaluation Activities.)

260 The evaluator shall carry out the following tests:

- a) Test 1.1: the evaluator shall confirm that an IT entity that is not currently a member of the distributed TOE cannot communicate with any component of the TOE until the non-member entity is enabled by a Security Administrator for each of the non-equivalent TOE components⁶ that it is required to communicate with (non-equivalent

⁶ An 'equivalent TOE component' is a type of distributed TOE component that exhibits the same security characteristics, behaviour and role in the TSF as some other TOE component. In principle a distributed TOE could operate with only one instance of each equivalent TOE component, although the minimum configuration of the distributed TOE may include more than one instance (see discussion of the minimum configuration of a distributed TOE, in section B.4). In practice a deployment of the TOE may include more than one instance of some equivalent TOE components for practical reasons, such as performance or the need to have separate instances for separate subnets or VLANs.

Moved (insertion) [78]

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

TOE components are as defined in the minimum configuration for the distributed TOE)

- b) Test 1.2: the evaluator shall confirm that after enablement, an IT entity can communicate only with the components that it has been enabled for. This includes testing that the enabled communication is successful for the enabled component pair, and that communication remains unsuccessful with any other component for which communication has not been explicitly enabled

Some TOEs may set up the registration channel before the enablement step is carried out, but in such a case the channel must not allow communications until after the enablement step has been completed.

261 The evaluator shall repeat Tests 1.1 and 1.2 for each different type of enablement process that can be used in the TOE.

- c) Test 2: The evaluator shall separately disable each TOE component in turn and ensure that the other TOE components cannot then communicate with the disabled component, whether by attempting to initiate communications with the disabled component or by responding to communication attempts from the disabled component.

- d) Test 3: The evaluator shall carry out the following tests according to those that apply to the values of the main (outer) selection made in the ST for FCO_CPC_EXT.1.2.

1) If the ST uses the first type of communication channel in the selection in FCO_CPC_EXT.1.2 then the evaluator tests the channel via the Evaluation Activities for FTP_ITC.1 or FPT_ITT.1 according to the second selection – the evaluator shall ensure that the test coverage for these SFRs includes their use in the registration process.

2) If the ST uses the second type of communication channel in the selection in FCO_CPC_EXT.1.2 then the evaluator tests the channel via the Evaluation Activities for FTP_TRP.1/Join.

3) If the ST uses the 'no channel' selection then no test is required.

- e) Test 4: The evaluator shall perform one of the following tests, according to the TOE characteristics identified in its TSS and operational guidance:

1) If the registration channel is not subsequently used for inter-component communication, and in all cases where the second selection in FCO_CPC_EXT.1.2 is made (i.e. using FTP_TRP.1/Join) then the evaluator shall confirm that the registration channel can no longer be used after the registration process has completed, by attempting to use the channel to communicate with each of the endpoints after registration has completed

Deleted: <object><object><object>

Evaluation Activities for Optional Requirements

- 2) If the registration channel is subsequently used for inter-component communication then the evaluator shall confirm that any aspects identified in the operational guidance as necessary to meet the requirements for a steady-state inter-component channel (as in FTP ITC.1 or FPT ITT.1) can indeed be carried out (e.g. there might be a requirement to replace the default key pair and/or public key certificate).
- f) Test 5: For each aspect of the security of the registration channel that operational guidance states can be modified by the operational environment in order to improve the channel security (cf. AGD PRE.1 refinement item 2 in (cf. the requirements on Preparative Procedures in 3.6.1.2), the evaluator shall confirm, by following the procedure described in the operational guidance, that this modification can be successfully carried out.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

4 Evaluation Activities for Selection-Based Requirements

4.1 Cryptographic Support (FCS)

4.1.1 FCS DTLSC EXT.1 Extended: DTLS Client Protocol

4.1.1.1 TSS

FCS DTLSC EXT.1.1

262 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that the ciphersuites supported are specified. The evaluator shall check the TSS to ensure that the ciphersuites specified include those listed for this component.

FCS DTLSC EXT.1.2

263 The evaluator shall ensure that the TSS describes the client's method of establishing all reference identifiers from the administrator/application-configured reference identifier, including which types of reference identifiers are supported (e.g. Common Name, DNS Name, URI Name, Service Name, or other application-specific Subject Alternative Names) and whether IP addresses and wildcards are supported. The evaluator shall ensure that this description identifies whether and the manner in which certificate pinning is supported or used by the TOE.

264 Note that where a DTLS channel is being used between components of a distributed TOE for FPT_ITT.1, the requirements to have the reference identifier established by the user are relaxed and the identifier may also be established through a "Gatekeeper" discovery process. The TSS should describe the discovery process and highlight how the reference identifier is supplied to the "joining" component.

FCS DTLSC EXT.1.4

265 The evaluator shall verify that TSS describes the Supported Elliptic Curves Extension and whether the required behaviour is performed by default or may be configured.

4.1.1.2 Guidance Documentation

FCS DTLSC EXT.1.1

266 The evaluator shall also check the guidance documentation to ensure that it contains instructions on configuring the TOE so that DTLS conforms to the description in the TSS.

Moved (insertion) [89]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS DTLSC EXT.1.2

267 The evaluator shall verify that the AGD guidance includes instructions for setting the reference identifier to be used for the purposes of certificate validation in DTLS.

FCS DTLSC EXT.1.4

268 If the TSS indicates that the Supported Elliptic Curves Extension must be configured to meet the requirement, the evaluator shall verify that AGD guidance includes configuration of the Supported Elliptic Curves Extension.

4.1.1.3 Tests

269 For clarification: For DTLS communication packets might be received in a different order than sent due to the use of the UDP protocol. All tests requiring a specific order of test steps ("before", "after") are therefore referring to the sequence numbering of DTLS packets.

FCS DTLSC EXT.1.1

270 Test 1: The evaluator shall establish a DTLS connection using each of the ciphersuites specified by the requirement. This connection may be established as part of the establishment of a higher-level application protocol, e.g., as part of a syslog session. It is sufficient to observe the successful negotiation of a ciphersuite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic in an attempt to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).

271 Test 2: The evaluator shall attempt to establish the connection using a server with a server certificate that contains the Server Authentication purpose in the extendedKeyUsage field and verify that a connection is established. The evaluator will then verify that the client rejects an otherwise valid server certificate that lacks the Server Authentication purpose in the extendedKeyUsage field and a connection is not established. Ideally, the two certificates should be identical except for the extendedKeyUsage field.

272 Test 3: The evaluator shall send a server certificate in the DTLS connection that does not match the server-selected ciphersuite (for example, send a ECDSA certificate while using the TLS_RSA_WITH_AES_128_CBC_SHA ciphersuite). The evaluator shall verify that the TOE disconnects after receiving the server's Certificate handshake message.

273 Test 4: The evaluator shall configure the server to select the TLS_NULL_WITH_NULL_NULL ciphersuite and verify that the client denies the connection.

274 Test 5: The evaluator performs the following modifications to the traffic:

- a) Change the DTLS version selected by the server in the Server Hello to a non-supported DTLS version (for example 1.3 represented by the two bytes 03 04) and verify that the client rejects the connection.

Moved (insertion) [93]

Moved (insertion) [94]

Moved (insertion) [95]

Moved (insertion) [118]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- b) If using DHE or ECDH, modify at least one byte in the server's nonce in the Server Hello handshake message, and verify that the client rejects the Server Key Exchange handshake message (if using a DHE or ECDHE ciphersuite) or that the server denies the client's Finished handshake message.
- c) Modify the server's selected ciphersuite in the Server Hello handshake message to be a ciphersuite not presented in the Client Hello handshake message. The evaluator shall verify that the client rejects the connection after receiving the Server Hello.
- d) If using DHE or ECDH, modify the signature block in the Server's Key Exchange handshake message, and verify that the client rejects the connection after receiving the Server Key Exchange message. This test does not apply to cipher suites using RSA key exchange. If a TOE only supports RSA key exchange in conjunction with TLS then this test shall be omitted.
- e) Modify a byte in the Server Finished handshake message, and verify that the client sends a fatal alert upon receipt and does not send any application data.
- f) Send a garbled message from the Server after the Server has issued the ChangeCipherSpec message and verify that the client denies the connection.

FCS_DTLSC_EXT.1.2

275 Note that where a DTLS channel is being used between components of a distributed TOE for FPT_ITT.1, the requirements to have the reference identifier established by the user are relaxed and the identifier may also be established through a "Gatekeeper" discovery process. The TSS should describe the discovery process and highlight how the reference identifier is supplied to the "joining" component.

276 The evaluator shall configure the reference identifier according to the AGD guidance and perform the following tests during a DTLS connection:

- a) Test 1: The evaluator shall present a server certificate that does not contain an identifier in either the Subject Alternative Name (SAN) or Common Name (CN) that matches the reference identifier. The evaluator shall verify that the connection fails.
- b) Test 2: The evaluator shall present a server certificate that contains a CN that matches the reference identifier, contains the SAN extension, but does not contain an identifier in the SAN that matches the reference identifier. The evaluator shall verify that the connection fails. The evaluator shall repeat this test for each supported SAN type.
- c) Test 3: The evaluator shall present a server certificate that contains a CN that matches the reference identifier and does not contain the SAN extension. The evaluator shall verify that the connection succeeds.

Moved (insertion) [97]

Moved (insertion) [98]

Moved (insertion) [122]

Moved (insertion) [102]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- d) Test 4: The evaluator shall present a server certificate that contains a CN that does not match the reference identifier but does contain an identifier in the SAN that matches. The evaluator shall verify that the connection succeeds.
- e) Test 5: The evaluator shall perform the following wildcard tests with each supported type of reference identifier:
- 1) The evaluator shall present a server certificate containing a wildcard that is not in the left-most label of the presented identifier (e.g. foo.*.example.com) and verify that the connection fails.
 - 2) The evaluator shall present a server certificate containing a wildcard in the left-most label (e.g. *.example.com). The evaluator shall configure the reference identifier with a single left-most label (e.g. foo.example.com) and verify that the connection succeeds. The evaluator shall configure the reference identifier without a left-most label as in the certificate (e.g. example.com) and verify that the connection fails. The evaluator shall configure the reference identifier with two left-most labels (e.g. bar.foo.example.com) and verify that the connection fails.
- f) Test 6: [conditional] If URI or Service name reference identifiers are supported, the evaluator shall configure the DNS name and the service identifier. The evaluator shall present a server certificate containing the correct DNS name and service identifier in the URIName or SRVName fields of the SAN and verify that the connection succeeds. The evaluator shall repeat this test with the wrong service identifier (but correct DNS name) and verify that the connection fails.
- g) Test 7: [conditional] If pinned certificates are supported the evaluator shall present a certificate that does not match the pinned certificate and verify that the connection fails.

Moved (insertion) [103]

Moved (insertion) [125]

FCS DTLSC EXT.1.3

- 277 Test 1: The evaluator shall demonstrate that using a certificate without a valid certification path results in the function failing. Using the administrative guidance, the evaluator shall then load a certificate or certificates needed to validate the certificate to be used in the function, and demonstrate that the function succeeds. If the certificate is validated and a trusted channel is established, the test passes. The evaluator then shall delete one of the certificates, and show that the certificate is not validated and the trusted channel is not established.

Moved (insertion) [106]

FCS DTLSC EXT.1.4

- 278 Test 1: If using ECDHE ciphers, the evaluator shall configure the server to perform an ECDHE key exchange in the DTLS connection using a non-

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

supported curve (for example P-192) and shall verify that the TOE disconnects after receiving the server's Key Exchange handshake message.

Moved (insertion) [108]

4.1.2 FCS_DTLSC_EXT.2 Extended: DTLS Client Protocols with authentication

4.1.2.1 TSS

FCS_DTLSC_EXT.2.1

279 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that the ciphersuites supported are specified. The evaluator shall check the TSS to ensure that the ciphersuites specified include those listed for this component.

FCS_DTLSC_EXT.2.2

280 The evaluator shall ensure that the TSS describes the client's method of establishing all reference identifiers from the administrator/application-configured reference identifier, including which types of reference identifiers are supported (e.g. Common Name, DNS Name, URI Name, Service Name, or other application-specific Subject Alternative Names) and whether IP addresses and wildcards are supported. The evaluator shall ensure that this description identifies whether and the manner in which certificate pinning is supported or used by the TOE.

Moved (insertion) [111]

FCS_DTLSC_EXT.2.4

281 The evaluator shall verify that TSS describes the Supported Elliptic Curves Extension and whether the required behaviour is performed by default or may be configured.

FCS_DTLSC_EXT.2.5

282 The evaluator shall ensure that the TSS description required per FIA_X509_EXT.2.1 includes the use of client-side certificates for DTLS mutual authentication.

FCS_DTLSC_EXT.2.6

283 The evaluator shall verify that the TSS describes the actions that take place if a message received from the DTLS Server fails the MAC integrity check.

FCS_DTLSC_EXT.2.7

284 The evaluator shall verify that TSS describes how replay is detected and silently discarded for DTLS records that have previously been received and too old to fit in the sliding window.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

4.1.2.2 Guidance Documentation

FCS DTLSC EXT.2.1

285 The evaluator shall also check the guidance documentation to ensure that it contains instructions on configuring the TOE so that DTLS conforms to the description in the TSS.

FCS DTLSC EXT.2.2

286 The evaluator shall verify that the AGD guidance includes instructions for setting the reference identifier to be used for the purposes of certificate validation in DTLS.

FCS DTLSC EXT.2.4

287 If the TSS indicates that the Supported Elliptic Curves Extension must be configured to meet the requirement, the evaluator shall verify that AGD guidance includes configuration of the Supported Elliptic Curves Extension.

FCS DTLSC EXT.2.5

288 The evaluator shall verify that the AGD guidance required per FIA X509 EXT.2.1 includes instructions for configuring the client-side certificates for DTLS mutual authentication.

4.1.2.3 Tests

289 For clarification: For DTLS communication packets might be received in a different order than sent due to the use of the UDP protocol. All tests requiring a specific order of test steps ("before", "after") are therefore referring to the sequence numbering of DTLS packets.

FCS DTLSC EXT.2.1

290 Test 1: The evaluator shall establish a DTLS connection using each of the ciphersuites specified by the requirement. This connection may be established as part of the establishment of a higher-level application protocol, e.g., as part of a syslog session. It is sufficient to observe the successful negotiation of a ciphersuite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic in an attempt to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).

291 Test 2: The evaluator shall attempt to establish the connection using a server with a server certificate that contains the Server Authentication purpose in the extendedKeyUsage field and verify that a connection is established. The evaluator will then verify that the client rejects an otherwise valid server certificate that lacks the Server Authentication purpose in the extendedKeyUsage field and a connection is not established. Ideally, the two certificates should be identical except for the extendedKeyUsage field.

292 Test 3: The evaluator shall send a server certificate in the DTLS connection that does not match the server-selected ciphersuite (for example, send a

Moved (insertion) [194]

Moved (insertion) [116]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

ECDSA certificate while using the TLS_RSA_WITH_AES_128_CBC_SHA ciphersuite.) The evaluator shall verify that the TOE disconnects after receiving the server's Certificate handshake message.

Moved (insertion) [117]

293 Test 4: The evaluator shall configure the server to select the TLS_NULL_WITH_NULL_NULL ciphersuite and verify that the client denies the connection.

Moved (insertion) [154]

294 Test 5: The evaluator performs the following modifications to the traffic:

a) Change the DTLS version selected by the server in the Server Hello to a non-supported DTLS version (for example 1.3 represented by the two bytes 03 04) and verify that the client rejects the connection.

b) If using DHE or ECDHE, modify at least one byte in the server's nonce in the Server Hello handshake message, and verify that the client rejects the Server Key Exchange handshake message (if using a DHE or ECDHE ciphersuite) or that the server denies the client's Finished handshake message.

Moved (insertion) [119]

c) Modify the server's selected ciphersuite in the Server Hello handshake message to be a ciphersuite not presented in the Client Hello handshake message. The evaluator shall verify that the client rejects the connection after receiving the Server Hello.

d) If using DHE or ECDHE, modify the signature block in the Server's Key Exchange handshake message, and verify that the client rejects the connection after receiving the Server Key Exchange message. This test does not apply to cipher suites using RSA key exchange. If a TOE only supports RSA key exchange in conjunction with TLS then this test shall be omitted.

Moved (insertion) [120]

e) Modify a byte in the Server Finished handshake message, and verify that the client sends a fatal alert upon receipt and does not send any application data.

f) Send a garbled message from the Server after the Server has issued the ChangeCipherSpec message and verify that the client denies the connection.

FCS DTLS EXT.2.2

295 Note that where a TLS channel is being used between components of a distributed TOE for FPT ITT.1, the requirements to have the reference identifier established by the user are relaxed and the identifier may also be established through a "Gatekeeper" discovery process. The TSS should describe the discovery process and highlight how the reference identifier is supplied to the "joining" component. The evaluator shall configure the reference identifier according to the AGD guidance and perform the following tests during a DTLS connection:

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- a) Test 1: The evaluator shall present a server certificate that does not contain an identifier in either the Subject Alternative Name (SAN) or Common Name (CN) that matches the reference identifier. The evaluator shall verify that the connection fails.
- b) Test 2: The evaluator shall present a server certificate that contains a CN that matches the reference identifier, contains the SAN extension, but does not contain an identifier in the SAN that matches the reference identifier. The evaluator shall verify that the connection fails. The evaluator shall repeat this test for each supported SAN type.
- c) Test 3: The evaluator shall present a server certificate that contains a CN that matches the reference identifier and does not contains the SAN extension. The evaluator shall verify that the connection succeeds.
- d) Test 4: The evaluator shall present a server certificate that contains a CN that does not match the reference identifier but does contain an identifier in the SAN that matches. The evaluator shall verify that the connection succeeds.
- e) Test 5: The evaluator shall perform the following wildcard tests with each supported type of reference identifier:
- 1) The evaluator shall present a server certificate containing a wildcard that is not in the left-most label of the presented identifier (e.g. `foo.*.example.com`) and verify that the connection fails.
 - 2) The evaluator shall present a server certificate containing a wildcard in the left-most label (e.g. `*.example.com`). The evaluator shall configure the reference identifier with a single left-most label (e.g. `foo.example.com`) and verify that the connection succeeds. The evaluator shall configure the reference identifier without a left-most label as in the certificate (e.g. `example.com`) and verify that the connection fails. The evaluator shall configure the reference identifier with two left-most labels (e.g. `bar.foo.example.com`) and verify that the connection fails.
- f) Test 6: [conditional] If URI or Service name reference identifiers are supported, the evaluator shall configure the DNS name and the service identifier. The evaluator shall present a server certificate containing the correct DNS name and service identifier in the URIName or SRVName fields of the SAN and verify that the connection succeeds. The evaluator shall repeat this test with the wrong service identifier (but correct DNS name) and verify that the connection fails.
- g) Test 7: [conditional] If pinned certificates are supported the evaluator shall present a certificate that does not match the pinned certificate and verify that the connection fails.

Moved (insertion) [100]

Moved (insertion) [101]

Moved (insertion) [123]

Moved (insertion) [124]

Moved (insertion) [104]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS DTLSC EXT.2.3

296 Test 1: The evaluator shall demonstrate that using a certificate without a valid certification path results in the function failing. Using the administrative guidance, the evaluator shall then load a certificate or certificates needed to validate the certificate to be used in the function, and demonstrate that the function succeeds. If the certificate is validated and a trusted channel is established, the test passes. The evaluator then shall delete one of the certificates, and show that the certificate is not validated and the trusted channel is not established.

Moved (insertion) [127]

FCS DTLSC EXT.2.4

297 Test 1: If using DHE or ECDH, the evaluator shall configure the server to perform an ECDHE key exchange in the DTLS connection using a non-supported curve (for example P-192) and shall verify that the TOE disconnects after receiving the server's Key Exchange handshake message.

FCS DTLSC EXT.2.5

298 Test 1: The evaluator shall perform the following modification to the traffic:

- a) Configure the server to require mutual authentication and then modify a byte in a CA field in the Server's Certificate Request handshake message. The modified CA field must not be the CA used to sign the client's certificate. The evaluator shall verify the connection fails.

FCS DTLSC EXT.2.6

299 Test 1: The evaluator shall establish a DTLS connection. The evaluator will then modify at least one byte in a record message, and verify that the Client discards the record or terminates the DTLS session.

FCS DTLSC EXT.2.7

300 Test 1: The evaluator shall set up a DTLS connection with a DTLS Server. The evaluator shall then capture traffic sent from the DTLS Server to the TOE. The evaluator shall retransmit copies of this traffic to the TOE in order to impersonate the DTLS Server. The evaluator shall observe that the TSF does not take action in response to receiving these packets and that the audit log indicates that the replayed traffic was discarded.

4.1.3 FCS DTLSS EXT.1 Extended: DTLS Server Protocol

4.1.3.1 TSS

FCS DTLSS EXT.1.1

301 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that the ciphersuites supported are specified. The evaluator shall check the TSS to ensure that the ciphersuites specified are identical to those listed for this component.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS DTLSS EXT.1.3

302 The evaluator shall verify that the TSS describes how the DTLS Client IP address is validated prior to issuing a ServerHello message.

FCS DTLSS EXT.1.4

303 The evaluator shall verify that the TSS describes the key agreement parameters of the server key exchange message.

FCS DTLSS EXT.1.5

304 The evaluator shall verify that the TSS describes the actions that take place if a message received from the DTLS Client fails the MAC integrity check.

FCS DTLSS EXT.1.6

305 The evaluator shall verify that TSS describes how replay is detected and silently discarded for DTLS records that have previously been received and too old to fit in the sliding window.

4.1.3.2 Guidance Documentation

FCS DTLSS EXT.1.1

306 The evaluator shall also check the guidance documentation to ensure that it contains instructions on configuring the TOE so that DTLS conforms to the description in the TSS (for instance, the set of ciphersuites advertised by the TOE may have to be restricted to meet the requirements).

FCS DTLSS EXT.1.4

307 ~~The evaluator shall verify that any configuration necessary to meet the requirement must be contained in the AGD guidance.~~

Moved (insertion) [152]

4.1.3.3 Tests

308 For clarification: For DTLS communication packets might be received in a different order than sent due to the use of the UDP protocol. All tests requiring a specific order of test steps ("before", "after") are therefore referring to the sequence numbering of DTLS packets.

FCS DTLSS EXT.1.1

309 Test 1: The evaluator shall establish a DTLS connection using each of the ciphersuites specified by the requirement. This connection may be established as part of the establishment of a higher-level application protocol, e.g., as part of a syslog session. It is sufficient to observe the successful negotiation of a ciphersuite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic in an attempt to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).

310 ~~Test 2: The evaluator shall send a Client Hello to the server with a list of ciphersuites that does not contain any of the ciphersuites in the server's ST~~

Moved (insertion) [136]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

and verify that the server denies the connection. Additionally, the evaluator shall send a Client Hello to the server containing only the TLS_NULL_WITH_NULL_NULL ciphersuite and verify that the server denies the connection.

Moved (insertion) [137]

311 Test 3: The evaluator shall use a client to send a key exchange message in the DTLS connection that does not match the server-selected ciphersuite (for example, send an ECDHE key exchange while using the TLS_RSA_WITH_AES_128_CBC_SHA ciphersuite or send a RSA key exchange while using one of the ECDSA ciphersuites.) The evaluator shall verify that the TOE disconnects after the receiving the key exchange message.

Moved (insertion) [156]

312 Test 4: The evaluator shall perform the following modifications to the traffic:

a) withdrawn

b) withdrawn

Moved (insertion) [140]

c) Modify a byte in the Client Finished handshake message, and verify that the server rejects the connection and does not send any application data.

d) After generating a fatal alert by sending a Finished message from the client before the client sends a ChangeCipherSpec message, send a Client Hello with the session identifier from the previous test, and verify that the server denies the connection.

e) Send a garbled message from the client after the client has issued the ChangeCipherSpec message and verify that the Server denies the connection.

FCS_DTLSS_EXT.1.3

313 Modify at least one byte in the cookie from the Server's HelloVerifyRequest message, and verify that the Server rejects the Client's handshake message.

FCS_DTLSS_EXT.1.4

314 If using ECDHE ciphers, the evaluator shall attempt a connection using an ECDHE ciphersuite and a configured curve and, using a packet analyzer, verify that the key agreement parameters in the Key Exchange message are the ones configured. (Determining that the size matches the expected size for the configured curve is sufficient.) The evaluator shall repeat this test for each supported NIST Elliptic Curve and each supported Diffie-Hellman key size.

Moved (insertion) [159]

315 The evaluator shall attempt establishing connection using each claimed key establishment protocol (RSA, DH, ECDHE) with each claimed parameter (RSA key size, Diffie-Hellman parameters, supported curves) as selected in FCS_DTLSS_EXT.1.4. For example, determining that the RSA key size matches the claimed size is sufficient to satisfy this test. The evaluator shall ensure that each supported parameter combination is tested.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

316 Note that this testing can be accomplished in conjunction with the other testing activities.

FCS DTLSS EXT.1.5

317 The evaluator shall establish a connection using a client. The evaluator will then modify at least one byte in a record message, and verify that the Server discards the record or terminates the DTLS session.

FCS DTLSS EXT.1.6

318 The evaluator shall set up a DTLS connection. The evaluator shall then capture traffic sent from the DTLS Client to the TOE. The evaluator shall retransmit copies of this traffic to the TOE in order to impersonate the DTLS Client. The evaluator shall observe that the TSF does not take action in response to receiving these packets and that the audit log indicates that the replayed traffic was discarded.

4.1.4 FCS DTLSS EXT.2 Extended: DTLS Server Protocol with mutual authentication

4.1.4.1 TSS

FCS DTLSS EXT.2.1

319 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that the ciphersuites supported are specified. The evaluator shall check the TSS to ensure that the ciphersuites specified are identical to those listed for this component.

Moved (insertion) [145]

FCS DTLSS EXT.2.3

320 The evaluator shall verify that the TSS describes how the DTLS Client IP address is validated prior to issuing a ServerHello message.

FCS DTLSS EXT.2.4

321 The evaluator shall verify that the TSS describes the key agreement parameters of the server key exchange message.

Moved (insertion) [132]

FCS DTLSS EXT.2.5

322 The evaluator shall verify that the TSS describes the actions that take place if a message received from the DTLS Client fails the MAC integrity check.

FCS DTLSS EXT.2.6

323 The evaluator shall verify that TSS describes how replay is detected and silently discarded for DTLS records that have previously been received and too old to fit in the sliding window.

FCS DTLSS EXT.2.7 and FCS DTLSS EXT.2.8

324 The evaluator shall ensure that the TSS description required per FIA X509 EXT.2.1 includes the use of client-side certificates for DTLS mutual authentication.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS DTLSS EXT.2.9

325 The evaluator shall verify that the TSS describes how the DN or SAN in the certificate is compared to the expected identifier.

4.1.4.2 Guidance Documentation

FCS DTLSS EXT.2.1

326 The evaluator shall also check the guidance documentation to ensure that it contains instructions on configuring the TOE so that DTLS conforms to the description in the TSS (for instance, the set of ciphersuites advertised by the TOE may have to be restricted to meet the requirements).

FCS DTLSS EXT.2.4

327 The evaluator shall verify that any configuration necessary to meet the requirement must be contained in the AGD guidance.

FCS DTLSS EXT.2.7 and FCS DTLSS EXT.2.8

328 The evaluator shall verify that the AGD guidance includes instructions for configuring the client-side certificates for DTLS mutual authentication.

FCS DTLSS EXT.2.9

329 If the DN is not compared automatically to the Domain Name or IP address, username, or email address, then the evaluator shall ensure that the AGD guidance includes configuration of the expected DN or the directory server for the connection.

4.1.4.3 Tests

330 For clarification: For DTLS communication packets might be received in a different order than sent due to the use of the UDP protocol. All tests requiring a specific order of test steps ("before", "after") are therefore referring to the sequence numbering of DTLS packets.

FCS DTLSS EXT.2.1

331 Test 1: The evaluator shall establish a DTLS connection using each of the ciphersuites specified by the requirement. This connection may be established as part of the establishment of a higher-level application protocol, e.g., as part of a syslog session. It is sufficient to observe the successful negotiation of a ciphersuite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic in an attempt to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).

332 Test 2: The evaluator shall send a Client Hello to the server with a list of ciphersuites that does not contain any of the ciphersuites in the server's ST and verify that the server denies the connection. Additionally, the evaluator shall send a Client Hello to the server containing only the TLS_NULL_WITH_NULL_NULL ciphersuite and verify that the server denies the connection.

Moved (insertion) [135]

Moved (insertion) [153]

Moved (insertion) [155]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

333 Test 3: The evaluator shall use a client to send a key exchange message in the DTLS connection that does not match the server-selected ciphersuite (for example, send an ECDHE key exchange while using the TLS_RSA_WITH_AES_128_CBC_SHA ciphersuite or send a RSA key exchange while using one of the ECDSA ciphersuites.) The evaluator shall verify that the TOE disconnects after the receiving the key exchange message.

Moved (insertion) [138]

334 Test 4: The evaluator shall perform the following modifications to the traffic:

a) withdrawn

b) withdrawn

c) Modify a byte in the Client Finished handshake message, and verify that the server rejects the connection and does not send any application data.

Moved (insertion) [158]

d) After generating a fatal alert by sending a Finished message from the client before the client sends a ChangeCipherSpec message, send a Client Hello with the session identifier from the previous test, and verify that the server denies the connection.

e) Send a garbled message from the client after the client has issued the ChangeCipherSpec message and verify that the Server denies the connection.

FCS DTLSS EXT.2.3

335 Modify at least one byte in the cookie from the Server's HelloVerifyRequest message, and verify that the Server rejects the Client's handshake message.

FCS DTLSS EXT.2.4

336 The evaluator shall attempt a connection using an ECDHE ciphersuite and a configured curve and, using a packet analyzer, verify that the key agreement parameters in the Key Exchange message are the ones configured. (Determining that the size matches the expected size for the configured curve is sufficient.) The evaluator shall repeat this test for each supported NIST Elliptic Curve and each supported Diffie-Hellman key size.

Moved (insertion) [143]

337 The evaluator shall attempt establishing connection using each claimed key establishment protocol (RSA, DH, ECDHE) with each claimed parameter (RSA key size, Diffie-Hellman parameters, supported curves) as selected in FCS DTLSS EXT.2.4. For example, determining that the RSA key size matches the claimed size is sufficient to satisfy this test. The evaluator shall ensure that each supported parameter combination is tested.

338 Note that this testing can be accomplished in conjunction with the other testing activities

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS DTLSS EXT.2.5

339 The evaluator shall establish a connection using a client. The evaluator will then modify at least one byte in a record message, and verify that the Server discards the record or terminates the DTLS session.

FCS DTLSS EXT.2.6

340 The evaluator shall set up a DTLS connection. The evaluator shall then capture traffic sent from the DTLS Client to the TOE. The evaluator shall retransmit copies of this traffic to the TOE in order to impersonate the DTLS Client. The evaluator shall observe that the TSF does not take action in response to receiving these packets and that the audit log indicates that the replayed traffic was discarded.

FCS DTLSS EXT.2.7 and FCS DTLSS EXT.2.8

341 Test 1: The evaluator shall configure the server to send a certificate request to the client and shall attempt a connection without sending a certificate from the client. The evaluator shall verify that the connection is denied.

Moved (insertion) [160]

342 Test 2: The evaluator shall configure the server to send a certificate request to the client without the supported signature algorithm used by the client's certificate. The evaluator shall attempt a connection using the client certificate and verify that the connection is denied.

343 Test 3: The evaluator shall demonstrate that using a certificate without a valid certification path results in the function failing. Using the administrative guidance, the evaluator shall then load a certificate or certificates needed to validate the certificate to be used in the function, and demonstrate that the function succeeds. The evaluator then shall delete one of the certificates, and show that the function fails.

344 Test 4: The evaluator shall configure the client to send a certificate that does not chain to one of the Certificate Authorities (either a Root or Intermediate CA) in the server's Certificate Request message. The evaluator shall verify that the attempted connection is denied.

Moved (insertion) [161]

345 Test 5: The evaluator shall configure the client to send a certificate with the Client Authentication purpose in the extendedKeyUsage field and verify that the server accepts the attempted connection. The evaluator shall repeat this test without the Client Authentication purpose and shall verify that the server denies the connection. Ideally, the two certificates should be identical except for the Client Authentication purpose.

346 Test 6: The evaluator shall perform the following modifications to the traffic:

- a) Configure the server to require mutual authentication and then modify a byte in the client's certificate. The evaluator shall verify that the server rejects the connection.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

b) Configure the server to require mutual authentication and then modify a byte in the client's Certificate Verify handshake message. The evaluator shall verify that the server rejects the connection.

Moved (insertion) [162]

FCS_DTLSS_EXT.2.9

347 The evaluator shall send a client certificate with an identifier that does not match an expected identifier and verify that the server denies the connection.

Moved (insertion) [163]

4.1.5 FCS_HTTPS_EXT.1 HTTPS Protocol

Moved (insertion) [18]

4.1.5.1 TSS

348 The evaluator shall examine the TSS and determine that enough detail is provided to explain how the implementation complies with RFC 2818.

4.1.5.2 Tests

349 The evaluator shall perform the following tests:

a) Test 1: The evaluator shall attempt to establish each trusted path or channel that utilizes HTTPS, observe the traffic with a packet analyser, verify that the connection succeeds, and verify that the traffic is identified as TLS or HTTPS.

Moved (insertion) [19]

350 Other tests are performed in conjunction with the TLS evaluation activities.

351 If the TOE is an HTTPS client or an HTTPS server utilizing X.509 client authentication, then the certificate validity shall be tested in accordance with testing performed for FIA_X509_EXT.1, and the evaluator shall perform the following test:

a) Test 1: The evaluator shall demonstrate that using a certificate without a valid certification path results in an application notification. Using the administrative guidance, the evaluator shall then load a valid certificate and certification path, and demonstrate that the function succeeds. The evaluator then shall delete one of the certificates, and show that the selection listed in the ST occurs.

Moved (insertion) [20]

4.1.6 FCS_IPSEC_EXT.1 IPsec Protocol

Moved (insertion) [21]

4.1.6.1 TSS

FCS_IPSEC_EXT.1.1

352 The evaluator shall examine the TSS and determine that it describes what takes place when a packet is processed by the TOE, e.g., the algorithm used to process the packet. The TSS describes how the SPD is implemented and the rules for processing both inbound and outbound packets in terms of the IPsec policy. The TSS describes the rules that are available and the resulting actions available after matching a rule. The TSS describes how those rules and actions

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

form the SPD in terms of the BYPASS (e.g., no encryption), DISCARD (e.g., drop the packet), and PROTECT (e.g., encrypt the packet) actions defined in RFC 4301.

Moved (insertion) [22]

353 As noted in section 4.4.1 of RFC 4301, the processing of entries in the SPD is non-trivial and the evaluator shall determine that the description in the TSS is sufficient to determine which rules will be applied given the rule structure implemented by the TOE. For example, if the TOE allows specification of ranges, conditional rules, etc., the evaluator shall determine that the description of rule processing (for both inbound and outbound packets) is sufficient to determine the action that will be applied, especially in the case where two different rules may apply. This description shall cover both the initial packets (that is, no SA is established on the interface or for that particular packet) as well as packets that are part of an established SA.

FCS_IPSEC_EXT.1.3

354 The evaluator checks the TSS to ensure it states that the VPN can be established to operate in transport mode and/or tunnel mode (as identified in FCS_IPSEC_EXT.1.3).

FCS_IPSEC_EXT.1.4

355 The evaluator shall examine the TSS to verify that the selected algorithms are implemented. In addition, the evaluator ensures that the SHA-based HMAC algorithm conforms to the algorithms specified in FCS_COP.1/KeyedHash Cryptographic Operations (for keyed-hash message authentication).

Moved (insertion) [23]

FCS_IPSEC_EXT.1.5

356 The evaluator shall examine the TSS to verify that IKEv1 and/or IKEv2 are implemented.

357 For IKEv1 implementations, the evaluator shall examine the TSS to ensure that, in the description of the IPsec protocol, it states that aggressive mode is not used for IKEv1 Phase 1 exchanges, and that only main mode is used. It may be that this is a configurable option.

FCS_IPSEC_EXT.1.6

358 The evaluator shall ensure the TSS identifies the algorithms used for encrypting the IKEv1 and/or IKEv2 payload, and that the algorithms chosen in the selection of the requirement are included in the TSS discussion.

Moved (insertion) [24]

FCS_IPSEC_EXT.1.7

359 The evaluator shall ensure the TSS identifies the lifetime configuration method used for limiting the IKEv1 Phase 1 SA lifetime and/or the IKEv2 SA lifetime. The evaluator shall verify that the selection made here corresponds to the selection in FCS_IPSEC_EXT.1.5.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS_IPSEC_EXT.1.8

360 The evaluator shall ensure the TSS identifies the lifetime configuration method used for limiting the IKEv1 Phase 2 SA lifetime and/or the IKEv2 Child SA lifetime. The evaluator shall verify that the selection made here corresponds to the selection in FCS_IPSEC_EXT.1.5.

Moved (insertion) [25]

FCS_IPSEC_EXT.1.9

361 The evaluator shall check to ensure that, for each DH group supported, the TSS describes the process for generating "x". The evaluator shall verify that the TSS indicates that the random number generated that meets the requirements in this PP is used, and that the length of "x" meets the stipulations in the requirement.

FCS_IPSEC_EXT.1.10

362 If the first selection is chosen, the evaluator shall check to ensure that, for each DH group supported, the TSS describes the process for generating each nonce. The evaluator shall verify that the TSS indicates that the random number generated that meets the requirements in this PP is used, and that the length of the nonces meet the stipulations in the requirement.

363 If the second selection is chosen, the evaluator shall check to ensure that, for each PRF hash supported, the TSS describes the process for generating each nonce. The evaluator shall verify that the TSS indicates that the random number generated that meets the requirements in this PP is used, and that the length of the nonces meet the stipulations in the requirement.

Moved (insertion) [29]

FCS_IPSEC_EXT.1.11

364 The evaluator shall check to ensure that the DH groups specified in the requirement are listed as being supported in the TSS. If there is more than one DH group supported, the evaluator checks to ensure the TSS describes how a particular DH group is specified/negotiated with a peer.

Moved (insertion) [26]

FCS_IPSEC_EXT.1.12

365 The evaluator shall check that the TSS describes the potential strengths (in terms of the number of bits in the symmetric key) of the algorithms that are allowed for the IKE and ESP exchanges. The TSS shall also describe the checks that are done when negotiating IKEv1 Phase 2 and/or IKEv2 CHILD SA suites to ensure that the strength (in terms of the number of bits of key in the symmetric algorithm) of the negotiated algorithm is less than or equal to that of the IKE SA this is protecting the negotiation.

FCS_IPSEC_EXT.1.13

366 The evaluator ensures that the TSS identifies RSA and/or ECDSA as being used to perform peer authentication. The description must be consistent with the algorithms as specified in FCS_COP.1/SigGen Cryptographic Operations (for cryptographic signature).

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

367 If pre-shared keys are chosen in the selection, the evaluator shall check to ensure that the TSS describes how pre-shared keys are established and used in authentication of IPsec connections. The description in the TSS shall also indicate how pre-shared key establishment is accomplished for TOEs that can generate a pre-shared key as well as TOEs that simply use a pre-shared key.

Moved (insertion) [27]

FCS_IPSEC_EXT.L14

368 The evaluator shall ensure that the TSS describes how the TOE compares the peer's presented identifier to the reference identifier. This description shall include which field(s) of the certificate are used as the presented identifier (DN, Common Name, or SAN). If the ST author assigned an additional identifier type, the TSS description shall also include a description of that type and the method by which that type is compared to the peer's presented certificate.

4.1.6.2 Guidance Documentation

Moved (insertion) [28]

FCS_IPSEC_EXT.L1

369 The evaluator shall examine the guidance documentation to verify it instructs the Administrator how to construct entries into the SPD that specify a rule for processing a packet. The description includes all three cases – a rule that ensures packets are encrypted/decrypted, dropped, and flow through the TOE without being encrypted. The evaluator shall determine that the description in the guidance documentation is consistent with the description in the TSS, and that the level of detail in the guidance documentation is sufficient to allow the administrator to set up the SPD in an unambiguous fashion. This includes a discussion of how ordering of rules impacts the processing of an IP packet.

FCS_IPSEC_EXT.L3

370 The evaluator shall confirm that the guidance documentation contains instructions on how to configure the connection in each mode selected.

FCS_IPSEC_EXT.L4

371 The evaluator checks the guidance documentation to ensure it provides instructions on how to configure the TOE to use the algorithms selected.

Moved (insertion) [31]

FCS_IPSEC_EXT.L5

372 The evaluator shall check the guidance documentation to ensure it instructs the administrator how to configure the TOE to use IKEv1 and/or IKEv2 (as selected), and how to configure the TOE to perform NAT traversal (if selected).

Moved (insertion) [30]

373 If the IKEv1 Phase 1 mode requires configuration of the TOE prior to its operation, the evaluator shall check the guidance documentation to ensure that instructions for this configuration are contained within that guidance.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS IPSEC EXT.1.6

374 The evaluator ensures that the guidance documentation describes the configuration of all selected algorithms in the requirement.

Moved (insertion) [32]

FCS IPSEC EXT.1.7

375 The evaluator shall verify that the values for SA lifetimes can be configured and that the instructions for doing so are located in the guidance documentation. If time-based limits are supported, the evaluator ensures that the Administrator is able to configure Phase 1 SA values for 24 hours. Currently there are no values mandated for the number of bytes, the evaluator just ensures that this can be configured if selected in the requirement.

Moved (insertion) [33]

FCS IPSEC EXT.1.8

376 The evaluator shall verify that the values for SA lifetimes can be configured and that the instructions for doing so are located in the guidance documentation. If time-based limits are supported, the evaluator ensures that the Administrator is able to configure Phase 2 SA values for 8 hours. Currently there are no values mandated for the number of bytes, the evaluator just ensures that this can be configured if selected in the requirement.

FCS IPSEC EXT.1.11

377 The evaluator ensures that the guidance documentation describes the configuration of all algorithms selected in the requirement.

Moved (insertion) [35]

FCS IPSEC EXT.1.13

378 The evaluator ensures the guidance documentation describes how to set up the TOE to use certificates with RSA and/or ECDSA signatures and public keys.

379 The evaluator shall check that the guidance documentation describes how pre-shared keys are to be generated and established. The description in the guidance documentation shall also indicate how pre-shared key establishment is accomplished for TOEs that can generate a pre-shared key as well as TOEs that simply use a pre-shared key.

Moved (insertion) [34]

380 The evaluator will ensure that the guidance documentation describes how to configure the TOE to connect to a trusted CA, and ensure a valid certificate for that CA is loaded into the TOE and marked "trusted".

Moved (insertion) [36]

FCS IPSEC EXT.1.14

381 The evaluator shall ensure that the operational guidance includes the configuration of the reference identifier(s) for the peer.

FCS IPSEC EXT.1.1

382 The evaluator uses the guidance documentation to configure the TOE to carry out the following tests:

- a) Test 1: The evaluator shall configure the SPD such that there is a rule for dropping a packet, encrypting a packet, and allowing a packet to

Moved (insertion) [38]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

flow in plaintext. The selectors used in the construction of the rule shall be different such that the evaluator can generate a packet and send packets to the gateway with the appropriate fields (fields that are used by the rule - e.g., the IP addresses, TCP/UDP ports) in the packet header. The evaluator performs both positive and negative test cases for each type of rule (e.g. a packet that matches the rule and another that does not match the rule). The evaluator observes via the audit trail, and packet captures that the TOE exhibited the expected behaviour; appropriate packets were dropped, allowed to flow without modification, encrypted by the IPsec implementation.

- b) Test 2: The evaluator shall devise several tests that cover a variety of scenarios for packet processing. As with Test 1, the evaluator ensures both positive and negative test cases are constructed. These scenarios must exercise the range of possibilities for SPD entries and processing modes as outlined in the TSS and guidance documentation. Potential areas to cover include rules with overlapping ranges and conflicting entries, inbound and outbound packets, and packets that establish SAs as well as packets that belong to established SAs. The evaluator shall verify, via the audit trail and packet captures, for each scenario that the expected behavior is exhibited, and is consistent with both the TSS and the guidance documentation.

FCS_IPSEC_EXT.1.2

383 The assurance activity for this element is performed in conjunction with the activities for FCS_IPSEC_EXT.1.1.

384 The evaluator uses the guidance documentation to configure the TOE to carry out the following tests:

385 The evaluator shall configure the SPD such that there is a rule for dropping a packet, encrypting a packet, and allowing a packet to flow in plaintext. The evaluator may use the SPD that was created for verification of FCS_IPSEC_EXT.1.1. The evaluator shall construct a network packet that matches the rule to allow the packet to flow in plaintext and send that packet. The evaluator should observe that the network packet is passed to the proper destination interface with no modification. The evaluator shall then modify a field in the packet header; such that it no longer matches the evaluator-created entries (there may be a "TOE created" final entry that discards packets that do not match any previous entries). The evaluator sends the packet, and observes that the packet was dropped.

FCS_IPSEC_EXT.1.3

386 The evaluator shall perform the following test(s) based on the selections chosen:

- a) Test 1: If tunnel mode is selected, the evaluator uses the guidance documentation to configure the TOE to operate in tunnel mode and also configures a VPN peer to operate in tunnel mode. The evaluator configures the TOE and the VPN peer to use any of the allowable

Moved (insertion) [39]

Moved (insertion) [40]

Moved (insertion) [41]

Moved (insertion) [42]

Moved (insertion) [43]

Moved (insertion) [44]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

cryptographic algorithms, authentication methods, etc. to ensure an allowable SA can be negotiated. The evaluator shall then initiate a connection from the TOE to connect to the VPN peer. The evaluator observes (for example, in the audit trail and the captured packets) that a successful connection was established using the tunnel mode.

Moved (insertion) [45]

- b) Test 2: If transport mode is selected, the evaluator uses the guidance documentation to configure the TOE to operate in transport mode and also configures a VPN peer to operate in transport mode. The evaluator configures the TOE and the VPN peer to use any of the allowed cryptographic algorithms, authentication methods, etc. to ensure an allowable SA can be negotiated. The evaluator then initiates a connection from the TOE to connect to the VPN peer. The evaluator observes (for example, in the audit trail and the captured packets) that a successful connection was established using the transport mode.

Moved (insertion) [46]

FCS_IPSEC_EXT.1.4

387 The evaluator shall configure the TOE as indicated in the guidance documentation configuring the TOE to use each of the supported algorithms, attempt to establish a connection using ESP, and verify that the attempt succeeds.

FCS_IPSEC_EXT.1.5

388 Tests are performed in conjunction with the other IPsec evaluation activities.

- a) Test 1: If IKEv1 is selected, the evaluator shall configure the TOE as indicated in the guidance documentation, and attempt to establish a connection using an IKEv1 Phase 1 connection in aggressive mode. This attempt should fail. The evaluator should then show that main mode exchanges are supported.
- b) Test 2: If NAT traversal is selected within the IKEv2 selection, the evaluator shall configure the TOE so that it will perform NAT traversal processing as described in the TSS and RFC 5996, section 2.23. The evaluator shall initiate an IPsec connection and determine that the NAT is successfully traversed.

Moved (insertion) [47]

Moved (insertion) [48]

FCS_IPSEC_EXT.1.6

389 The evaluator shall configure the TOE to use the ciphersuite under test to encrypt the IKEv1 and/or IKEv2 payload and establish a connection with a peer device, which is configured to only accept the payload encrypted using the indicated ciphersuite. The evaluator will confirm the algorithm was that used in the negotiation.

FCS_IPSEC_EXT.1.7

390 When testing this functionality, the evaluator needs to ensure that both sides are configured appropriately. From the RFC "A difference between IKEv1 and IKEv2 is that in IKEv1 SA lifetimes were negotiated. In IKEv2, each end of the SA is responsible for enforcing its own lifetime policy on the SA and

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

rekeying the SA when necessary. If the two ends have different lifetime policies, the end with the shorter lifetime will end up always being the one to request the rekeying. If the two ends have the same lifetime policies, it is possible that both will initiate a rekeying at the same time (which will result in redundant SAs). To reduce the probability of this happening, the timing of rekeying requests SHOULD be jittered.

Moved (insertion) [49]

Moved (insertion) [50]

391 Each of the following tests shall be performed for each version of IKE selected in the FCS_IPSEC_EXT.1.5 protocol selection:

a) Test 1: If 'number of bytes' is selected as the SA lifetime measure, the evaluator shall configure a maximum lifetime in terms of the number of bytes allowed following the guidance documentation. The evaluator shall configure a test peer with a byte lifetime that exceeds the lifetime of the TOE. The evaluator shall establish an SA between the TOE and the test peer, and determine that once the allowed number of bytes through this SA is exceeded, a new SA is negotiated. The evaluator shall verify that the TOE initiates a Phase 1 negotiation.

Moved (insertion) [51]

b) Test 2: If 'length of time' is selected as the SA lifetime measure, the evaluator shall configure a maximum lifetime of 24 hours for the Phase 1 SA following the guidance documentation. The evaluator shall configure a test peer with a lifetime that exceeds the lifetime of the TOE. The evaluator shall establish an SA between the TOE and the test peer, maintain the Phase 1 SA for 24 hours, and determine that a new Phase 1 SA is negotiated on or before 24 hours has elapsed. The evaluator shall verify that the TOE initiates a Phase 1 negotiation.

Moved (insertion) [52]

Moved (insertion) [53]

FCS_IPSEC_EXT.1.8

392 When testing this functionality, the evaluator needs to ensure that both sides are configured appropriately. From the RFC "A difference between IKEv1 and IKEv2 is that in IKEv1 SA lifetimes were negotiated. In IKEv2, each end of the SA is responsible for enforcing its own lifetime policy on the SA and rekeying the SA when necessary. If the two ends have different lifetime policies, the end with the shorter lifetime will end up always being the one to request the rekeying. If the two ends have the same lifetime policies, it is possible that both will initiate a rekeying at the same time (which will result in redundant SAs). To reduce the probability of this happening, the timing of rekeying requests SHOULD be jittered."

393 Each of the following tests shall be performed for each version of IKE selected in the FCS_IPSEC_EXT.1.5 protocol selection:

a) Test 1: If 'number of bytes' is selected as the SA lifetime measure, the evaluator shall configure a maximum lifetime in terms of the number of bytes allowed following the guidance documentation. The evaluator shall configure a test peer with a byte lifetime that exceeds the lifetime of the TOE. The evaluator shall establish an SA between the TOE and the test peer, and determine that once the allowed number of bytes

Moved (insertion) [54]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

through this SA is exceeded, a new SA is negotiated. The evaluator shall verify that the TOE initiates a Phase 2 negotiation.

Moved (insertion) [55]

- b) Test 2: If 'length of time' is selected as the SA lifetime measure, the evaluator shall configure a maximum lifetime of 8 hours for the Phase 2 SA following the guidance documentation. The evaluator shall configure a test peer with a lifetime that exceeds the lifetime of the TOE. The evaluator shall establish an SA between the TOE and the test peer, maintain the Phase 1 SA for 8 hours, and determine that once a new Phase 2 SA is negotiated when or before 8 hours has lapsed. The evaluator shall verify that the TOE initiates a Phase 2 negotiation.

Moved (insertion) [56]

Moved (insertion) [57]

FCS_IPSEC_EXT.1.10

394 Each of the following tests shall be performed for each version of IKE selected in the FCS_IPSEC_EXT.1.5 protocol selection:

- a) Test 1: If the first selection is chosen, the evaluator shall check to ensure that, for each DH group supported, the TSS describes the process for generating each nonce. The evaluator shall verify that the TSS indicates that the random number generated that meets the requirements in this PP is used, and that the length of the nonces meet the stipulations in the requirement.
- b) Test 2: If the second selection is chosen, the evaluator shall check to ensure that, for each PRF hash supported, the TSS describes the process for generating each nonce. The evaluator shall verify that the TSS indicates that the random number generated that meets the requirements in this PP is used, and that the length of the nonces meet the stipulations in the requirement.

Moved (insertion) [58]

Moved (insertion) [59]

FCS_IPSEC_EXT.1.11

395 For each supported DH group, the evaluator shall test to ensure that all supported IKE protocols can be successfully completed using that particular DH group.

FCS_IPSEC_EXT.1.12

396 The evaluator simply follows the guidance to configure the TOE to perform the following tests.

- a) Test 1: This test shall be performed for each version of IKE supported. The evaluator shall successfully negotiate an IPsec connection using each of the supported algorithms and hash functions identified in the requirements.
- b) Test 2: This test shall be performed for each version of IKE supported. The evaluator shall attempt to establish an SA for ESP that selects an encryption algorithm with more strength than that being used for the

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

IKE SA (i.e., symmetric algorithm with a key size larger than that being used for the IKE SA). Such attempts should fail.

Moved (insertion) [60]

- c) Test 3: This test shall be performed for each version of IKE supported. The evaluator shall attempt to establish an IKE SA using an algorithm that is not one of the supported algorithms and hash functions identified in the requirements. Such an attempt should fail.
- d) Test 4: This test shall be performed for each version of IKE supported. The evaluator shall attempt to establish an SA for ESP (assumes the proper parameters were used to establish the IKE SA) that selects an encryption algorithm that is not identified in FCS_IPSEC_EXT.1.4. Such an attempt should fail.

Moved (insertion) [61]

FCS_IPSEC_EXT.1.13

397 For efficiency sake, the testing that is performed may be combined with the testing for FIA_X509_EXT.1, FIA_X509_EXT.2 (for IPsec connections), and FCS_IPSEC_EXT.1.1. The following tests shall be repeated for each peer authentication method selected in FCS_IPSEC_EXT.1.13.

Moved (insertion) [62]

- a) Test 1: The evaluator shall configure the TOE to use a private key and associated certificate signed by a trusted CA and shall establish an IPsec connection with the peer.
- b) Test 2: If pre-shared keys are selected, the evaluator shall generate a pre-shared key off-TOE and use it, as indicated in the guidance documentation, to establish an IPsec connection with the peer.

FCS_IPSEC_EXT.1.14

398 For each supported identifier type (excluding DNs), the evaluator shall repeat the following tests:

- a) Test 1: For each field of the certificate supported for comparison, the evaluator shall configure the peer's reference identifier on the TOE (per the administrative guidance) to match the field in the peer's presented certificate and shall verify that the IKE authentication succeeds.
- b) Test 2: For each field of the certificate support for comparison, the evaluator shall configure the peer's reference identifier on the TOE (per the administrative guidance) to not match the field in the peer's presented certificate and shall verify that the IKE authentication fails.
- c) Test 3: (conditional) If the TOE supports DN identifier types, the evaluator shall configure the peer's reference identifier on the TOE (per the administrative guidance) to match the subject DN in the peer's presented certificate and shall verify that the IKE authentication succeeds. To demonstrate a bit-wise comparison of the DN, the

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

evaluator shall change a single bit in the DN (preferably, in an Object Identifier (OID) in the DN) and verify that the IKE authentication fails.

Moved (insertion) [63]

4.1.7 FCS_SSHC_EXT.1 SSH Client

4.1.7.1 TSS

FCS_SSHC_EXT.1.2

399 The evaluator shall check to ensure that the TSS contains a description of the public key algorithms that are acceptable for use for authentication and that this list conforms to FCS_SSHC_EXT.1.5. and ensure that if password-based authentication methods have been selected in the ST then these are also described.

Moved (insertion) [64]

FCS_SSHC_EXT.1.3

400 The evaluator shall check that the TSS describes how “large packets” in terms of RFC 4253 are detected and handled.

FCS_SSHC_EXT.1.4

401 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that optional characteristics are specified, and the encryption algorithms supported are specified as well. The evaluator shall check the TSS to ensure that the encryption algorithms specified are identical to those listed for this component.

Moved (insertion) [65]

FCS_SSHC_EXT.1.5

402 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that optional characteristics are specified, and the public key algorithms supported are specified as well. The evaluator shall check the TSS to ensure that the public key algorithms specified are identical to those listed for this component.

FCS_SSHC_EXT.1.6

403 The evaluator shall check the TSS to ensure that it lists the supported data integrity algorithms, and that that list corresponds to the list in this component.

FCS_SSHC_EXT.1.7

404 The evaluator shall check the TSS to ensure that it lists the supported key exchange algorithms, and that that list corresponds to the list in this component.

FCS_SSHC_EXT.1.8

405 The evaluator shall check that the TSS specifies the following:

1. Both thresholds are checked by the TOE.
2. Rekeying is performed upon reaching the threshold that is hit first.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

4.1.7.2 Guidance Documentation

Moved (insertion) [66]

FCS_SSHC_EXT.1.4

406 The evaluator shall also check the guidance documentation to ensure that it contains instructions on configuring the TOE so that SSH conforms to the description in the TSS (for instance, the set of algorithms advertised by the TOE may have to be restricted to meet the requirements).

FCS_SSHC_EXT.1.5

407 The evaluator shall also check the guidance documentation to ensure that it contains instructions on configuring the TOE so that SSH conforms to the description in the TSS (for instance, the set of algorithms advertised by the TOE may have to be restricted to meet the requirements).

FCS_SSHC_EXT.1.6

408 The evaluator shall also check the guidance documentation to ensure that it contains instructions to the administrator on how to ensure that only the allowed data integrity algorithms are used in SSH connections with the TOE (specifically, that the “none” MAC algorithm is not allowed).

FCS_SSHC_EXT.1.7

409 The evaluator shall also check the guidance documentation to ensure that it contains instructions to the administrator on how to ensure that only the allowed key exchange algorithms are used in SSH connections with the TOE.

FCS_SSHC_EXT.1.8

410 If one or more thresholds that are checked by the TOE to fulfil the SFR are configurable, then the evaluator shall check that the guidance documentation describes how to configure those thresholds. Either the allowed values are specified in the guidance documentation and must not exceed the limits specified in the SFR (one hour of session time, one gigabyte of transmitted traffic) or the TOE must not accept values beyond the limits specified in the SFR. The evaluator shall check that the guidance documentation describes that the TOE reacts to the first threshold reached.

4.1.7.3 Tests

Moved (insertion) [72]

FCS_SSHC_EXT.1.2

411 Test 1: If password-based authentication methods have been selected in the ST then using the guidance documentation, the evaluator shall configure the TOE to perform password-based authentication to an SSH server, and demonstrate that a user can be successfully authenticated by the TOE to an SSH server using a password as an authenticator.

Note: Public key authentication is tested as part of testing for FCS_SSHC_EXT.1.5

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS SSHC EXT.1.3

412 The evaluator shall demonstrate that if the TOE receives a packet larger than that specified in this component, that packet is dropped.

Moved (insertion) [67]

FCS SSHC EXT.1.4

413 The evaluator must ensure that only claimed ciphers and cryptographic primitives are used to establish a SSH connection. To verify this, the evaluator shall start session establishment for a SSH connection with a remote server (referred to as 'remote endpoint' below). The evaluator shall capture the traffic exchanged between the TOE and the remote endpoint during protocol negotiation (e.g. using a packet capture tool or information provided by the endpoint, respectively). The evaluator shall verify from the captured traffic that the TOE offers all the ciphers defined in the TSS for the TOE for SSH sessions, but no additional ones compared to the definition in the TSS. The evaluator shall perform one successful negotiation of an SSH session to verify that the TOE behaves as expected. It is sufficient to observe the successful negotiation of the session to satisfy the intent of the test. If the evaluator detects that not all ciphers defined in the TSS for SSH are supported by the TOE and/or the TOE supports one or more additional ciphers not defined in the TSS for SSH, the test shall be regarded as failed.

FCS SSHC EXT.1.5

414 Test 1: The evaluator shall establish a SSH connection using each of the public key algorithms specified by the requirement to authenticate an SSH server to the TOE. It is sufficient to observe (on the wire) the successful negotiation of the algorithm to satisfy the intent of the test.

415 Test 2: The evaluator shall configure an SSH server to only allow a public key algorithm that is not included in the ST selection. The evaluator shall attempt to establish an SSH connection from the TOE to the SSH server and observe that the connection is rejected.

Moved (insertion) [68]

FCS SSHC EXT.1.6

416 Test 1: The evaluator shall establish a SSH connection using each of the integrity algorithms specified by the requirement. It is sufficient to observe (on the wire) the successful negotiation of the algorithm to satisfy the intent of the test.

417 Test 2: The evaluator shall configure an SSH server to only allow a MAC algorithm that is not included in the ST selection. The evaluator shall attempt to connect from the TOE to the SSH server and observe that the attempt fails.

Moved (insertion) [85]

Moved (insertion) [70]

FCS SSHC EXT.1.7

418 Test 1: The evaluator shall configure an SSH server to permit all allowed key exchange methods. The evaluator shall attempt to connect from the TOE to the SSH server using each allowed key exchange method, and observe that each attempt succeeds.

Moved (insertion) [71]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS SSHC EXT.1.8

- 419 The evaluator needs to perform testing that rekeying is performed according to the description in the TSS. The evaluator shall test both, the time-based threshold and the traffic-based threshold.
- 420 For testing of the time-based threshold the evaluator shall use the TOE to connect to an SSH server and keep the session open until the threshold is reached. The evaluator shall verify that the SSH session has been active longer than the threshold value and a corresponding audit event has been generated by the TOE.
- 421 Testing does not necessarily have to be performed with the threshold configured at the maximum allowed value of one hour of session time but the value used for testing shall not exceed one hour. The evaluator needs to ensure that the rekeying has been initiated by the TOE and not by the SSH server the TOE is connected to.
- 422 For testing of the traffic-based threshold the evaluator shall use the TOE to connect to an SSH server, and shall transmit data from and to the TOE within the active SSH session until the threshold for transmitted traffic is reached. The transmitted traffic is the total traffic comprising incoming and outgoing traffic.
- 423 The evaluator shall verify that more data has been transmitted within the SSH session than the threshold allows and a corresponding audit event has been generated by the TOE.
- 424 Testing does not necessarily have to be performed with the threshold configured at the maximum allowed value of one gigabyte of transferred traffic but the value used for testing shall not exceed one gigabyte. The evaluator needs to ensure that the rekeying has been initiated by the TOE and not by the SSH server the TOE is connected to.
- 425 If one or more thresholds that are checked by the TOE to fulfil the SFR are configurable, the evaluator needs to verify that the threshold(s) can be configured as described in the guidance documentation and the evaluator needs to test that modification of the thresholds is restricted to Security Administrators (as required by FMT_MOF.1/Functions).

Moved (insertion) [73]

FCS SSHC EXT.1.9

- 426 Test 1: The evaluator shall delete all entries in the TOE's list of recognized SSH server host keys and, if selected, all entries in the TOE's list of trusted certification authorities. The evaluator shall initiate a connection from the TOE to an SSH server. The evaluator shall ensure that the TOE either rejects the connection or displays the SSH server's public key (either the key bytes themselves or a hash of the key using any allowed hash algorithm) and prompts the user to accept or deny the key before continuing the connection.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

427 Test 2: The evaluator shall add an entry associating a host name with a public key into the TOE's local database. The evaluator shall replace, on the corresponding SSH server, the server's host key with a different host key. The evaluator shall initiate a connection from the TOE to the SSH server using password-based authentication, shall ensure that the TOE rejects the connection, and shall ensure that the password was not transmitted to the SSH server (for example, by instrumenting the SSH server with a debugging capability to output received passwords).

Moved (insertion) [74]

4.1.8 FCS SSHS_EXT.1 SSH Server

4.1.8.1 TSS

FCS SSHS_EXT.1.2

428 The evaluator shall check to ensure that the TSS contains a description of the public key algorithms that are acceptable for use for authentication, that this list conforms to FCS SSHS_EXT.1.5, and ensure that password-based authentication methods are also allowed.

FCS SSHS_EXT.1.3

429 The evaluator shall check that the TSS describes how "large packets" in terms of RFC 4253 are detected and handled.

FCS SSHS_EXT.1.4

430 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that optional characteristics are specified, and ~~the encryption algorithms supported are specified as well~~. The evaluator shall check the TSS to ensure that the encryption algorithms specified are identical to those listed for this component.

Moved (insertion) [75]

FCS SSHS_EXT.1.5

431 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that optional characteristics are specified, and the public key algorithms supported are specified as well. The evaluator shall check the TSS to ensure that the public key algorithms specified are identical to those listed for this component.

FCS SSHS_EXT.1.6

432 The evaluator shall check the TSS to ensure that it lists the supported data integrity algorithms, and that that list corresponds to the list in this component.

FCS SSHS_EXT.1.7

433 The evaluator shall check the TSS to ensure that it lists the supported key exchange algorithms, and that that list corresponds to the list in this component.

FCS SSHS_EXT.1.8

434 The evaluator shall check that the TSS specifies the following:

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

1. Both thresholds are checked by the TOE.
2. Rekeying is performed upon reaching the threshold that is hit first.

4.1.8.2 Guidance Documentation

FCS_SSHS_EXT.1.4

435 The evaluator shall also check the guidance documentation to ensure that it contains instructions on configuring the TOE so that SSH conforms to the description in the TSS (for instance, the set of algorithms advertised by the TOE may have to be restricted to meet the requirements).

FCS_SSHS_EXT.1.5

436 The evaluator shall also check the guidance documentation to ensure that it contains instructions on configuring the TOE so that SSH conforms to the description in the TSS (for instance, the set of algorithms advertised by the TOE may have to be restricted to meet the requirements).

FCS_SSHS_EXT.1.6

437 The evaluator shall also check the guidance documentation to ensure that it contains instructions to the administrator on how to ensure that only the allowed data integrity algorithms are used in SSH connections with the TOE (specifically, that the “none” MAC algorithm is not allowed).

FCS_SSHS_EXT.1.7

438 The evaluator shall also check the guidance documentation to ensure that it contains instructions to the administrator on how to ensure that only the allowed key exchange algorithms are used in SSH connections with the TOE.

FCS_SSHS_EXT.1.8

439 If one or more thresholds that are checked by the TOE to fulfil the SFR are configurable, then the evaluator shall check that the guidance documentation describes how to configure those thresholds. Either the allowed values are specified in the guidance documentation and must not exceed the limits specified in the SFR (one hour of session time, one gigabyte of transmitted traffic) or the TOE must not accept values beyond the limits specified in the SFR. The evaluator shall check that the guidance documentation describes that the TOE reacts to the first threshold reached.

4.1.8.3 Tests

FCS_SSHS_EXT.1.2

440 Test 1: Using the guidance documentation, the evaluator shall configure the TOE to accept password-based authentication, and demonstrate that a user can be successfully authenticated to the TOE over SSH using a password as an authenticator.

Moved (insertion) [76]

Moved (insertion) [84]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

441 Test 2: The evaluator shall use an SSH client, enter an incorrect password to attempt to authenticate to the TOE, and demonstrate that the authentication fails.

Note: Public key authentication is tested as part of testing for FCS_SSHS_EXT.1.5

FCS_SSHS_EXT.1.3

442 The evaluator shall demonstrate that if the TOE receives a packet larger than that specified in this component, that packet is dropped.

FCS_SSHS_EXT.1.4

443 The evaluator must ensure that only claimed ciphers and cryptographic primitives are used to establish a SSH connection. To verify this, the evaluator shall start session establishment for a SSH connection from a remote client (referred to as 'remote endpoint' below). The evaluator shall capture the traffic exchanged between the TOE and the remote endpoint during protocol negotiation (e.g. using a packet capture tool or information provided by the endpoint, respectively). The evaluator shall verify from the captured traffic that the TOE offers all the ciphers defined in the TSS for the TOE for SSH sessions, but no additional ones compared to the definition in the TSS. The evaluator shall perform one successful negotiation of an SSH session to verify that the TOE behaves as expected. It is sufficient to observe the successful negotiation of the session to satisfy the intent of the test. If the evaluator detects that not all ciphers defined in the TSS for SSH are supported by the TOE and/or the TOE supports one or more additional ciphers not defined in the TSS for SSH, the test shall be regarded as failed.

FCS_SSHS_EXT.1.5

444 Test 1: The evaluator shall establish a SSH connection using each of the public key algorithms specified by the requirement to authenticate the TOE to an SSH client. It is sufficient to observe (on the wire) the successful negotiation of the algorithm to satisfy the intent of the test.

445 Test 2: The evaluator shall choose one public key algorithm supported by the TOE. The evaluator shall generate a new key pair for that algorithm without configuring the TOE to recognize the public key for authentication. The evaluator shall use an SSH client to attempt to connect to the TOE with the new key pair and demonstrate that authentication fails.

446 Test 3: The evaluator shall configure an SSH client to only allow the a public key algorithm that is not included in the ST selection. The evaluator shall attempt to establish an SSH connection from the SSH client to the TOE and observe that the connection is rejected.

FCS_SSHS_EXT.1.6

447 Test 1: The evaluator shall establish a SSH connection using each of the integrity algorithms specified by the requirement. It is sufficient to observe

Moved (insertion) [80]

Moved (insertion) [82]

Moved (insertion) [79]

Moved (insertion) [83]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

(on the wire) the successful negotiation of the algorithm to satisfy the intent of the test.

Moved (insertion) [81]

448 Test 2: The evaluator shall configure an SSH client to only allow a MAC algorithm that is not included in the ST selection. The evaluator shall attempt to connect from the SSH client to the TOE and observe that the attempt fails.

Moved (insertion) [87]

FCS_SSHS_EXT.1.7

449 Test 1: The evaluator shall configure an SSH client to only allow the diffie-hellman-group1-sha1 key exchange. The evaluator shall attempt to connect from the SSH client to the TOE and observe that the attempt fails.

450 Test 2: For each allowed key exchange method, the evaluator shall configure an SSH client to only allow that method for key exchange, attempt to connect from the client to the TOE, and observe that the attempt succeeds.

FCS_SSHS_EXT.1.8

451 The evaluator needs to perform testing that rekeying is performed according to the description in the TSS. The evaluator shall test both, the time-based threshold and the traffic-based threshold.

452 For testing of the time-based threshold the evaluator shall use an SSH client to connect to the TOE and keep the session open until the threshold is reached. The evaluator shall verify that the SSH session has been active longer than the threshold value and a corresponding audit event has been generated by the TOE.

453 Testing does not necessarily have to be performed with the threshold configured at the maximum allowed value of one hour of session time but the value used for testing shall not exceed one hour. The evaluator needs to ensure that the rekeying has been initiated by the TOE and not by the SSH client that is connected to the TOE.

454 For testing of the traffic-based threshold the evaluator shall use an SSH client to connect to the TOE, and shall transmit data from and to the TOE within the active SSH session until the threshold for transmitted traffic is reached. The transmitted traffic is the total traffic comprising incoming and outgoing traffic.

455 The evaluator shall verify that more data has been transmitted within the SSH session than the threshold allows and a corresponding audit event has been generated by the TOE.

456 Testing does not necessarily have to be performed with the threshold configured at the maximum allowed value of one gigabyte of transferred traffic but the value used for testing shall not exceed one gigabyte. The evaluator needs to ensure that the rekeying has been initiated by the TOE and not by the SSH client that is connected to the TOE.

457 If one or more thresholds that are checked by the TOE to fulfil the SFR are configurable, the evaluator needs to verify that the threshold(s) can be

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

configured as described in the guidance documentation and the evaluator needs to test that modification of the thresholds is restricted to Security Administrators (as required by FMT_MOF.1/Functions).

Moved (insertion) [88]

4.1.9 FCS_TLSC_EXT.1 Extended: TLS Client Protocol

4.1.9.1 TSS

FCS_TLSC_EXT.1.1

458 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that the ciphersuites supported are specified. The evaluator shall check the TSS to ensure that the ciphersuites specified include those listed for this component.

FCS_TLSC_EXT.1.2

459 The evaluator shall ensure that the TSS describes the client's method of establishing all reference identifiers from the administrator/application-configured reference identifier, including which types of reference identifiers are supported (e.g. application-specific Subject Alternative Names) and whether IP addresses and wildcards are supported. The evaluator shall ensure that this description identifies if certificate pinning is supported or used by the TOE and how it is implemented.

460 Note that where a TLS channel is being used between components of a distributed TOE for FPT_ITT.1, the requirements to have the reference identifier established by the user are relaxed and the identifier may also be established through a "Gatekeeper" discovery process. The TSS should describe the discovery process and highlight how the reference identifier is supplied to the "joining" component.

Moved (insertion) [90]

FCS_TLSC_EXT.1.4

461 The evaluator shall verify that TSS describes the Supported Elliptic Curves Extension and whether the required behaviour is performed by default or may be configured.

4.1.9.2 Guidance Documentation

FCS_TLSC_EXT.1.1

462 The evaluator shall check the guidance documentation to ensure that it contains instructions on configuring the TOE so that TLS conforms to the description in the TSS.

Moved (insertion) [91]

FCS_TLSC_EXT.1.2

463 The evaluator shall verify that the AGD guidance includes instructions for setting the reference identifier to be used for the purposes of certificate validation in TLS.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS_TLSC_EXT.1.4

464 If the TSS indicates that the Supported Elliptic Curves Extension must be configured to meet the requirement, the evaluator shall verify that AGD guidance includes configuration of the Supported Elliptic Curves Extension.

4.1.9.3 Tests

FCS_TLSC_EXT.1.1

465 Test 1: The evaluator shall establish a TLS connection using each of the ciphersuites specified by the requirement. This connection may be established as part of the establishment of a higher-level protocol, e.g., as part of an HTTPS session. It is sufficient to observe the successful negotiation of a ciphersuite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).

466 Test 2: The evaluator shall attempt to establish the connection using a server with a server certificate that contains the Server Authentication purpose in the extendedKeyUsage field and verify that a connection is established. The evaluator will then verify that the client rejects an otherwise valid server certificate that lacks the Server Authentication purpose in the extendedKeyUsage field and a connection is not established. Ideally, the two certificates should be identical except for the extendedKeyUsage field.

467 Test 3: The evaluator shall send a server certificate in the TLS connection that does not match the server-selected ciphersuite (for example, send an ECDSA certificate while using the TLS_RSA_WITH_AES_128_CBC_SHA ciphersuite). The evaluator shall verify that the TOE disconnects after receiving the server's Certificate handshake message.

468 Test 4: The evaluator shall configure the server to select the TLS_NULL_WITH_NULL_NULL ciphersuite and verify that the client denies the connection.

469 Test 5: The evaluator performs the following modifications to the traffic:

- a) Change the TLS version selected by the server in the Server Hello to a non-supported TLS version (for example 1.5 represented by the two bytes 03 06) and verify that the client rejects the connection.
- b) Modify at least one byte in the server's nonce in the Server Hello handshake message, and verify that the client rejects the Server Key Exchange handshake message (if using a DHE or ECDHE ciphersuite) or that the server denies the client's Finished handshake message.
- c) Modify the server's selected ciphersuite in the Server Hello handshake message to be a ciphersuite not presented in the Client Hello handshake message. The evaluator shall verify that the client rejects the connection after receiving the Server Hello.

Moved (insertion) [92]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- d) If using DHE or ECDH, modify the signature block in the Server's Key Exchange handshake message, and verify that the client rejects the connection after receiving the Server Key Exchange message. This test does not apply to cipher suites using RSA key exchange. If a TOE only supports RSA key exchange in conjunction with TLS, then this test shall be omitted.
- e) Modify a byte in the Server Finished handshake message, and verify that the client sends a fatal alert upon receipt and does not send any application data.
- f) Send a garbled message from the server after the server has issued the ChangeCipherSpec message and verify that the client denies the connection.

FCS TLSC EXT.1.2

470 Note that where a TLS channel is being used between components of a distributed TOE for FPT ITT.1, the requirements to have the reference identifier established by the user are relaxed and the identifier may also be established through a "Gatekeeper" discovery process.

471 The evaluator shall configure the reference identifier per the AGD guidance and perform the following tests during a TLS connection:

- a) Test 1: The evaluator shall present a server certificate that does not contain an identifier in either the Subject Alternative Name (SAN) or Common Name (CN) that matches the reference identifier. The evaluator shall verify that the connection fails.
- b) Test 2: The evaluator shall present a server certificate that contains a CN that matches the reference identifier, contains the SAN extension, but does not contain an identifier in the SAN that matches the reference identifier. The evaluator shall verify that the connection fails. The evaluator shall repeat this test for each supported SAN type.
- c) Test 3: The evaluator shall present a server certificate that contains a CN that matches the reference identifier and does not contains the SAN extension. The evaluator shall verify that the connection succeeds.
- d) Test 4: The evaluator shall present a server certificate that contains a CN that does not match the reference identifier but does contain an identifier in the SAN that matches. The evaluator shall verify that the connection succeeds.
- e) Test 5: The evaluator shall perform the following wildcard tests with each supported type of reference identifier:
 - 1) The evaluator shall present a server certificate containing a wildcard that is not in the left-most label of the presented identifier (e.g. foo.*.example.com) and verify that the connection fails.

Moved (insertion) [99]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- 2) The evaluator shall present a server certificate containing a wildcard in the left-most label (e.g. *.example.com). The evaluator shall configure the reference identifier with a single left-most label (e.g. foo.example.com) and verify that the connection succeeds. The evaluator shall configure the reference identifier without a left-most label as in the certificate (e.g. example.com) and verify that the connection fails. The evaluator shall configure the reference identifier with two left-most labels (e.g. bar.foo.example.com) and verify that the connection fails.
- f) Test 6: [conditional] If URI or service name reference identifiers are supported, the evaluator shall configure the DNS name and the service identifier. The evaluator shall present a server certificate containing the correct DNS name and service identifier in the URIName or SRVName fields of the SAN and verify that the connection succeeds. The evaluator shall repeat this test with the wrong service identifier (but correct DNS name) and verify that the connection fails.
- g) Test 7: [conditional] If pinned certificates are supported, the evaluator shall present a certificate that does not match the pinned certificate and verify that the connection fails.

FCS_TLSC_EXT.1.3

- 472 Test 1: The evaluator shall demonstrate that using a certificate without a valid certification path results in the function failing. Using the administrative guidance, the evaluator shall then load a certificate or certificates needed to validate the certificate to be used in the function and demonstrate that the function succeeds. If the certificate is validated and a trusted channel is established, the test passes. The evaluator then shall delete one of the certificates and show that the certificate is not validated and the trusted channel is not established.

FCS_TLSC_EXT.1.4

- 473 Test 1: If using ECDHE ciphers, the evaluator shall configure the server to perform an ECDHE key exchange in the TLS connection using a non-supported curve (for example P-192) and shall verify that the TOE disconnects after receiving the server's Key Exchange handshake message.

4.1.10 FCS_TLSC_EXT.2 Extended: TLS Client Protocol with authentication

4.1.10.1 TSS

FCS_TLSC_EXT.2.1

- 474 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that the ciphersuites supported are specified. The evaluator shall check the TSS to ensure that the ciphersuites specified include those listed for this component.

Moved (insertion) [105]

Moved (insertion) [107]

Moved (insertion) [109]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS TLSC EXT.2.2

475 The evaluator shall ensure that the TSS describes the client's method of establishing all reference identifiers from the administrator/application-configured reference identifier, including which types of reference identifiers are supported (e.g. application-specific Subject Alternative Names) and whether IP addresses and wildcards are supported. The evaluator shall ensure that this description identifies if certificate pinning is supported or used by the TOE and how it is implemented.

Moved (insertion) [110]

FCS TLSC EXT.2.4

476 The evaluator shall verify that TSS describes the Supported Elliptic Curves Extension and whether the required behaviour is performed by default or may be configured.

Moved (insertion) [112]

FCS TLSC EXT.2.5

477 The evaluator shall ensure that the TSS description required per FIA X509 EXT.2.1 includes the use of client-side certificates for TLS mutual authentication.

4.1.10.2 Guidance Documentation

FCS TLSC EXT.2.1

478 The evaluator shall check the guidance documentation to ensure that it contains instructions on configuring the TOE so that TLS conforms to the description in the TSS.

Moved (insertion) [113]

FCS TLSC EXT.2.2

479 The evaluator shall verify that the AGD guidance includes instructions for setting the reference identifier to be used for the purposes of certificate validation in TLS.

Moved (insertion) [114]

FCS TLSC EXT.2.4

480 If the TSS indicates that the Supported Elliptic Curves Extension must be configured to meet the requirement, the evaluator shall verify that AGD guidance includes configuration of the Supported Elliptic Curves Extension.

FCS TLSC EXT.2.5

481 If the TSS indicates that mutual authentication using X.509v3 certificates is used, the evaluator shall verify that the AGD guidance includes instructions for configuring the client-side certificates for TLS mutual authentication.

Moved (insertion) [115]

4.1.10.3 Tests

FCS TLSC EXT.2.1

482 Test 1: The evaluator shall establish a TLS connection using each of the ciphersuites specified by the requirement. This connection may be established as part of the establishment of a higher-level protocol, e.g., as part of an HTTPS session. It is sufficient to observe the successful negotiation of a

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

ciphersuite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).

483 Test 2: The evaluator shall attempt to establish the connection using a server with a server certificate that contains the Server Authentication purpose in the extendedKeyUsage field and verify that a connection is established. The evaluator will then verify that the client rejects an otherwise valid server certificate that lacks the Server Authentication purpose in the extendedKeyUsage field and a connection is not established. Ideally, the two certificates should be identical except for the extendedKeyUsage field.

484 Test 3: The evaluator shall send a server certificate in the TLS connection that does not match the server-selected ciphersuite (for example, send an ECDSA certificate while using the TLS_RSA_WITH_AES_128_CBC_SHA ciphersuite.) The evaluator shall verify that the TOE disconnects after receiving the server's Certificate handshake message.

485 Test 4: The evaluator shall configure the server to select the TLS_NULL_WITH_NULL_NULL ciphersuite and verify that the client denies the connection.

486 Test 5: The evaluator performs the following modifications to the traffic:

a) Change the TLS version selected by the server in the Server Hello to a non-supported TLS version (for example 1.5 represented by the two bytes 03 06) and verify that the client rejects the connection.

b) Modify at least one byte in the server's nonce in the Server Hello handshake message, and verify that the client rejects the Server Key Exchange handshake message (if using a DHE or ECDHE ciphersuite) or that the server denies the client's Finished handshake message.

c) Modify the server's selected ciphersuite in the Server Hello handshake message to be a ciphersuite not presented in the Client Hello handshake message. The evaluator shall verify that the client rejects the connection after receiving the Server Hello.

d) If using DHE or ECDH, modify the signature block in the Server's Key Exchange handshake message, and verify that the client rejects the connection after receiving the Server Key Exchange message. This test does not apply to cipher suites using RSA key exchange. If a TOE only supports RSA key exchange in conjunction with TLS then this test shall be omitted.

e) Modify a byte in the Server Finished handshake message, and verify that the client sends a fatal alert upon receipt and does not send any application data.

Moved (insertion) [139]

Moved (insertion) [157]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- f) Send a garbled message from the Server after the Server has issued the ChangeCipherSpec message and verify that the client denies the connection.

FCS_TLSC_EXT.2.2

487 The evaluator shall configure the reference identifier per the AGD guidance and perform the following tests during a TLS connection:

- a) Test 1: The evaluator shall present a server certificate that does not contain an identifier in either the Subject Alternative Name (SAN) or Common Name (CN) that matches the reference identifier. The evaluator shall verify that the connection fails.
- b) Test 2: The evaluator shall present a server certificate that contains a CN that matches the reference identifier, contains the SAN extension, but does not contain an identifier in the SAN that matches the reference identifier. The evaluator shall verify that the connection fails. The evaluator shall repeat this test for each supported SAN type.
- c) Test 3: The evaluator shall present a server certificate that contains a CN that matches the reference identifier and does not contain the SAN extension. The evaluator shall verify that the connection succeeds.
- d) Test 4: The evaluator shall present a server certificate that contains a CN that does not match the reference identifier but does contain an identifier in the SAN that matches. The evaluator shall verify that the connection succeeds.
- e) Test 5: The evaluator shall perform the following wildcard tests with each supported type of reference identifier:
 - 1) The evaluator shall present a server certificate containing a wildcard that is not in the left-most label of the presented identifier (e.g. foo.*.example.com) and verify that the connection fails.
 - 2) The evaluator shall present a server certificate containing a wildcard in the left-most label (e.g. *.example.com). The evaluator shall configure the reference identifier with a single left-most label (e.g. foo.example.com) and verify that the connection succeeds. The evaluator shall configure the reference identifier without a left-most label as in the certificate (e.g. example.com) and verify that the connection fails. The evaluator shall configure the reference identifier with two left-most labels (e.g. bar.foo.example.com) and verify that the connection fails.
- f) Test 6: [conditional] If URI or Service name reference identifiers are supported, the evaluator shall configure the DNS name and the service identifier. The evaluator shall present a server certificate containing the correct DNS name and service identifier in the URIName or

Moved (insertion) [121]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

SRVName fields of the SAN and verify that the connection succeeds. The evaluator shall repeat this test with the wrong service identifier (but correct DNS name) and verify that the connection fails.

- g) Test 7: [conditional] If pinned certificates are supported, the evaluator shall present a certificate that does not match the pinned certificate and verify that the connection fails.

FCS_TLSC_EXT.2.3

488 Test 1: The evaluator shall demonstrate that using a certificate without a valid certification path results in the function failing. Using the administrative guidance, the evaluator shall then load a certificate or certificates needed to validate the certificate to be used in the function, and demonstrate that the function succeeds. If the certificate is validated and a trusted channel is established, the test passes. The evaluator then shall delete one of the certificates and show that the certificate is not validated and the trusted channel is not established.

Moved (insertion) [126]

FCS_TLSC_EXT.2.4

489 Test 1: If using DHE or ECDH, the evaluator shall configure the server to perform an ECDHE key exchange in the TLS connection using a non-supported curve (for example P-192) and shall verify that the TOE disconnects after receiving the server's Key Exchange handshake message.

Moved (insertion) [128]

FCS_TLSC_EXT.2.5

490 Test 1: The evaluator shall perform the following modification to the traffic:

- a) Configure the server to require mutual authentication and then modify a byte in a CA field in the Server's Certificate Request handshake message. The modified CA field must not be the CA used to sign the client's certificate. The evaluator shall verify the connection fails.

Moved (insertion) [129]

Moved (insertion) [130]

4.1.11 FCS_TLSS_EXT.1 Extended: TLS Server Protocol

4.1.11.1 TSS

FCS_TLSS_EXT.1.1

491 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that the ciphersuites supported are specified. The evaluator shall check the TSS to ensure that the ciphersuites specified are identical to those listed for this component.

FCS_TLSS_EXT.1.2

492 The evaluator shall verify that the TSS contains a description of the denial of old SSL and TLS versions.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS TLSS EXT.1.3

493 The evaluator shall verify that the TSS describes the key agreement parameters of the server Key Exchange message.

4.1.11.2 Guidance Documentation

FCS TLSS EXT.1.1

494 The evaluator shall check the guidance documentation to ensure that it contains instructions on configuring the TOE so that TLS conforms to the description in the TSS (for instance, the set of ciphersuites advertised by the TOE may have to be restricted to meet the requirements).

FCS TLSS EXT.1.2

495 The evaluator shall verify that any configuration necessary to meet the requirement must be contained in the AGD guidance.

FCS TLSS EXT.1.3

496 The evaluator shall verify that any configuration necessary to meet the requirement must be contained in the AGD guidance.

4.1.11.3 Tests

FCS TLSS EXT.1.1

497 Test 1: The evaluator shall establish a TLS connection using each of the ciphersuites specified by the requirement. This connection may be established as part of the establishment of a higher-level protocol, e.g., as part of an HTTPS session. It is sufficient to observe the successful negotiation of a ciphersuite to satisfy the intent of the test; it is not necessary to examine the characteristics of the encrypted traffic to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).

498 Test 2: The evaluator shall send a Client Hello to the server with a list of ciphersuites that does not contain any of the ciphersuites in the server's ST and verify that the server denies the connection. Additionally, the evaluator shall send a Client Hello to the server containing only the TLS NULL WITH NULL_NULL ciphersuite and verify that the server denies the connection.

499 Test 3: The evaluator shall use a client to send a key exchange message in the TLS connection that does not match the server-selected ciphersuite (for example, send an ECDHE key exchange while using the TLS RSA WITH AES 128 CBC SHA ciphersuite or send a RSA key exchange while using one of the ECDSA ciphersuites.) The evaluator shall verify that the TOE disconnects after receiving the key exchange message.

500 Test 4: The evaluator shall perform the following modifications to the traffic:

a) withdrawn

Moved (insertion) [131]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- b) withdrawn
- c) Modify a byte in the Client Finished handshake message, and verify that the server rejects the connection and does not send any application data.
- d) After generating a fatal alert by sending a Finished message from the client before the client sends a ChangeCipherSpec message, send a Client Hello with the session identifier from the previous test, and verify that the server denies the connection.
- e) Send a garbled message from the client after the client has issued the ChangeCipherSpec message and verify that the Server denies the connection.

FCS_TLSS_EXT.1.2

501 The evaluator shall send a Client Hello requesting a connection for all mandatory and selected protocol versions in the SFR (e.g. by enumeration of protocol versions in a test client) and verify that the server denies the connection for each attempt.

FCS_TLSS_EXT.1.3

502 If using ECDHE ciphers, the evaluator shall attempt a connection using an ECDHE ciphersuite and a configured curve. Using a packet analyser, verify that the key agreement parameters in the Key Exchange message are the ones configured. (Determining that the size matches the expected size for the configured curve is sufficient.) The evaluator shall repeat this test for each supported NIST Elliptic Curve and each supported Diffie-Hellman key size.

503 The evaluator shall attempt establishing connection using each claimed key establishment protocol (RSA, DH, ECDHE) with each claimed parameter (RSA key size, Diffie-Hellman parameters, supported curves) as selected in FCS_TLSS_EXT.1.3. For example, determining that the RSA key size matches the claimed size is sufficient to satisfy this test. The evaluator shall ensure that each supported parameter combination is tested.

504 Note that this testing can be accomplished in conjunction with other testing activities

4.1.12 FCS_TLSS_EXT.2 Extended: TLS Server Protocol with mutual authentication

4.1.12.1 TSS

FCS_TLSS_EXT.2.1

505 The evaluator shall check the description of the implementation of this protocol in the TSS to ensure that the ciphersuites supported are specified. The evaluator shall check the TSS to ensure that the ciphersuites specified are identical to those listed for this component.

Moved (insertion) [133]

Moved (insertion) [134]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS TLSS EXT.2.2

506 The evaluator shall verify that the TSS contains a description of the denial of old SSL and TLS versions.

Moved (insertion) [146]

FCS TLSS EXT.2.3

507 The evaluator shall verify that the TSS describes the key agreement parameters of the server Key Exchange message.

Moved (insertion) [142]

FCS TLSS EXT.2.4 and FCS TLSS EXT.2.5

508 The evaluator shall ensure that the TSS description required per FIA X509 EXT.2.1 includes the use of client-side certificates for TLS mutual authentication.

Moved (insertion) [144]

FCS TLSS EXT.2.6

509 The evaluator shall verify that the TSS describes how the DN or SAN in the certificate is compared to the expected identifier.

Moved (insertion) [144]

4.1.12.2 Guidance Documentation

FCS TLSS EXT.2.1

510 The evaluator shall check the guidance documentation to ensure that it contains instructions on configuring the TOE so that TLS conforms to the description in the TSS (for instance, the set of ciphersuites advertised by the TOE may have to be restricted to meet the requirements).

Moved (insertion) [147]

FCS TLSS EXT.2.2

511 The evaluator shall verify that any configuration necessary to meet the requirement must be contained in the AGD guidance.

Moved (insertion) [148]

FCS TLSS EXT.2.3

512 The evaluator shall verify that any configuration necessary to meet the requirement must be contained in the AGD guidance.

FCS TLSS EXT.2.4 and FCS TLSS EXT.2.5

513 If the TSS indicates that mutual authentication using X.509v3 certificates is used, the evaluator shall verify that the AGD guidance includes instructions for configuring the client-side certificates for TLS mutual authentication.

Moved (insertion) [151]

FCS TLSS EXT.2.6

514 If the DN is not compared automatically to the Domain Name or IP address, username, or email address, then the evaluator shall ensure that the AGD guidance includes configuration of the expected DN or the directory server for the connection.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

4.1.12.3 Tests

FCS TLSS EXT.2.1

- 515 Test 1: The evaluator shall establish a TLS connection using each of the ciphersuites specified by the requirement. This connection may be established as part of the establishment of a higher-level protocol, e.g., as part of an HTTPS session. It is sufficient to observe the successful negotiation of a ciphersuite to satisfy the intent of the test: it is not necessary to examine the characteristics of the encrypted traffic to discern the ciphersuite being used (for example, that the cryptographic algorithm is 128-bit AES and not 256-bit AES).
- 516 Test 2: The evaluator shall send a Client Hello to the server with a list of ciphersuites that does not contain any of the ciphersuites in the server's ST and verify that the server denies the connection. Additionally, the evaluator shall send a Client Hello to the server containing only the TLS NULL WITH NULL NULL ciphersuite and verify that the server denies the connection.
- 517 Test 3: The evaluator shall use a client to send a key exchange message in the TLS connection that does not match the server-selected ciphersuite (for example, send an ECDHE key exchange while using the TLS_RSA_WITH_AES_128_CBC_SHA ciphersuite or send a RSA key exchange while using one of the ECDSA ciphersuites.) The evaluator shall verify that the TOE disconnects after receiving the Key Exchange message.
- 518 Test 4: The evaluator shall perform the following modifications to the traffic:
- a) withdrawn
 - b) withdrawn
 - c) Modify a byte in the Client Finished handshake message, and verify that the server rejects the connection and does not send any application data.
 - d) After generating a fatal alert by sending a Finished message from the client before the client sends a ChangeCipherSpec message, send a Client Hello with the session identifier from the previous test, and verify that the server denies the connection.
 - e) Send a garbled message from the client after the client has issued the ChangeCipherSpec message and verify that the Server denies the connection.

FCS TLSS EXT.2.2

- 519 The evaluator shall send a Client Hello requesting a connection for all mandatory and selected protocol versions in the SFR (e.g. by enumeration of protocol versions in a test client) and verify that the server denies the connection for each attempt.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

FCS TLSS EXT.2.3

- 520 The evaluator shall attempt a connection using an ECDHE ciphersuite and a configured curve. Using a packet analyser, verify that the key agreement parameters in the Key Exchange message are the ones configured. (Determining that the size matches the expected size for the configured curve is sufficient.) The evaluator shall repeat this test for each supported NIST Elliptic Curve and each supported Diffie-Hellman key size.
- 521 The evaluator shall attempt establishing connection using each claimed key establishment protocol (RSA, DH, ECDHE) with each claimed parameter (RSA key size, Diffie-Hellman parameters, supported curves) as selected in FCS TLSS EXT.2.3. For example, determining that the RSA key size matches the claimed size is sufficient to satisfy this test. The evaluator shall ensure that each supported parameter combination is tested.
- 522 Note that this testing can be accomplished in conjunction with the other testing activities

FCS TLSS EXT.2.4 and FCS TLSS EXT.2.5

- 523 Test 1: The evaluator shall configure the server to send a certificate request to the client and shall attempt a connection without sending a certificate from the client. The evaluator shall verify that the connection is denied.
- 524 Test 2: The evaluator shall configure the server to send a certificate request to the client without the supported signature algorithm used by the client's certificate. The evaluator shall attempt a connection using the client certificate and verify that the connection is denied.
- 525 Test 3: The evaluator shall demonstrate that using a certificate without a valid certification path results in the function failing. Using the administrative guidance, the evaluator shall then load a certificate, or certificates, needed to validate the certificate to be used in the function and demonstrate that the function succeeds. The evaluator then shall delete one of the certificates and show that the function fails.
- 526 Test 4: The evaluator shall configure the client to send a certificate that does not chain one of the Certificate Authorities (either a Root or Intermediate CA) in the server's Certificate Request message. The evaluator shall verify that the attempted connection is denied.
- 527 Test 5: The evaluator shall configure the client to send a certificate with the Client Authentication purpose in the extendedKeyUsage field and verify that the server accepts the attempted connection. The evaluator shall repeat this test without the Client Authentication purpose and shall verify that the server denies the connection. Ideally, the two certificates should be identical except for the Client Authentication purpose.
- 528 Test 6: The evaluator shall perform the following modifications to the traffic:

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- a) Configure the server to require mutual authentication and then modify a byte in the client's certificate. The evaluator shall verify that the server rejects the connection.
- b) Configure the server to require mutual authentication and then modify a byte in the signature block of the client's Certificate Verify handshake message. The evaluator shall verify that the server rejects the connection.

FCS_TLSS_EXT.2.6

529 The evaluator shall send a client certificate with an identifier that does not match an expected identifier and verify that the server denies the connection.

4.2 Identification and Authentication (FIA)

4.2.1 FIA_X509_EXT.1/Rev X.509 Certificate Validation

4.2.1.1 TSS

530 The evaluator shall ensure the TSS describes where the check of validity of the certificates takes place, and that the TSS identifies any of the rules for extendedKeyUsage fields (in FIA_X509_EXT.1.1) that are not supported by the TOE (i.e. where the ST is therefore claiming that they are trivially satisfied). It is expected that revocation checking is performed when a certificate is used in an authentication step and when performing trusted updates (if selected). It is not sufficient to verify the status of a X.509 certificate only when it's loaded onto the device. It is not necessary to verify the revocation status of X.509 certificates during power-up self-tests (if the option for using X.509 certificates for self-testing is selected).

4.2.1.2 Tests

531 The evaluator shall demonstrate that checking the validity of a certificate is performed when a certificate is used in an authentication step or when performing trusted updates (if FPT_TUD_EXT.2 is selected). It is not sufficient to verify the status of a X.509 certificate only when it is loaded onto the TOE. It is not necessary to verify the revocation status of X.509 certificates during power-up self-tests (if the option for using X.509 certificates for self-testing is selected). The evaluator shall perform the following tests for FIA_X509_EXT.1.1/Rev:

- a) Test 1a: The evaluator shall present the TOE with a valid chain of certificates (terminating in a trusted CA certificate) as needed to validate the certificate to be used in the function, and shall use this chain to demonstrate that the function succeeds.

Test 1b: The evaluator shall then delete one of the certificates in the presented chain (i.e. the root CA certificate or other intermediate certificate, but not the end-entity certificate), and show that an attempt to validate an incomplete chain fails.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- b) Test 2: The evaluator shall demonstrate that validating an expired certificate results in the function failing.
- c) Test 3: The evaluator shall test that the TOE can properly handle revoked certificates—conditional on whether CRL or OCSP is selected; if both are selected, then a test shall be performed for each method. The evaluator shall test revocation of the peer certificate and revocation of the peer intermediate CA certificate i.e. the intermediate CA certificate should be revoked by the root CA. The evaluator shall ensure that a valid certificate is used, and that the validation function succeeds. The evaluator then attempts the test with a certificate that has been revoked (for each method chosen in the selection) to ensure when the certificate is no longer valid that the validation function fails.
- d) Test 4: If OCSP is selected, the evaluator shall configure the OCSP server or use a man-in-the-middle tool to present a certificate that does not have the OCSP signing purpose and verify that validation of the OCSP response fails. If CRL is selected, the evaluator shall configure the CA to sign a CRL with a certificate that does not have the cRLsign key usage bit set, and verify that validation of the CRL fails.
- e) Test 5: The evaluator shall modify any byte in the first eight bytes of the certificate and demonstrate that the certificate fails to validate. (The certificate will fail to parse correctly.)
- f) Test 6: The evaluator shall modify any byte in the last byte of the certificate and demonstrate that the certificate fails to validate. (The signature on the certificate will not validate.)
- g) Test 7: The evaluator shall modify any byte in the public key of the certificate and demonstrate that the certificate fails to validate. (The hash of the certificate will not validate.)

532 The evaluator shall perform the following tests for FIA_X509_EXT.1.2/Rev. The tests described must be performed in conjunction with the other certificate services assurance activities, including the functions in FIA_X509_EXT.2.1/Rev. The tests for the extendedKeyUsage rules are performed in conjunction with the uses that require those rules. Where the TSS identifies any of the rules for extendedKeyUsage fields (in FIA_X509_EXT.1.1) that are not supported by the TOE (i.e. where the ST is therefore claiming that they are trivially satisfied) then the associated extendedKeyUsage rule testing may be omitted.

533 The evaluator shall create a chain of at least three certificates: the node certificate to be tested, an intermediate CA, and the self-signed Root CA.

- a) Test 1: The evaluator shall construct a certificate path, such that the certificate of the CA issuing the TOE's certificate does not contain the basicConstraints extension. The validation of the certificate path fails.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- b) Test 2: The evaluator shall construct a certificate path, such that the certificate of the CA issuing the TOE's certificate has the cA flag in the basicConstraints extension set to FALSE. The validation of the certificate path fails.
- c) Test 3: The evaluator shall construct a certificate path, such that the certificate of the CA issuing the TOE's certificate has the cA flag in the basicConstraints extension set to TRUE. The validation of the certificate path succeeds.

534 The evaluator shall repeat these tests for each distinct use of certificates. Thus, for example, use of certificates for TLS connection is distinct from use of certificates for trusted updates so both of these uses would be tested. But there is no need to repeat the tests for each separate TLS channel in FTP_ITC.1 and FTP_TRP.1/Admin (unless the channels use separate implementations of TLS).

4.2.2 FIA_X509_EXT.2 X.509 Certificate Authentication

4.2.2.1 TSS

535 The evaluator shall check the TSS to ensure that it describes how the TOE chooses which certificates to use, and any necessary instructions in the administrative guidance for configuring the operating environment so that the TOE can use the certificates.

536 The evaluator shall examine the TSS to confirm that it describes the behaviour of the TOE when a connection cannot be established during the validity check of a certificate used in establishing a trusted channel. The evaluator shall verify that any distinctions between trusted channels are described. If the requirement that the administrator is able to specify the default action, then the evaluator shall ensure that the guidance documentation contains instructions on how this configuration action is performed.

4.2.2.2 Tests

537 The evaluator shall perform the following test for each trusted channel:

538 The evaluator shall demonstrate that using a valid certificate that requires certificate validation checking to be performed in at least some part by communicating with a non-TOE IT entity. The evaluator shall then manipulate the environment so that the TOE is unable to verify the validity of the certificate, and observe that the action selected in FIA_X509_EXT.2.2 is performed. If the selected action is administrator-configurable, then the evaluator shall follow the guidance documentation to determine that all supported administrator-configurable options behave in their documented manner.

Moved (insertion) [171]

Moved (insertion) [172]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

4.2.3 FIA_X509_EXT.3 Extended: X509 Certificate Requests

Moved (insertion) [173]

4.2.3.1 TSS

539 If the ST author selects "device-specific information", the evaluator shall verify that the TSS contains a description of the device-specific fields used in certificate requests.

4.2.3.2 Guidance Documentation

540 The evaluator shall check to ensure that the guidance documentation contains instructions on requesting certificates from a CA, including generation of a Certificate Request Message. If the ST author selects "Common Name", "Organization", "Organizational Unit", or "Country", the evaluator shall ensure that this guidance includes instructions for establishing these fields before creating the certificate request message.

4.2.3.3 Tests

541 The evaluator shall perform the following tests:

a) Test 1: The evaluator shall use the guidance documentation to cause the TOE to generate a certificate request message. The evaluator shall capture the generated message and ensure that it conforms to the format specified. The evaluator shall confirm that the certificate request provides the public key and other required information, including any necessary user-input information.

b) Test 2: The evaluator shall demonstrate that validating a certificate response message without a valid certification path results in the function failing. The evaluator shall then load a certificate or certificates as trusted CAs needed to validate the certificate response message, and demonstrate that the function succeeds.

Moved (insertion) [174]

4.3 Protection of the TSF (FPT)

4.3.1 FPT_TST_EXT.2 Self tests based on certificates

Moved (insertion) [189]

4.3.1.1 Tests

542 The evaluator shall verify that the self test mechanism includes a certificate validation according to FIA_X509_EXT.1 and a check for the Code Signing purpose in the extendedKeyUsage.

543 The evaluator shall use an invalid certificate and perform the self test. This attempt should fail. The evaluator shall use a certificate that does not have the Code Signing purpose and verify that the self test fails. The evaluator shall repeat the test using a valid certificate and a certificate that contains the Code Signing purpose and verify that the self test succeeds. Testing for this element is performed in conjunction with the assurance activities for FPT_TST_EXT.1.

Moved (insertion) [190]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

544 It is not necessary to verify the revocation status of X.509 certificates during power-up.

4.3.2 FPT_TUD_EXT.2 Trusted Update based on certificates

4.3.2.1 TSS

545 The evaluator shall verify that the TSS describes how the TOE reacts if X.509 certificates are used for trusted updates and the administrator attempts to perform the trusted update using an expired certificate.

546 The TSS shall describe the point at which revocation checking is performed. It is expected that revocation checking is performed when a certificate is used when performing trusted updates. It is not sufficient to verify the status of a X.509 certificate only when it is loaded onto the device.

4.3.2.2 Guidance Documentation

547 The evaluator shall verify that the guidance documentation describes how the TOE reacts if X.509 certificates are used for trusted updates and the administrator attempts to perform the trusted update using an expired certificate. The description shall correspond to the description in the TSS.

4.3.2.3 Tests

548 The evaluator shall verify that the update mechanism includes a certificate validation according to FIA_X509_EXT.1 and a check for the Code Signing purpose in the extendedKeyUsage.

549 The evaluator shall digitally sign the update with an invalid certificate and verify that update installation fails. The evaluator shall digitally sign the application with a certificate that does not have the Code Signing purpose and verify that application installation fails. The evaluator shall repeat the test using a valid certificate and a certificate that contains the Code Signing purpose and verify that the application installation succeeds. The evaluator shall use a previously valid but expired certificate and verifies that the TOE reacts as described in the TSS and the guidance documentation. Testing for this element is performed in conjunction with the assurance activities for FPT_TUD_EXT.1.

550 The evaluator shall demonstrate that checking the validity of a certificate is performed at the time a certificate is used when performing trusted updates. It is not sufficient to verify the status of a X.509 certificate only when it is loaded onto the device.

Moved (insertion) [191]

Moved (insertion) [192]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

4.4 Security management (FMT)

4.4.1 FMT MOF.1/AutoUpdate

4.4.1.1 TSS

551 For distributed TOEs see chapter 2.4.1.1. There are no specific requirements for non-distributed TOEs.

4.4.1.2 Tests

552 The evaluator shall try to enable and disable automatic checking for updates or automatic updates (whichever is supported by the TOE) without prior authentication as security administrator (by authenticating as a user with no administrator privileges or without user authentication). The attempt to enable/disable automatic checking for updates should fail. According to the implementation no other users than the Security Administrator might be defined and without any user authentication the user might not be able to get to the point where the attempt to enable/disable automatic checking for updates can be executed. In that case it shall be demonstrated that access control mechanisms prevent execution up to the step that can be reached without authentication as Security Administrator.

Moved (insertion) [178]

553 The evaluator shall try to enable and disable automatic checking for updates or automatic updates (whichever is supported by the TOE) with prior authentication as security administrator. The attempt to enable/disable automatic checking for updates should be successful.

Moved (insertion) [180]

4.4.2 FMT MOE.1/Functions Management of security functions behaviour

4.4.2.1 TSS

554 For distributed TOEs see chapter 2.4.1.1. There are no specific requirements for non-distributed TOEs.

4.4.2.2 Tests

555 Test 1 (if 'transmission of audit data to external IT entity' is selected from the second selection together with 'modify the behaviour of' in the first selection): The evaluator shall try to modify all security related parameters for configuration of the transmission protocol for transmission of audit data to an external IT entity without prior authentication as security administrator (by authentication as a user with no administrator privileges or without user authentication at all). Attempts to modify parameters without prior authentication should fail. According to the implementation no other users than the Security Administrator might be defined and without any user authentication the user might not be able to get to the point where the attempt to modify the security related parameters can be executed. In that case it shall be demonstrated that access control mechanisms prevent execution up to the step that can be reached without authentication as Security Administrator.

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- 556 Test 2 (if 'transmission of audit data to external IT entity' is selected from the second selection together with 'modify the behaviour of' in the first selection): The evaluator shall try to modify all security related parameters for configuration of the transmission protocol for transmission of audit data to an external IT entity with prior authentication as security administrator. The effects of the modifications should be confirmed.
- 557 The evaluator does not have to test all possible values of the security related parameters for configuration of the transmission protocol for transmission of audit data to an external IT entity but at least one allowed value per parameter.
- 558 Test 1 (if 'handling of audit data' is selected from the second selection together with 'modify the behaviour of' in the first selection): The evaluator shall try to modify all security related parameters for configuration of the handling of audit data without prior authentication as security administrator (by authentication as a user with no administrator privileges or without user authentication at all). Attempts to modify parameters without prior authentication should fail. According to the implementation no other users than the Security Administrator might be defined and without any user authentication the user might not be able to get to the point where the attempt can be executed. In that case it shall be demonstrated that access control mechanisms prevent execution up to the step that can be reached without authentication as Security Administrator. The term 'handling of audit data' refers to the different options for selection and assignments in SFRs FAU_STG_EXT.1.2, FAU_STG_EXT.1.3 and FAU_STG_EXT.2/LocSpace.
- 559 Test 2 (if 'handling of audit data' is selected from the second selection together with 'modify the behaviour of' in the first selection): The evaluator shall try to modify all security related parameters for configuration of the handling of audit data with prior authentication as security administrator. The effects of the modifications should be confirmed. The term 'handling of audit data' refers to the different options for selection and assignments in SFRs FAU_STG_EXT.1.2, FAU_STG_EXT.1.3 and FAU_STG_EXT.2/LocSpace.
- 560 The evaluator does not necessarily have to test all possible values of the security related parameters for configuration of the handling of audit data but at least one allowed value per parameter.
- 561 Test 1 (if 'audit functionality when Local Audit Storage Space is full' is selected from the second selection together with 'modify the behaviour of' in the first selection): The evaluator shall try to modify the behaviour when Local Audit Storage Space is full without prior authentication as security administrator (by authentication as a user with no administrator privileges or without user authentication at all). This attempt should fail. According to the implementation no other users than the Security Administrator might be defined and without any user authentication the user might not be able to get to the point where the attempt can be executed. In that case it shall be demonstrated that access control mechanisms prevent execution up to the step that can be reached without authentication as Security Administrator.

Moved (insertion) [179]

Moved (insertion) [182]

Deleted: <object><object><object>

Evaluation Activities for Selection-Based Requirements

- 562 Test 2 (if 'audit functionality when Local Audit Storage Space is full' is selected from the second selection together with 'modify the behaviour of' in the first selection): The evaluator shall try to modify the behaviour when Local Audit Storage Space is full with prior authentication as security administrator. This attempt should be successful. The effect of the change shall be verified.
- 563 The evaluator does not necessarily have to test all possible values for the behaviour when Local Audit Storage Space is full but at least one change between allowed values for the behaviour.
- 564 Test 3 (if in the first selection 'determine the behaviour of' has been chosen together with for any of the options in the second selection): The evaluator shall try to determine the behaviour of all options chosen from the second selection without prior authentication as security administrator (by authentication as a user with no administrator privileges or without user authentication at all). This can be done in one test or in separate tests. The attempt(s) to determine the behaviour of the selected functions without administrator authentication shall fail. According to the implementation no other users than the Security Administrator might be defined and without any user authentication the user might not be able to get to the point where the attempt can be executed. In that case it shall be demonstrated that access control mechanisms prevent execution up to the step that can be reached without authentication as Security Administrator.
- 565 Test 4 (if in the first selection 'determine the behaviour of' has been chosen together with for any of the options in the second selection): The evaluator shall try to determine the behaviour of all options chosen from the second selection with prior authentication as security administrator. This can be done in one test or in separate tests. The attempt(s) to determine the behaviour of the selected functions with administrator authentication shall be successful.

Deleted: <object><object><object>

Evaluation Activities for SARs

5 Evaluation Activities for SARs

566 The sections below specify EAs for the Security Assurance Requirements (SARs) included in the related cPPs (see section 1.1 above). The EAs in Section 2 (Evaluation Activities for SFRs), Section 3 (Evaluation Activities for Optional Requirements), and Section 4 (Evaluation Activities for Selection-Based Requirements) are an interpretation of the more general CEM assurance requirements as they apply to the specific technology area of the TOE.

567 In this section, each SAR that is contained in the cPP is listed, and the EAs that are not associated with an SFR are captured here, or a reference is made to the CEM, and the evaluator is expected to perform the CEM work units.

5.1 ASE: Security Target Evaluation

5.1.1 General ASE

568 When evaluating a Security Target, the evaluator performs the work units as presented in the CEM. In addition, the evaluator ensures the content of the TSS in the ST satisfies the EAs specified in Section 2 (Evaluation Activities for SFRs).

5.1.2 TOE summary specification (ASE_TSS.1) for Distributed TOEs

569 For distributed TOEs only the SFRs classified as 'all' have to be fulfilled by all TOE parts. The SFRs classified as 'One' or 'Feature Dependent' only have to be fulfilled by either one or some TOE parts, respectively. To make sure that the distributed TOE as a whole fulfills all the SFRs the following actions for ASE_TSS.1 have to be performed as part of ASE_TSS.1.1E.

ASE_TSS.1 element	Evaluator Action
ASE_TSS.1.1C	<p><u>The evaluator shall examine the TSS to determine that it is clear which TOE components contribute to each SFR or how the components combine to meet each SFR.</u></p> <p><u>The evaluator shall verify the sufficiency to fulfil the related SFRs. This includes checking that the TOE as a whole fully covers all SFRs and that all functionality that is required to be audited is in fact audited regardless of the component that carries it out.</u></p>

Deleted: <object>

Deleted: Evaluation Activities

Deleted: The Evaluation Activities

Deleted: cases where the requirements are not technology dependent,

Deleted: (e.g., ASE (except as in section 3.1), ALC_CMC.1, ALC_CMS.1), those activities are not repeated here, rather they are expressed as part of the cPP...

Deleted: <#>An evaluation activity is defined here for evaluation of Exact Conformance claims against a cPP in a Security Target. Other aspects of ASE remain as defined in [CEM, 10].¶

<#>3.1.1—Conformance claims (ASE_CCL.1)¶

<#>¶The table below indicates the actions to be taken for particular ASE_CCL.1 elements in order to determine exact conformance with a cPP.¶

Deleted: CCL

Deleted: ASE_CCL.1.8C ... [54]

Deleted: CCL

Deleted: 10C

Deleted: The evaluator shall check that the statements of security requirements in the ST include all the mandatory SFRs in the cPP, and all of the selection-based SFRs that are entailed by selections made in other SFRs (including any SFR iterations added in the ST). The evaluator shall check that if any other SFRs are present in the ST (apart from iterations of SFRs in the cPP) then these are taken only from the list of optional SFRs specified in the cPP (the cPP will not necessarily include optional SFRs, but may do so). If optional SFRs from the cPP are included in the ST then the evaluator shall check that any selection-based SFRs entailed by the optional SFRs adopted are also included in the ST.

Deleted: <object><object><object>

Evaluation Activities for SARs

570 Note that additional Evaluation Activities for the TSS in the case of a distributed TOE are defined in section B.4.1.1.

5.2 ADV: Development

5.2.1 Basic Functional Specification (ADV_FSP.1)

571 The EAs for this assurance component focus on understanding the interfaces (e.g., application programming interfaces, command line interfaces, graphical user interfaces, network interfaces) described in the AGD documentation, and possibly identified in the TOE Summary Specification (TSS) in response to the SFRs. Specific evaluator actions to be performed against this documentation are identified (where relevant) for each SFR in Section 2, and in EAs for AGD, ATE and AVA SARs in other parts of Section 5.

572 The EAs presented in this section address the CEM work units ADV_FSP.1-1, ADV_FSP.1-2, ADV_FSP.1-3, and ADV_FSP.1-5.

573 The EAs are reworded for clarity and interpret the CEM work units such that they will result in more objective and repeatable actions by the evaluator. The EAs in this SD are intended to ensure the evaluators are consistently performing equivalent actions.

574 The documents to be examined for this assurance component in an evaluation are therefore the Security Target, AGD documentation, and any required supplementary information required by the cPP; no additional “functional specification” documentation is necessary to satisfy the EAs. The interfaces that need to be evaluated are also identified by reference to the EAs listed for each SFR, and are expected to be identified in the context of the Security Target, AGD documentation, and any required supplementary information defined in the cPP rather than as a separate list specifically for the purposes of CC evaluation. The direct identification of documentation requirements and their assessment as part of the EAs for each SFR also means that the tracing required in ADV_FSP.1.2D (work units ADV_FSP.1-4, ADV_FSP.1-6 and ADV_FSP.1-7) is treated as implicit and no separate mapping information is required for this element.

CEM ADV_FSP.1 Work Units	Evaluation Activities
ADV_FSP.1-1 The evaluator <i>shall examine</i> the functional specification to determine that it states the purpose of each SFR-supporting and SFR-enforcing TSFI.	5.2.1.1 Evaluation Activity: <i>The evaluator shall examine the interface documentation to ensure it describes the purpose and method of use for each TSFI that is identified as being security relevant.</i>
ADV_FSP.1-2 The evaluator <i>shall examine</i> the functional specification to determine that the	5.2.1.2 Evaluation Activity: <i>The evaluator shall examine the interface documentation</i>

Deleted: <object>

Deleted: ¶

Deleted: 3.2.1 →

Deleted: Evaluation Activities

Deleted: presented in

Deleted: functional requirements, and on the interfaces presented in the AGD documentation.

Deleted: requirements on

Deleted: section 2 above,

Deleted: Evaluation Activities

Deleted: 3 in this Supporting Document

Deleted: 3.2.1.1 → Evaluation Activity: ¶

¶ The evaluator shall check the interface documentation to ensure it describes the purpose and method of use for each TSFI that is identified as being security relevant. ¶

¶ In this context, TSFI are deemed security relevant if they are used by the administrator to configure the TOE, or to perform other administrative functions (e.g.,

Moved down [199]: audit review or performing updates). Additionally, those interfaces that are identified in the ST, or guidance documentation, as adhering to the security policies (as presented in the SFRs), are also considered security relevant. The intent, is that these interfaces will be

Deleted: The intent, is that these interfaces will be adequately tested, and having an understanding of how these interfaces are used in the TOE is necessary to ensure proper test coverage is applied. ¶

¶ The evaluator shall check the interface documentation to ensure it identifies and describes the parameters for each TSFI that is identified as being security relevant. ¶

Deleted: for aspects such as entropy analysis or cryptographic key management architecture¹

Deleted: Evaluation Activities.

Deleted: assurance activities

Deleted: required by

Deleted: Evaluation Activities

Deleted: <object><object><object>

Evaluation Activities for SARs

Deleted: <object>

method of use for each SFR-supporting and SFR-enforcing TSFI is given.	<i>to ensure it describes the purpose and method of use for each TSFI that is identified as being security relevant.</i>
ADV_FSP.1-3 The evaluator shall examine the presentation of the TSFI to determine that it identifies all parameters associated with each SFR-enforcing and SFR supporting TSFI.	5.2.1.3 Evaluation Activity: <i>The evaluator shall check the interface documentation to ensure it identifies and describes the parameters for each TSFI that is identified as being security relevant.</i>
ADV_FSP.1-4 The evaluator shall examine the rationale provided by the developer for the implicit categorisation of interfaces as SFR-non-interfering to determine that it is accurate.	Paragraph 561 from the CEM: <i>“In the case where the developer has provided adequate documentation to perform the analysis called for by the rest of the work units for this component without explicitly identifying SFR-enforcing and SFR-supporting interfaces, this work unit should be considered satisfied.”</i> Since the rest of the ADV_FSP.1 work units will have been satisfied upon completion of the EAs, it follows that this work unit is satisfied as well.
ADV_FSP.1-5 The evaluator shall check that the tracing links the SFRs to the corresponding TSFIs.	5.2.1.4 Evaluation Activity: <i>The evaluator shall examine the interface documentation to develop a mapping of the interfaces to SFRs.</i>
ADV_FSP.1-6 The evaluator shall examine the functional specification to determine that it is a complete instantiation of the SFRs.	EAs that are associated with the SFRs in Section 2, and, if applicable, Sections 3 and 4, are performed to ensure that all the SFRs where the security functionality is externally visible (i.e. at the TSFI) are covered. Therefore, the intent of this work unit is covered.
ADV_FSP.1-7 The evaluator shall examine the functional specification to determine that it is an accurate instantiation of the SFRs.	EAs that are associated with the SFRs in Section 2, and, if applicable, Sections 3 and 4, are performed to ensure that all the SFRs where the security functionality is externally visible (i.e. at the TSFI) are addressed, and that the description of the interfaces is accurate with respect to the specification captured in the SFRs. Therefore, the intent of this work unit is covered.

Table 1: Mapping of ADV_FSP.1 CEM Work Units to Evaluation Activities

Deleted: <object><object><object>

Evaluation Activities for SARs

5.2.1.1 Evaluation Activity:

575 *The evaluator shall examine the interface documentation to ensure it describes the purpose and method of use for each TSFI that is identified as being security relevant.*

576 *In this context, TSFI are deemed security relevant if they are used by the administrator to configure the TOE, or to perform other administrative functions (e.g. audit review or performing updates). Additionally, those interfaces that are identified in the ST, or guidance documentation, as adhering to the security policies (as presented in the SFRs), are also considered security relevant. The intent is that these interfaces will be adequately tested, and having an understanding of how these interfaces are used in the TOE is necessary to ensure proper test coverage is applied.*

577 The set of TSFI that are provided as evaluation evidence are contained in the Administrative Guidance and User Guidance.

5.2.1.2 Evaluation Activity

578 *The evaluator shall check the interface documentation to ensure it identifies and describes the parameters for each TSFI that is identified as being security relevant.*

5.2.1.3 Evaluation Activity

579 *The evaluator shall examine the interface documentation to develop a mapping of the interfaces to SFRs.*

580 The evaluator uses the provided documentation and first identifies, and then examines a representative set of interfaces to perform the EAs presented in Section 2, including the EAs associated with testing of the interfaces.

581 It should be noted that there may be some SFRs that do not have an interface that is explicitly “mapped” to invoke the desired functionality. For example, generating a random bit string, destroying a cryptographic key that is no longer needed, or the TSF failing to a secure state, are capabilities that may be specified in SFRs, but are not invoked by an interface.

582 However, if the evaluator is unable to perform some other required EA because there is insufficient design and interface information, then the evaluator is entitled to conclude that an adequate functional specification has not been provided, and hence that the verdict for the ADV_FSP.1 assurance component is a ‘fail’.

5.3 AGD: Guidance Documents

583 It is not necessary for a TOE to provide separate documentation to meet the individual requirements of AGD_OPE and AGD_PRE. Although the EAs in this section are described under the traditionally separate AGD families, the mapping between the documentation provided by the developer and

Deleted: <object>

Moved (insertion) [199]

Deleted: <object>

1

Deleted: Security Target

Deleted: AGD documentation

Deleted: public documents. Supplementary information may be public or proprietary:

Deleted: cPP

Deleted: /or

Deleted: descriptions will identify where such supplementary...

Deleted: is permitted to be proprietary and non-public...

Deleted: ~~~~~Section Break (Next Page)~~~~~

1

required in ADV_FSP.1.2D is treated as implicit, and no separate mapping information is required for this element.

Deleted: Evaluation Activity

Deleted: 3.3

Deleted: Evaluation Activities

Deleted: real TOE documents

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SARs

AGD_OPE and AGD_PRE requirements may be many-to-many, as long as all requirements are met in documentation that is delivered to administrators and users (as appropriate) as part of the TOE.

Deleted: <object>

584 Note that additional Evaluation Activities for the guidance documentation in the case of a distributed TOE are defined in section B.4.1.1.

5.3.1 Operational User Guidance (AGD_OPE.1)

585 The evaluator performs the CEM work units associated with the AGD_OPE.1 SAR. Specific requirements and EAs on the guidance documentation are identified (where relevant) in the individual EAs for each SFR.

Deleted: checks

Deleted: user

Deleted: Evaluation Activities

586 In addition, the evaluator performs the EAs specified below.

Deleted: , and for some other SARs (e.g. ALC_CMC.1)...

Deleted: 3.3.1.1 →

5.3.1.1 Evaluation Activity:

587 The evaluator shall ensure the Operational guidance documentation is distributed to administrators and users (as appropriate) as part of the TOE, so that there is a reasonable guarantee that administrators and users are aware of the existence and role of the documentation in establishing and maintaining the evaluated configuration.

Deleted: check

Deleted: requirements below are met by the

Deleted: ¶

Guidance documentation shall be

5.3.1.2 Evaluation Activity

588 The evaluator shall ensure that the Operational guidance is provided for every Operational Environment that the product supports as claimed in the Security Target and shall adequately address all platforms claimed for the TOE in the Security Target.

Deleted: Guidance documentation must be

5.3.1.3 Evaluation Activity

589 The evaluator shall ensure that the Operational guidance contains instructions for configuring any cryptographic engine associated with the evaluated configuration of the TOE. It shall provide a warning to the administrator that use of other cryptographic engines was not evaluated nor tested during the CC evaluation of the TOE.

Deleted: must

Deleted: <#>The contents of the guidance documentation will be verified by the Evaluation Activities defined below and as appropriate for each individual SFR in section 2 above. ¶
<#>In addition to SFR-related Evaluation Activities, the following information is also required. ¶
<#>The guidance documentation shall contain

5.3.1.4 Evaluation Activity

590 The evaluator shall ensure the Operational guidance makes it clear to an administrator which security functionality and interfaces have been assessed and tested by the EAs.

Deleted: ¶

5.3.1.5 Evaluation Activity

591 In addition the evaluator shall ensure that the following requirements are also met.

- a) The guidance documentation shall contain instructions for configuring any cryptographic engine associated with the evaluated configuration of the TOE. It shall provide a warning to the administrator that use of

Deleted: <object><object><object>

Evaluation Activities for SARs

Deleted: <object>

other cryptographic engines was not evaluated nor tested during the CC evaluation of the TOE.

- b) The documentation must describe the process for verifying updates to the TOE by verifying a digital signature. The evaluator shall verify that this process includes the following steps:
 - 1) Instructions for obtaining the update itself. This should include instructions for making the update accessible to the TOE (e.g., placement in a specific directory).
 - 2) Instructions for initiating the update process, as well as discerning whether the process was successful or unsuccessful. This includes instructions that describe at least one method of validating the hash/digital signature.
- c) The TOE will likely contain security functionality that does not fall in the scope of evaluation under this cPP. The guidance documentation shall make it clear to an administrator which security functionality is covered by the Evaluation Activities.

Deleted: generation

Deleted:

5.3.2 Preparative Procedures (AGD_PRE.1)

592 The evaluator performs the CEM work units associated with the AGD_PRE.1 SAR. Specific requirements and EAs on the preparative documentation are identified (and where relevant are captured in the Guidance Documentation portions of the EAs) in the individual EAs for each SFR.

Deleted: As for

Deleted: guidance documentation, specific

Deleted: checks

Deleted: procedures

593 Preparative procedures are distributed to administrators and users (as appropriate) as part of the TOE, so that there is a reasonable guarantee that administrators and users are aware of the existence and role of the documentation in establishing and maintaining the evaluated configuration.

Deleted: Evaluation Activities

Deleted: 3.3.2.1 Evaluation Activity:

The evaluator shall check the requirements below are met by the preparative procedures.

The contents of the preparative procedures will be verified by the Evaluation Activities defined below and as appropriate for each individual SFR in section 2 above.

594 In addition, the evaluator performs the EAs specified below.

5.3.2.1 Evaluation Activity:

Deleted: shall be

595 The evaluator shall examine the Preparative procedures to ensure they include a description of how the administrator verifies that the operational environment can fulfil its role to support the security functionality (including the requirements of the Security Objectives for the Operational Environment specified in the Security Target).

Deleted: <#>The contents of the preparative procedures will be verified by the Evaluation Activities defined below and as appropriate for each individual SFR in section 2 above.

<#>In addition to SFR-related Evaluation Activities,

596 The documentation should be in an informal style and should be written with sufficient detail and explanation that they can be understood and used by the target audience (which will typically include IT staff who have general IT experience but not necessarily experience with the TOE product itself).

Deleted: following information is also required.

Deleted: must

Deleted: administrator

Deleted: The

5.3.2.2 Evaluation Activity

Deleted: Section Break (Next Page)

597 The evaluator shall examine the Preparative procedures to ensure they are provided for every Operational Environment that the product supports as

Deleted: must be

Deleted:

Deleted: <object><object><object>

Evaluation Activities for SARs

claimed in the Security Target and shall adequately address all platforms claimed for the TOE in the Security Target.

Deleted: <object>

Deleted: must

5.3.2.3 Evaluation Activity

598 The evaluator shall examine the preparative procedures to ensure they include instructions to successfully install the TSF in each Operational Environment.

Deleted: must

Deleted: ¶

Deleted: ; and

5.3.2.4 Evaluation Activity

599 The evaluator shall examine the preparative procedures to ensure they include instructions to manage the security of the TSF as a product and as a component of the larger operational environment.

Deleted: ; and

5.3.2.5 Evaluation Activity

600 In addition the evaluator shall ensure that the following requirements are also met.

601 The preparative procedures must

- a) include instructions to provide a protected administrative capability, and
- b) identify TOE passwords that have default values associated with them and instructions shall be provided for how these can be changed.

Deleted: .

5.4 ALC: Life-cycle Support

5.4.1 Labelling of the TOE (ALC CMC.1)

602 When evaluating that the TOE has been provided and is labelled with a unique reference, the evaluator performs the work units as presented in the CEM.

5.4.2 TOE CM coverage (ALC CMS.1)

603 When evaluating the developer's coverage of the TOE in their CM system, the evaluator performs the work units as presented in the CEM.

5.5 ATE: Tests

5.5.1 Independent Testing – Conformance (ATE_IND.1)

Deleted: 3.4.1 →

604 The focus of the testing is to confirm that the requirements specified in the SFRs are being met. Additionally, testing is performed to confirm the functionality described in the TSS, as well as the dependencies on the Operational guidance documentation is accurate.

Deleted: Testing

Deleted: . The focus of the testing is to confirm that the requirements specified in the SFRs are being met

605 The evaluator performs the CEM work units associated with the ATE_IND.1 SAR. Specific testing requirements and EAs are captured for each SFR in Sections 2, 3 and 4.

Deleted: <object><object><object>

Evaluation Activities for SARs

606 The evaluator should consult Appendix B when determining the appropriate strategy for testing multiple variations or models of the TOE that may be under evaluation.

607 Note that additional Evaluation Activities relating to evaluator testing in the case of a distributed TOE are defined in section B.4.3.1.

5.6 AVA: Vulnerability Assessment

5.6.1 Vulnerability Survey (AVA_VAN.1)

608 While vulnerability analysis is inherently a subjective activity, a minimum level of analysis can be defined and some measure of objectivity and repeatability (or at least comparability) can be imposed on the vulnerability analysis process. In order to achieve such objectivity and repeatability it is important that the evaluator follows a set of well-defined activities, and documents their findings so others can follow their arguments and come to the same conclusions as the evaluator. While this does not guarantee that different evaluation facilities will identify exactly the same type of vulnerabilities or come to exactly the same conclusions, the approach defines the minimum level of analysis and the scope of that analysis, and provides Certification Bodies a measure of assurance that the minimum level of analysis is being performed by the evaluation facilities.

609 In order to meet these goals some refinement of the AVA_VAN.1 CEM work units is needed. The following table indicates, for each work unit in AVA_VAN.1, whether the CEM work unit is to be performed as written, or if it has been clarified by an Evaluation Activity. If clarification has been provided, a reference to this clarification is provided in the table.

610

CEM AVA_VAN.1 Work Units	Evaluation Activities
AVA_VAN.1-1 The evaluator shall examine the TOE to determine that the test configuration is consistent with the configuration under evaluation as specified in the ST.	<p>The evaluator shall perform the CEM activity as specified.</p> <p>The calibration of test resources specified in paragraph 1418 of the CEM applies to the tools listed in Section A.1.4.</p>
AVA_VAN.1-2 The evaluator shall examine the TOE to determine that it has been installed properly and is in a known state	The evaluator shall perform the CEM activity as specified.
AVA_VAN.1-3 The evaluator shall examine sources of information publicly available to identify potential vulnerabilities in the TOE.	Replace CEM work unit with activities outlined in Section A.1.

Deleted: <object>

Deleted: B

Deleted: <#>The SFR-related Evaluation Activities in the SD identify the specific testing activities necessary to verify compliance with the SFRs. The tests identified in these other Evaluation Activities constitute a sufficient set of tests for the purposes of meeting ATE_IND.1.2E. It is important to note that while the Evaluation Activities identify the testing that is necessary to be performed, the evaluator is responsible for ensuring that the interfaces are adequately tested for the security functionality specified for each SFR.

<#>3.4.1.1 –Evaluation Activity:

<#>The evaluator shall examine the TOE to determine that the test configuration is consistent with the configuration under evaluation as specified in the ST.

<#>The evaluator shall examine the TOE to determine that it has been installed properly and is in a known state.

<#>The evaluator shall prepare a test plan that covers all of the testing actions for ATE_IND.1 in the CEM and in the SFR-related Evaluation Activities. While it is not necessary to have one test case per test listed in an Evaluation Activity, the evaluator must show in the test plan that each applicable testing requirement in the

Deleted: 3.5.1 →

Deleted: 3.5.1.1 –Evaluation Activity: ... [56]

Moved down [200]: Examples of such information could be entropy analysis, or description of a cryptographic key

Deleted:] Appendix D. References ... [57]

Moved down [201]: –References

Moved down [202]: [FWcPP] –collaborative Protection Profile for Stateful Traffic

Moved down [203]: [NDcPP] –collaborative Protection Profile for Network

Deleted: Version 1.0, 27 February 2015

Deleted: Version 1.0, 27 February 2015 ... [58]

Moved down [204]: Vulnerability Analysis

Deleted: Introduction As noted in [VAWP], while

Deleted: his

Deleted: such that

Deleted: his

Deleted: conclusion

Deleted: in his report

Deleted: schemes

Deleted: that

Deleted: <#>This supplemental guidance provides the information described in [VAWP] for the Network. [59]

Deleted: <object><object><object>

<p><u>AVA VAN.1-4 The evaluator shall record in the ETR the identified potential vulnerabilities that are candidates for testing and applicable to the TOE in its operational environment.</u></p>	<p><u>Replace the CEM work unit with the analysis activities on the list of potential vulnerabilities in Section A.1, and documentation as specified in Section A.3.</u></p>
<p><u>AVA VAN.1-5 The evaluator shall devise penetration tests, based on the independent search for potential vulnerabilities.</u></p>	<p><u>Replace the CEM work unit with the activities specified in Section A.2.</u></p>
<p><u>AVA VAN.1-6 The evaluator shall produce penetration test documentation for the tests based on the list of potential vulnerabilities in sufficient detail to enable the tests to be repeatable. The test documentation shall include:</u></p> <ul style="list-style-type: none"> <u>a) identification of the potential vulnerability the TOE is being tested for;</u> <u>b) instructions to connect and setup all required test equipment as required to conduct the penetration test;</u> <u>c) instructions to establish all penetration test prerequisite initial conditions;</u> <u>d) instructions to stimulate the TSF;</u> <u>e) instructions for observing the behaviour of the TSF;</u> <u>f) descriptions of all expected results and the necessary analysis to be performed on the observed behaviour for comparison against expected results;</u> <u>g) instructions to conclude the test and establish the necessary post-test state for the TOE.</u> 	<p><u>The CEM work unit is captured in Section A.3; there are no substantive differences.</u></p>
<p><u>AVA VAN.1-7 The evaluator shall conduct penetration testing.</u></p>	<p><u>The evaluator shall perform the CEM activity as specified. See Section A.2, paragraph 642 for guidance related to attack potential for confirmed flaws.</u></p>
<p><u>AVA VAN.1-8 The evaluator shall record the actual results of the penetration tests.</u></p>	<p><u>The evaluator shall perform the CEM activity as specified.</u></p>

Deleted:

Evaluation Activities for SARs

Deleted: <object>

<p><u>AVA VAN.1-9</u> The evaluator <i>shall report</i> in the ETR the evaluator penetration testing effort, outlining the testing approach, configuration, depth and results.</p>	<p>Replace the CEM work unit with the reporting called for in Section A.3.</p>
<p><u>AVA VAN.1-10</u> The evaluator <i>shall examine</i> the results of all penetration testing to determine that the TOE, in its operational environment, is resistant to an attacker possessing a Basic attack potential.</p>	<p>This work unit is not applicable for Type 1 and Type 2 flaws (as defined in Section A.1), as inclusion in this Supporting Document by the iTC makes any confirmed vulnerabilities stemming from these flaws subject to an attacker possessing a Basic attack potential. This work unit is replaced for Type 3 and Type 4 flaws by the activities defined in Section A.2, paragraph 642.</p>
<p><u>AVA VAN.1-11</u> The evaluator <i>shall report</i> in the ETR all exploitable vulnerabilities and residual vulnerabilities, detailing for each:</p> <ul style="list-style-type: none"> a) its source (e.g. CEM activity being undertaken when it was conceived, known to the evaluator, read in a publication); b) the SFR(s) not met; c) a description; d) whether it is exploitable in its operational environment or not (i.e. exploitable or residual); e) the amount of time, level of expertise, level of knowledge of the TOE, level of opportunity and the equipment required to perform the identified vulnerabilities, and the corresponding values using the tables 3 and 4 of Annex B.4. 	<p>Replace the CEM work unit with the reporting called for in Section A.3.</p>

Table 2: Mapping of AVA VAN.1 CEM Work Units to Evaluation Activities

611 Because of the level of detail required for the evaluation activities, the bulk of the instructions are contained in Appendix A, while an “outline” of the assurance activity is provided below.

Deleted: team

Deleted: <object><object><object>

Vulnerability Analysis

5.6.1.1 Evaluation Activity (Documentation):

612 In addition to the activities specified by the CEM in accordance with Table 2, the evaluator shall perform the following activities.

613 The evaluator shall examine the documentation outlined below provided by the developer, to confirm that it contains all required information. This documentation is in addition to the documentation already required to be supplied in response to the EAs listed previously.

614 The developer shall provide documentation identifying the list of software and hardware components⁷ that compose the TOE. Hardware components should identify at a minimum the processors used by the TOE. Software components include applications, the operating system and other major components that are independently identifiable and reusable (outside the TOE) such as a web server and protocol or cryptographic libraries. This additional documentation is merely a list of the name and version number of the components, and will be used by the evaluators in formulating hypotheses during their analysis.

615 If the TOE is a distributed TOE then the developer shall provide:

- a) documentation describing the allocation of requirements between distributed TOE components as in [NDcPP, 3.4]
- b) a mapping of the auditable events recorded by each distributed TOE component as in [NDcPP, 6.3.3]
- c) additional information in the Preparative Procedures as identified in the refinement of AGD_PRE.1 in additional information in the Preparative Procedures as identified in 3.5.1.2 and 3.6.1.2.

5.6.1.2 Evaluation Activity:

616 The evaluator formulates hypotheses in accordance with process defined in Appendix A. The evaluator documents the flaw hypotheses generated for the TOE in the report in accordance with the guidelines in Appendix A.3. The evaluator shall perform vulnerability analysis in accordance with Appendix A.2. The results of the analysis shall be documented in the report according to Appendix A.3.

⁷In this sub-section the term “components” refers to parts that make up the TOE. It is therefore distinguished from the term “distributed TOE components”, which refers to the parts of a TOE that are present in one physical part of a distributed TOE. Each distributed TOE component will therefore generally include a number of the hardware and software components that are referred to in this sub-section: for example, each distributed TOE component will generally include hardware components such as processors and software components such as an operating system and libraries.

Deleted: <object>

Deleted: TOE

Deleted: .

Deleted: that called out in the cPP evaluation activities and other SARs.[¶]

Moved up [2]: ¶
For the

Deleted: ND cPP, the additional

Deleted: will at a minimum include

Deleted: components

Deleted: comprise

Deleted: apply to all systems claimed in the ST, and

Deleted: ¶

Deleted: network hardware and

Deleted: underlying

Deleted: environment/operating

Deleted: , plus

Deleted: , libraries such as

Deleted: , etc

Deleted: <object><object><object>

Required Supplementary Information

6 Required Supplementary Information

617 This Supporting Document refers in various places to the possibility that 'required supplementary information' may need to be supplied as part of the deliverables for an evaluation. This term is intended to describe information that is not necessarily included in the Security Target or operational guidance, and that may not necessarily be public. Examples of such information could be entropy analysis, or description of a cryptographic key management architecture used in (or in support of) the TOE. The requirement for any such supplementary information will be identified in the relevant cPP.

618 The cPPs associated with this SD require an entropy analysis as described in [NDcPP, Appendix D].

Moved (insertion) [200]

Deleted: <object><object><object>

References

7 References

[CC1] Common Criteria for Information Technology Security Evaluation, Part 1: Introduction and General Model
CCMB-2012-09-001, Version 3.1 Revision 4, September 2012

[CC2] Common Criteria for Information Technology Security Evaluation, Part 2: Security Functional Components
CCMB-2012-09-002, Version 3.1 Revision 4, September 2012

[CC3] Common Criteria for Information Technology Security Evaluation, Part 3: Security Assurance Components
CCMB-2012-09-003, Version 3.1 Revision 4, September 2012

[CEM] Common Methodology for Information Technology Security Evaluation, Evaluation Methodology
CCMB-2012-09-004, Version 3.1, Revision 4, September 2012

[FIPS 140-2] FIPS PUB 140-2, Security Requirements for cryptographic modules, May 25 2001 with change notices (12-03-2002)

[FIPS 186-4] FIPS PUB 186-4, Digital Signature Standard (DSS), July 2013

[FWcPP] collaborative Protection Profile for Stateful Traffic Filter Firewalls
Version 2.0, May 2017

[NDcPP] collaborative Protection Profile for Network Devices, Version 2.0, 5 May 2017

[NIST SP800-56A] NIST Special Publication SP800-56B Revision 2: Recommendation for Pair-Wise Key Establishment Schemes Using Discrete Logarithm Cryptography, May 2013

[NIST SP800-56B] NIST Special Publication SP800-56B Revision 1: Recommendation for Pair-Wise Key-Establishment Schemes Using Integer Factorization Cryptography, March 2014

Moved (insertion) [201]

Moved (insertion) [202]

Moved (insertion) [203]

Deleted: <object><object><object>

References


[\[NIST SP800-90A\]](#) NIST Special Publication SP800-90A Deterministic Random Bit Generator Validation System (DRBGVS), October 29 2015

[\[SHAVS\]](#) The Secure Hash Algorithm Validation System (SHAVS), Updated: May 21, 2014

Deleted: <object><object><object>

References

Appendices



Deleted: <object><object><object>

Vulnerability Analysis

A. Vulnerability Analysis

A.1 Sources of vulnerability information

619 CEM Work Unit AVA VAN.1-3 has been supplemented in this Supporting Document to provide a better-defined set of flaws to investigate and procedures to follow based on this particular technology. Terminology used is based on the flaw hypothesis methodology, where the evaluation team hypothesizes flaws and then either proves or disproves those flaws (a flaw is equivalent to a “potential vulnerability” as used in the CEM). Flaws are categorized into four “types” depending on how they are formulated:

1. A list of flaw hypotheses applicable to the technology described by the cPP (in this case, a network device) derived from public sources as documented in Section A.1.1 – this fixed set has been agreed by the iTC. Additionally, this will be supplemented with entries for a set of public sources (as indicated below) that are directly applicable to the TOE or its identified components (as defined by the process in Section A.1.1 below); this is to ensure that the evaluators include in their assessment applicable entries that have been discovered since the cPP was published;
2. A list of flaw hypotheses listed in this document that are derived from lessons learned specific to that technology and other iTC input (that might be derived from other open sources and vulnerability databases, for example) as documented in Section A.1.2;
3. A list of flaw hypotheses derived from information available to the evaluators; this includes the baseline evidence provided by the developer described in this Supporting Document (documentation associated with EAs, documentation described in Section 5.6.1.2, documentation described in Section 6), as well as other information (public and/or based on evaluator experience) as documented in Section A.1.3; and
4. A list of flaw hypotheses that are generated through the use of TC-defined tools (e.g., nmap, fuzz testers) and their application as specified in section A.1.4.

A.1.1 Type 1 Hypotheses – Public Vulnerability-Based

620 The list of public sources of vulnerability information selected by the iTC is given in Section A.4.

621 The evaluators shall perform a search on the sources listed in Section A.4 to determine a list of potential flaw hypotheses that are more recent than the publication date of the cPP, and those that are specific to the TOE and its components as specified by the additional documentation mentioned above. Any duplicates – either in a specific entry, or in the flaw hypothesis that is generated from an entry from the same or a different source – can be noted and removed from consideration by the evaluation team.

622 The search criteria to be used when searching the sources published after the publication date of the cPP shall include:

Moved (insertion) [204]

Deleted: The method to be used in the vulnerability analysis for cPPs as outlined in [VAWP]

Deleted: .

Deleted: drawn from

Deleted: sources (

Deleted:):

Deleted: Common Vulnerability Enumeration (CVE) or similar...

Deleted: —there is a

Deleted: in the cPP/supplemental guidance that are

Deleted: to

Deleted: CVEs or

Deleted: those same

Deleted: . The

Deleted: will also

Deleted: in those sources CVEs

Deleted: issued

Deleted: the cPP/supplemental guidance

Deleted:); and

Deleted: based on the SFRs and

Deleted: vendor

Deleted: the cPP/supplemental guidance (includes section...

Deleted: A.2), also including referenced

Deleted: resources.

Deleted: may also be included.

Deleted:

Deleted: Database

Deleted: Section A.6 contains the

Deleted: sources, and entries

Deleted: those sources to be considered for flaw hypotheses of type 1 above. In order to supplement this list, the

Deleted: also

Deleted: those

Deleted: A.6

Deleted: It should be noted that the list in A.6 applies to all TOEs and indicate a type of flaw that is to be considered, which the evaluators use the search criteria (identified below) to collect the list of entries that apply *specifically* to the TOE. See the [VAWP] appendix for the analysis associated with CVE entries as an example.

Deleted: ~~~~~Section Break (Next Page)~~~~~

Deleted: ¶

Deleted: <object><object><object>

Vulnerability Analysis

- The terms “router” and “switch” (or similar generic term describing the device type of the TOE)
- The following protocols: TCP
- Any protocols not listed above supported (through an SFR) by the TOE (these will include at least one of the remote management protocols (IPsec, TLS, SSH))
- The TOE name (including appropriate model information as appropriate)

623 As part of type 1 flaw hypothesis generation for the specific components of the TOE, the evaluator shall also search the component manufacturer’s websites to determine if flaw hypotheses can be generated on this basis (for instance, if security patches have been released for the version of the component being evaluated, the subject of those patches may form the basis for a flaw hypothesis).

A.1.2 Type 2 Hypotheses – iTC-Sourced

624 Section A.5 contains the list of flaw hypothesis generated by the iTC for this technology that must be considered by the evaluation team as flaw hypotheses in performing the vulnerability assessment.

625 If the evaluators discover a Type 3 or Type 4 flaw that they believe should be considered as a Type 2 flaw in future versions of this cPP, they should work with their Certification Body to determine the appropriate means of submitting the flaw for consideration by the iTC.

A.1.3 Type 3 Hypotheses – Evaluation-Team-Generated

626 Type 3 flaws are formulated by the evaluator based on information presented by the product (through on-line help, product documentation and user guides, etc.) and product behaviour during the (functional) testing activities. The evaluator is also free to formulate flaws that are based on material that is not part of the baseline evidence (e.g., information gleaned from an Internet mailing list, or reading interface documentation on interfaces not included in the set provided by the developer), although such activities have the potential to vary significantly based upon the product and evaluation facility performing the analysis.

627 If the evaluators discover a Type 3 flaw that they believe should be considered as a Type 2 flaw in future versions of this cPP, they should work with their Certification Body to determine the appropriate means of submitting the flaw for consideration by the iTC.

A.1.4 Type 4 Hypotheses – Tool-Generated

628 The evaluator shall perform the following activities to generate type 4 flaw hypotheses:

- Fuzz testing
 - Examine effects of sending:

Deleted: Generated

Deleted: A.7

Deleted: cPP. Should

Deleted: type

Deleted: type

Deleted: for inclusion in Section A.7

Deleted: will submit a non-proprietary write-up

Deleted:

Deleted:

Deleted: With respect to type

Deleted: ,

Deleted: is free to formulate flaws that are

Deleted:

Deleted: <object><object><object>

Vulnerability Analysis

- mutated packets carrying each 'Type' and 'Code' value that is undefined in the relevant RFC for each of ICMPv4 (RFC 792) and ICMPv6 (RFC 4443)
- mutated packets carrying each 'Transport Layer Protocol' value that is undefined in the respective RFC for IPv4 (RFC 791) IPv6 (RFC 2460) should also be covered if it is supported and claimed by the TOE.

Since none of these packets will belong to an allowed session, the packets should not be processed by the TOE, and the TOE should not be adversely affected by this traffic. Any results that are unexpected (e.g., core dumps) are candidates for a flaw hypothesis.

- Mutation fuzz testing of the remaining fields in the required protocol headers. This testing requires sending mutations of well-formed packets that have both carefully chosen and random values inserted into each header field in turn (i.e. testing is to include both carefully chosen and random insertion test cases). The original well-formed packets would be accepted as part of a normal existing communication stream and may still be accepted as valid packets when subject to the carefully chosen mutations (the individual packet alone would be valid although its contents may not be valid in the context of preceding and/or following packets), but will often not be valid packets when random values are inserted into fields. The carefully chosen values should include semantically significant values that can be determined from the type of the data that the field represents, such as values indicating positive and negative integers, boundary conditions, invalid binary combinations (e.g. for flag sets with dependencies between bits), and missing start or end values. Randomly chosen values may not result in well-formed packets, but are included nonetheless to see whether they can lead to the device entering an insecure state. Any results that are unexpected (e.g., core dumps) are candidates for a flaw hypothesis.

629 The iTC has not identified a specific tool to be used in accomplishing the above flaw hypothesis generation activity, so any tool used by the evaluation team is acceptable. The evaluation team shall record in the test report the name, version, parameters, and results of all test tools used for this this activity.

630 If the evaluators discover a Type 4 flaw that they believe should be considered as a Type 2 flaw in future versions of this CPP, they should work with their Certification Body to determine the appropriate means of submitting the flaw for consideration by the iTC.

Deleted: ¶

Deleted:

Deleted: <object><object><object>

Vulnerability Analysis

A.2 Process for Evaluator Vulnerability Analysis

631 As flaw hypotheses are generated from the activities described above, the evaluation team will disposition them; that is, attempt to prove, disprove, or determine the non-applicability of the hypotheses. This process is as follows.

Deleted: , as outlined in the [VAWP],

632 The evaluator will refine each flaw hypothesis for the TOE and attempt to disprove it using the information provided by the developer or through penetration testing. During this process, the evaluator is free to interact with the developer to determine if the flaw exists, including requests to the developer for additional evidence (e.g., detailed design information, consultation with engineering staff); however, the CB should be included in all of these discussions. Should the developer object to the information being requested as being not compatible with the overall level of the evaluation activity/cPP and cannot provide evidence otherwise that the flaw is disproved, the evaluator prepares an appropriate set of materials as follows:

Deleted: without consulting the Certification Body (CB) ...

Deleted: 1

Deleted: copied on

Deleted: requests

Deleted:

1. the source documents used in formulating the hypothesis, and why it represents a potential compromise against a specific TOE function;

Deleted:

2. an argument why the flaw hypothesis could not be proven or disproved by the evidence provided so far;

Deleted: and

3. the type of information required to investigate the flaw hypothesis further.

Deleted:

633 The Certification Body (CB) will then either approve or disapprove the request for additional information. If approved, the developer provides the requested evidence to disprove the flaw hypothesis (or, of course, acknowledge the flaw).

634 For each hypothesis, the evaluator will note whether the flaw hypothesis has been successfully disproved, successfully proven to have identified a flaw, or requires further investigation. It is important to have the results documented as outlined in Section A.3 below.

Deleted: to be performed as part of the penetration testing effort. Again this can be dealt with in terms of meetings or written charts.

635 If the evaluator finds a flaw, the evaluator will report these flaws to the developer. All reported flaws must be addressed as follows.

Deleted: Should

Deleted: be found (either through the developer agreeing with the documentation analysis, or through the penetration effort),

636 If the developer confirms that the flaw exists and that it is exploitable at Basic Attack Potential, then a change is made by the developer, and the resulting resolution is agreed by the evaluator and noted as part of the evaluation report.

Deleted: vendor

Deleted: confirmed

637 If the developer, the evaluator, and the CB agree that the flaw is exploitable only above Basic Attack Potential and does not require resolution for any other reason, then no change is made and the flaw is noted as a residual vulnerability in the CB-internal report (ETR).

Deleted: should

Deleted: should be

638 If the developer and evaluator agree that the flaw is exploitable only above Basic Attack Potential, but it is deemed critical to fix because of technology-specific or cPP-specific aspects such as typical use cases or operational

Deleted: to

Deleted: <object><object><object>

Vulnerability Analysis

environments, then a change is made by the developer, and the resulting resolution is agreed by the evaluator and noted as part of the evaluation report.

639 Disagreements between evaluator and developer regarding questions of the existence of a flaw, its attack potential, or whether it should be deemed critical to fix are resolved by the CB.

640 Any testing performed by the evaluator shall be documented in the test report as outlined in Section A.3 below.

641 As indicated in Section A.3, the public statement with respect to vulnerability analysis that is performed on TOEs conformant to the cPP is constrained to coverage of flaws associated with Types 1 and 2 (defined in Section A.1) flaw hypotheses only. The fact that the iTC generates these candidate hypotheses indicates these must be addressed.

642 For flaws of Types 3 and 4, each CB will be responsible for determining what constitutes Basic Attack Potential for the purposes of determining whether a flaw is exploitable in the TOE's environment. The determination criteria shall be documented in the CB-internal report as specified in Section A.3. As this is a per-CB activity, no public claims are made with respect to the resistance of a particular TOE against flaws of Types 3 and 4; rather, the claim is that the activities outlined in this appendix were carried out, and the evaluation team and CB agreed that any residual vulnerabilities are not exploitable by an attacker with Basic Attack Potential.

A.3 Reporting

643 The evaluators shall produce two reports on the testing effort; one that is public-facing (that is, included in the non-proprietary evaluation report, which is a subset of the Evaluation Technical Report (ETR)) and the complete ETR that is delivered to the overseeing CB.

644 The public-facing report contains:

- The flaw identifiers returned when the procedures for searching public sources were followed according to instructions in the Supporting Document per Section A.1.1;
- A statement that the evaluators have examined the Type 1 flaw hypotheses specified in this Supporting Document in section A.1.1 (i.e. the flaws listed in the previous bullet) and the Type 2 flaw hypotheses specified in this Supporting Document by the iTC in Section A.1.2;

645 A statement that the evaluation team developed Types 3 and 4 flaw hypotheses in accordance with Sections A.1.3, A.1.4, and A.2, and that no residual vulnerabilities exist that are exploitable by attackers with Basic Attack Potential as defined by the CB in accordance with the guidance in the CEM. It should be noted that this is just a statement about the "fact of" Types 3 and 4 flaw hypotheses being developed, and that no specifics about the number of

Deleted: A.5,

Deleted: A.3

Deleted: because they are exploitable by an attacker with Basic Attack Potential

Deleted: determine

Deleted: exploited

Deleted:) and one

Deleted: is just a

Deleted: CVEs applicable to the product (Section A.6 plus additional CVE-based

Deleted: Section Break (Next Page)

Deleted: hypotheses generated by the evaluators per Section A.3.1) and those specified in the cPP by the iTC and contained in Section A.7 (this encompasses hypotheses of Types 1 and 2 mentioned above). Additionally, there is a

Deleted: Section A.3

Deleted: No other information is provided in the public-facing report.

Deleted: ¶
For

Deleted: <object><object><object>

Vulnerability Analysis

flaws, the flaws themselves, or the analysis pertaining to those flaws will be included in the public-facing report.

646 No other information is provided in the public-facing report.

647 The internal CB report contains, in addition to the information in the public-facing report:

- a list of all of the flaw hypotheses generated (cf. AVA VAN.1-4);
- the evaluator penetration testing effort, outlining the testing approach, configuration, depth and results (cf. AVA VAN.1-9);
- all documentation used to generate the flaw hypotheses (in identifying the documentation used in coming up with the flaw hypotheses, the evaluation team must characterize the documentation so that a reader can determine whether it is strictly required by this Supporting Document, and the nature of the documentation (design information, developer engineering notebooks, etc.));
- the evaluator shall report all exploitable vulnerabilities and residual vulnerabilities, detailing for each:
 - its source (e.g. CEM activity being undertaken when it was conceived, known to the evaluator, read in a publication);
 - the SFR(s) not met;
 - a description;
 - whether it is exploitable in its operational environment or not (i.e. exploitable or residual).
 - the amount of time, level of expertise, level of knowledge of the TOE, level of opportunity and the equipment required to perform the identified vulnerabilities (cf. AVA VAN.1-11);
- how each flaw hypothesis was resolved (this includes whether the original flaw hypothesis was confirmed or disproved, and any analysis relating to whether a residual vulnerability is exploitable by an attacker with Basic Attack Potential) (cf. AVA VAN1-10); and
- in the case that actual testing was performed in the investigation (either as part of flaw hypothesis generation using tools specified by the iTC in Section A.1.4, or in proving/disproving a particular flaw) the steps followed in setting up the TOE (and any required test equipment); executing the test; post-test procedures; and the actual results (to a level of detail that allow repetition of the test, including the following:
 - identification of the potential vulnerability the TOE is being tested for;

Deleted: (

Deleted:)

Deleted: , we suggest that

Deleted: evaluation team must

Deleted: ;

Deleted: ; and

Deleted:). In identifying the documentation used in coming up with the flaw hypotheses, the evaluation team must characterize the documentation so that a reader can determine whether it is strictly required by the support documents/evaluation activities (that is, it forms part of the baseline evidence), and the nature of the documentation (design information, developer engineering notebooks, etc.). At the conclusion of the evaluation, a set of interested CBs (subject to negotiation between all parties concerned) and perhaps other members of the iTC may review this information and make a determination of the impacts to supporting documents for future evaluations against that cPP (for example, if a large number of the flaw hypotheses were generated based on a certain type of documentation, then additional documentation in this area may be required by the iTC for future evaluations).

Deleted: <object><object><object>

Vulnerability Analysis

- instructions to connect and setup all required test equipment as required to conduct the penetration test;
- instructions to establish all penetration test prerequisite initial conditions;
- instructions to stimulate the TSF;
- instructions for observing the behaviour of the TSF;
- descriptions of all expected results and the necessary analysis to be performed on the observed behaviour for comparison against expected results;
- instructions to conclude the test and establish the necessary post-test state for the TOE. (cf. AVA_VAN.1-6, AVA_VAN.1-8).

A.4 Public Vulnerability Sources

648 The following sources of public vulnerabilities are sources for the iTC to consider in both formulating the specific list of flaws to be investigated by the evaluators, as well as to reference in directing the evaluators to perform keyword searches during the evaluation of a specific TOE.

- NIST National Vulnerabilities Database (can be used to access CVE and US-CERT databases identified below):
<https://web.nvd.nist.gov/view/vuln/search>
- Common Vulnerabilities and Exposures:
<http://cve.mitre.org/cve/>
<https://www.cvedetails.com/vulnerability-search.php>
- US-CERT:
<http://www.kb.cert.org/vuls/html/search>
- Exploit / Vulnerability Search Engine:
www.exploitsearch.net
- SecuriTeam Exploit Search:
www.securiteam.com
- Tenable Network Security:
<http://nessus.org/plugins/index.php?view=search>
- Tipping Point Zero Day Initiative:
<http://www.zerodayinitiative.com/advisories>
- Offensive Security Exploit Database:
<https://www.exploit-db.com/>
- Rapid7 Vulnerability Database:
<https://www.rapid7.com/db/vulnerabilities>

Deleted: Entries for Flaw Hypotheses

Deleted: 421 No entries are currently defined for this list

Deleted: <object><object><object>

Vulnerability Analysis

A.5 Additional Flaw Hypotheses

[649](#) No entries are currently defined for this list.

Deleted: 422

Deleted: **iTC Activities – cPP and Supporting Document Maintenance**

423—As indicated in the preceding sections, the iTC plays a key role in determining the scope of the vulnerability analysis with respect to what is publically reported. This section details the activities that the iTC must perform in order to ensure that flaws to be investigated by the evaluation team are identified, are compatible with the overall level of assurance of a TOE conformant to this PP, and cover the areas of concern by the iTC for this technology.

424—There are four activities (and associated outputs) that need to be accomplished by the iTC:

The iTC must determine what additional documentation is necessary for the evaluation team to examine in the course of their vulnerability

assessment. The cPP and associated Supporting Document detail a set of information that must be available (for example, information called for by the TSS in the various evaluation activities in the Supporting Document). If the iTC feels that additional documentation not already covered (or only partially covered) in the cPP or the Supporting Document is necessary, they define that information and include it in section A.2.

The iTC must determine what public vulnerability databases are to be used as the basis for Type 1 (Section A.3) hypotheses, and what entries in these databases apply. In performing this activities, the iTC first agrees upon the sources to be used; for instance, the Common Vulnerability Enumeration (CVE) list. Note that it is not expected that this be an exhaustive list; only that it is a list that the iTC feels gives good representation for vulnerabilities with respect to the technology type.

Having identified the sources, for each source the iTC defines criteria for selecting entries in the list. The lists and criteria should be identified in section A.3.1 so that evaluators can use the same sources and criteria at evaluation time to select entries that were made after the cPP was published. For each entry that meets the criteria, the iTC determines whether or not to include it in the list to be considered by the evaluation team. This will likely necessitate the creation of some criteria by which to judge an entry that is agreed to by the iTC. For instance, CVEs that would generate flaw hypotheses related to buffer overflows would probably be rejected as a generic flaw hypothesis.

The output of this activity would be a list of entries that the evaluation team would consider as applicable in generating flaw hypotheses. See the appendix to the [VAWP] for an example of this analysis activity as applied to firewalls using the CVE database.

The iTC must consider if there are any technology-specific vulnerabilities or types of vulnerabilities that the evaluators should consider that are not contained in section A.6. This could be based on previous evaluations against the cPP, experience of the iTC members, or other factors. This set of vulnerabilities (Type 2) would be captured in Section A.7 and would then need to be considered by the evaluation team. It is likely that there will be few or no entries identified for this type until more experience is gained with the cPP.

The final activity the iTC must perform is the identification of

Deleted: *<object><object><object>*

Network Device Equivalency Considerations

Deleted: <object>

B. Network Device Equivalency Considerations

B.1 Introduction

650 This appendix provides a foundation for evaluators to determine whether a developer's request for equivalency of products for different models wishing to claim conformance to the Network Device collaborative Protection Profiles, is allowed.

Deleted: vendor's

Deleted: .

2 For the purpose of evaluation, equivalency can be broken into two categories:

- Variations in models: Separate TOE models/variations may include differences that could necessitate separate testing across each model. If there are no variations in any of the categories listed below, the models may be considered equivalent.
- Variations in TOE dependencies on the environment (e.g., OS/platform the product is tested on): The method a TOE provides functionality (or the functionality itself) may vary depending upon the environment on which it is installed. If there is no difference in the TOE-provided functionality or in the manner in which the TOE provides the functionality, the models may be considered equivalent.

Deleted: ¶

651 Determination of equivalency between models can result in several different testing outcomes.

Deleted: as described in section B.3.

652 If a set of TOE are determined to be equivalent, testing may be performed on a single variation of the TOE. However, if the TOE variations have security-relevant functional differences, each of the TOE models that exhibits either functional or structural differences must be separately tested. Generally speaking, only the difference between each variation of TOE must be separately tested. Other equivalent functionality may be tested on a representative model and not across multiple platforms.

653 If it is determined that a TOE operates the same regardless of the environment, testing may be performed on a single instance for all equivalent configurations. However, if the TOE is determined to provide environment-specific functionality, testing must take place in each environment for which a difference in functionality exists. Similar to the above scenario, only the functionality affected by environment differences must be retested.

Deleted: If a vendor

654 If a developer disagrees with the evaluator's assessment of equivalency, the Certification Body arbitrates between the two parties as to whether equivalency exists.

B.2 Evaluator guidance for determining equivalence

B.2.1 Strategy

Deleted: ¶

655 When performing the equivalency analysis, the evaluator should consider each factor independently. A factor may be any number of things at various levels

Moved (insertion) [205]

Deleted: <object><object><object>

Network Device Equivalency Considerations

of abstraction, ranging from the processor a device uses, to the underlying operating system and hardware platform a software application relies upon. Examples may be the various chip sets employed by the product, the type of network interface (different device drivers), storage media (solid state drive, spinning disk, EEPROM). It is important to consider how the difference in these factors may influence the TOE's ability to enforce the SFRs. Each analysis of an individual factor will result in one of two outcomes,

- For the particular factor, all variations of the TOE on all supported platforms are equivalent. In this case, testing may be performed on a single model in a single test environment and cover all supported models and environments.
- For the particular factor, a subset of the product has been identified to require separate testing to ensure that it operates identically to all other equivalent TOE. The analysis would identify the specific combinations of models/testing environments that needed to be tested.

656 Complete CC testing of the product would encompass the totality of each individual analysis performed for each of the identified factors.

B.2.2 Guidance for Network Devices

657 The following table provides a description of how an evaluator should consider each of the factors that affect equivalency between TOE model variations and across operating environments. Additionally, the table also identifies scenarios that will result in additional separate testing across models.

Factor	Same/Not Same	Evaluator guidance
Platform/Hardware Dependencies	Independent	If there are no identified platform/hardware dependencies, the evaluator shall consider testing on multiple hardware platforms to be equivalent.
	Dependencies	If there are specified differences between platforms/hardware, the evaluator must identify if the differences affect the cPP-specified security functionality or if they apply to non-cPP-specified functionality. If functionality specified in the cPP is dependent upon platform/hardware provided services, the product must be tested on each of the different platforms to be considered validated on that particular hardware combination. In these cases, the evaluator has the option of only re-testing the functionality dependent upon the platform/hardware provided functionality. If the differences only affect non-cPP-specified functionality, the variations may still be considered equivalent. For each

Deleted: <object>

Moved (insertion) [206]

Moved (insertion) [207]

Deleted: of the different platforms to

Deleted: <object><object><object>

Network Device Equivalency Considerations

Factor	Same/Not Same	Evaluator guidance
		difference the evaluator must provide an explanation of why the difference does or does not affect cPP-specified functionality.
Differences in TOE Software Binaries	Identical	If the model binaries are identical, the model variations shall be considered equivalent.
	Different	If there are differences between model software binaries, a determination must be made if the differences affect cPP-specified security functionality. If cPP-specified functionality is affected, the models are not considered equivalent and must be tested separately. The evaluator has the option of only retesting the functionality that was affected by the software differences. If the differences only affect non-PP specified functionality, the models may still be considered equivalent. For each difference the evaluator must provide an explanation of why the difference does or does not affect cPP specified functionality.
Differences in Libraries Used to Provide TOE Functionality	Same	If there are no differences between the libraries used in various TOE models, the model variations shall be considered equivalent.
	Different	If the separate libraries are used between model variations, a determination of whether the functionality provided by the library affects cPP-specified functionality must be made. If cPP-specified functionality is affected, the models are not considered equivalent and must be tested separately. The evaluator has the option of only retesting the functionality that was affected by the differences in the included libraries. If the different libraries only affect non-PP specified functionality, the models may still be considered equivalent. For each different library, the evaluator must provide an explanation of why the different libraries do or do not affect cPP specified functionality.
TOE Management Interface Differences	Consistent	If there are no differences in the management interfaces between various TOE models, the models variations shall be considered equivalent.
	Differences	If the product provides separate interfaces based on the model variation, a determination must be made of whether cPP-specified functionality can be configured by the different interfaces. If the interface differences affect cPP-specified

Deleted: <object>

Deleted: ¶

Deleted: validated on that particular hardware combination....

Moved up [207]: In these cases, the evaluator has the option of only re-testing the functionality dependent upon the platform/hardware provided functionality.

Deleted: If the differences only affect non-cPP-specified functionality, the variations may still be considered equivalent. For each

Deleted: cPP-specified

Deleted:

Deleted:

Deleted:

Deleted:

Deleted:

Deleted:

Deleted: ¶

Deleted: <object><object><object>

Network Device Equivalency Considerations

Factor	Same/Not Same	Evaluator guidance
		functionality, the variations are not considered equivalent and must be separately tested. The evaluator has the option of only retesting the functionality that can be configured by the different interfaces (and the configuration of said functionality). If the different management interfaces only affect non-PP specified functionality, the models may still be considered equivalent. For each management interface difference, the evaluator must provide an explanation of why the different management interfaces do or do not affect cPP specified functionality.
TOE Functional Differences	Identical	If the functionality provided by different TOE model variation is identical, the models variations shall be considered equivalent.
	Different	If the functionality provided by different TOE model variations differ, a determination must be made if the functional differences affect cPP- specified functionality. If cPP-specific functionality differs between models, the models are not considered equivalent and must be tested separately. In these cases, the evaluator has the option of only retesting the functionality that differs model-to-model. If the functional differences only affect non-cPP specified functionality, the model variations may still be considered equivalent. For each difference the evaluator must provide an explanation of why the difference does or does not affect cPP specified functionality.

Table 3: Evaluation Equivalency Analysis

B.3 Test presentation/Truth in advertising

658 In addition to determining what to test, the evaluation results and resulting Certification Report, must identify the actual module and environment combinations that have been tested. The analysis used to determine the testing subset may be considered proprietary and will only optionally be publicly included.

B.4 Evaluating additional components for a distributed TOE

659 In the case of a distributed TOE the Security Target will identify an evaluated configuration that consists of a number of separate components chosen by the

Deleted: <object>

Deleted: ¶

Deleted: Differences ... [61]

Deleted: Differences

Deleted: If the product provides separate interfaces based on the model variation, a determination must be made of whether cPP-specified functionality can be configured by the different interfaces. If the interface differences affect cPP-specified

Deleted:

Deleted:

Deleted: Section Break (Continuous)

¶

¶

Moved up [205]: Strategy ¶

Deleted: Column Break

Deleted: 1 -

Deleted: Section Break (Continuous)

¶

When performing the equivalency analysis, the evaluator should consider each factor independently. Each analysis of an individual factor will result in one of three outcomes. ¶

Moved up [7]: ¶

For

Moved up [206]: single model in a single test environment and cover all supported models and environments. ¶
For the particular factor, a subset of the product has been identified to require separate testing to ensure that it operates identically to all other equivalent TOE. The analysis would identify the specific combinations of models/testing environments that needed to be tested. ¶

Deleted: the particular factor, all variations of the TOE on all supported platforms are equivalent. In this case, testing may be performed on a ¶

¶

Deleted: For the particular factor, none of the variations of the TOE are equivalent and testing is therefore performed on all models and environments. ¶
Complete CC testing of the product would encompass the totality of each individual analysis performed for each of the identified factors. ¶

Deleted: testing

Deleted: <object><object><object>

Network Device Equivalency Considerations

Deleted: <object>

ST author, which collectively satisfy the requirements of the cPP. This evaluated configuration need not be the minimum set of components that could possibly meet the cPP (e.g. if the TOE is intended for large enterprise deployments then the evaluated configuration might include some redundancy in components in order to support expected connectivity and loads), but because this is the main configuration referred to in the ST and the evaluation, it is treated in this section as the minimum configuration of interest and is referred to here as the 'minimum configuration' as well as the 'evaluated configuration'.

660 In addition to the minimum configuration above, the ST may also identify (at the author's discretion, and subject to verification as described in this section) which TOE components can have instances added to an operational configuration without affecting the validity of the CC certification. The ST description may include constraints on how such components are added, including required and/or prohibited configurations of the components.

661 Extra instances of a TOE component must have the same hardware and software as the original component included in the evaluated configuration.

662 It is noted that undesirable configurations may be possible in the operational deployment of a TOE – such as allowing a TOE component to be managed from separate and potentially conflicting administration domains. However, the definition of 'undesirable' and of the risks involved in such cases will be specific to each operational environment and is therefore not treated as part of the evaluation. Correct and appropriate configuration of this sort remains a matter for expert network planning and design in the operational environment.

B.4.1 Evaluator Actions for Assessing the ST

B.4.1.1 TSS

663 The evaluator shall examine the TSS to identify any extra instances of TOE components allowed in the ST and shall examine the description of how the additional components maintain the SFRs to confirm that it is consistent with the role that the component plays in the evaluated configuration. For example: the secure channels used by the extra component for intra-TOE communications (FPT_ITT) and external communications (FTP_ITC) must be consistent, the audit information generated by the extra component must be maintained, and the management of the extra component must be consistent with that used for the original instance of the component in the minimum configuration.

B.4.2 Evaluator Actions for Assessing the Guidance Documentation

B.4.2.1 Guidance Documentation

664 The evaluator shall examine the description of the extra instances of TOE components in the guidance documentation to confirm that they are consistent with those identified as allowed in the ST. This includes confirmation that the result of applying the guidance documentation to configure the extra

Deleted: <object><object><object>

Network Device Equivalency Considerations

component will leave the TOE in a state such that the claims for SFR support in each component are as described in the ST and therefore that all SFRs continue to be met when the extra components are present.

665 The evaluator shall examine the secure communications described for the extra components to confirm that they are the same as described for the components in the minimum configuration (additional connections between allowed extra components and the components in the minimum configuration are allowed of course).

B.4.3 Evaluator Actions for Testing the TOE

B.4.3.1 Tests

666 The evaluator tests the TOE in the minimum configuration as defined in the ST (and the guidance documentation).

667 If the description of the use of extra components in the ST and guidance documentation identifies any difference in the SFRs allocated to a component, or the scope of the SFRs involved (e.g. if different selections apply to different instances of the component) then the evaluator tests these additional SFR cases that were not included in the minimum configuration.

668 In addition the evaluator tests the following aspects for each extra component that is identified as allowed in the distributed TOE:

- Communications: the evaluator follows the guidance documentation to confirm, by testing, that any additional connections introduced with the extra component and not present in the minimum configuration are consistent with the requirements stated in the ST (e.g. with regard to protocols and ciphersuites used). An example of such an additional connection would be if a single instance of the component is present in the minimum configuration and adding a duplicate component then introduces an extra communication between the two instances. Another example might be if the use of the additional components necessitated the use of a connection to an external authentication server instead of using locally stored credentials.
- Audit: the evaluator confirms that the audit records from different instances of a component can be distinguished so that it is clear which instance generated the record.
- Management: if the extra component manages other components in the distributed TOE then the evaluator shall follow the guidance documentation to confirm that management via the extra component uses the same roles and role holders for administrators as for the component in the minimum configuration.

Deleted: <object>

Deleted: <object><object><object>

Page 3: [1] Deleted	NiTC	2/7/19 11:44:00 AM
Page 22: [2] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [3] Moved to page 78 (Move #18)	NiTC	2/7/19 11:44:00 AM
Page 33: [3] Moved to page 78 (Move #18)	NiTC	2/7/19 11:44:00 AM
Page 33: [4] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [5] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [6] Moved to page 78 (Move #20)	NiTC	2/7/19 11:44:00 AM
Page 33: [6] Moved to page 78 (Move #20)	NiTC	2/7/19 11:44:00 AM
Page 33: [7] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [8] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [9] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [10] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [11] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [12] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [13] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [14] Moved to page 81 (Move #30)	NiTC	2/7/19 11:44:00 AM
Page 33: [14] Moved to page 81 (Move #30)	NiTC	2/7/19 11:44:00 AM
Page 33: [15] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [16] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [17] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [18] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [19] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [20] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [21] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [22] Deleted	NiTC	2/7/19 11:44:00 AM
Page 33: [23] Moved to page 83 (Move #40)	NiTC	2/7/19 11:44:00 AM
Page 33: [23] Moved to page 83 (Move #40)	NiTC	2/7/19 11:44:00 AM

Page 33: [24] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 33: [25] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 33: [26] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 33: [27] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 33: [28] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 33: [29] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 33: [30] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
a) Page 33: [30] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
b) Page 33: [30] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
c) Page 33: [30] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
d) Page 33: [30] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
e) Page 35: [31] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 35: [32] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 35: [33] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 35: [34] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 36: [35] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
144 Page 36: [36] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
145 Page 36: [37] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
Page 36: [38] Deleted	NiTC	2/7/19 11:44:00 AM
▼		
146 Page 36: [39] Deleted	NiTC	2/7/19 11:44:00 AM

147

Page 36: [39] Deleted NiTC 2/7/19 11:44:00 AM

148

Page 36: [40] Deleted NiTC 2/7/19 11:44:00 AM

2.4.1

Page 36: [41] Deleted NiTC 2/7/19 11:44:00 AM

Page 36: [42] Deleted NiTC 2/7/19 11:44:00 AM

Page 36: [43] Deleted NiTC 2/7/19 11:44:00 AM

2.4.2

Page 36: [44] Deleted NiTC 2/7/19 11:44:00 AM

2.4.3

Page 36: [45] Deleted NiTC 2/7/19 11:44:00 AM

2.4.4

Page 36: [46] Deleted NiTC 2/7/19 11:44:00 AM

Page 36: [47] Deleted NiTC 2/7/19 11:44:00 AM

Page 36: [48] Deleted NiTC 2/7/19 11:44:00 AM

Page 36: [49] Deleted NiTC 2/7/19 11:44:00 AM

Page 36: [50] Deleted NiTC 2/7/19 11:44:00 AM

Page 36: [51] Deleted NiTC 2/7/19 11:44:00 AM

149

Page 36: [51] Deleted NiTC 2/7/19 11:44:00 AM

150

Page 36: [51] Deleted NiTC 2/7/19 11:44:00 AM

151

Page 36: [51] Deleted NiTC 2/7/19 11:44:00 AM

152

Page 36: [51] Deleted NiTC 2/7/19 11:44:00 AM

153

Page 36: [52] Deleted NiTC 2/7/19 11:44:00 AM

Page 36: [53] Deleted NiTC 2/7/19 11:44:00 AM

154

Page 36: [53] Deleted NiTC 2/7/19 11:44:00 AM

155

Page 36: [53] Deleted NiTC 2/7/19 11:44:00 AM

156

Page 36: [53] Deleted NiTC 2/7/19 11:44:00 AM

157

Page 36: [53] Deleted NiTC 2/7/19 11:44:00 AM

158

Page 117: [54] Deleted NiTC 2/7/19 11:44:00 AM

Page 124: [55] Deleted NiTC 2/7/19 11:44:00 AM

Page 124: [56] Deleted NiTC 2/7/19 11:44:00 AM

Page 124: [57] Deleted NiTC 2/7/19 11:44:00 AM

Page 124: [58] Deleted NiTC 2/7/19 11:44:00 AM

Page 124: [59] Deleted NiTC 2/7/19 11:44:00 AM

Page 139: [60] Deleted NiTC 2/7/19 11:44:00 AM

Page 143: [61] Deleted NiTC 2/7/19 11:44:00 AM